This document is made available electronically by the Minnesota Legislative Reference Library as part of an ongoing digital archiving project. http://www.leg.state.mn.us/lrl/lrl.asp





# **CIVIL EAST CONSTRUCTION**

# VOLUME 10 **TRAFFIC / LIGHTING**

THE PROPOSED SOUTHWEST LRT PROJECT IS NOT FINAL BUT IS STILL UNDER ENVIRONMENTAL REVIEW AND THE PROJECT IS SUBJECT TO CHANGE. THESE PLANS ARE NOT FINAL.

THE COUNCIL, THROUGH THE DEVELOPMENT OF THESE PLANS, DOES NOT INTEND THAT THEY WILL PREJUDICE OR COMPROMISE ANY STATE OR FEDERAL ENVIRONMENTAL REVIEW OR OTHER LEGAL REQUIREMENTS. THESE PLANS DO NOT LIMIT THE PROJECT DESIGN ALTERNATIVES OR MITIGATIVE MEASURES THAT THE COUNCIL MAY UNDERTAKE IF THE PROPOSED SWLRT PROJECT PROCEEDS TO CONSTRUCTION.

THE COUNCIL WILL NOT TAKE FINAL ACTION ON THIS MATTER UNLESS THE COUNCIL PROCEEDS WITH THE PROJECT AFTER THE FTA'S RECORD OF DECISION AND THE COUNCIL'S DETERMINATION OF ADEQUACY.

THIS RECORD MAY CONTAIN SENSITIVE SECURITY INFORMATION THAT IS CONTROLLED UNDER 49 CFR PARTS 15 WARNING: AND 1520. NO PART OF THIS RECORD MAY BE DISCLOSED TO PERSONS WITHOUT A "NEED TO KNOW", AS DEFINED IN 49 CFR PARTS 15 AND 1520. EXCEPT WITH THE WRITTEN PERMISSION OF THE ADMINISTRATOR OF THE TRANSPORTATION SECURITY ADMINISTRATION OR THE SECRETARY OF TRANSPORTATION. UNAUTHORIZED RELEASE MAY RESULT IN CIVIL PENALTY OR OTHER ACTION. FOR U.S. GOVERNMENT AGENCIES, PUBLIC DISCLOSURE IS GOVERNED BY 5 U.S.C. 552 AND 49 CFR PARTS 15 AND 1520.

60% SUBMISSION DATE: 09/28/15


PLAN PACKAGE INDEX / DESCRIPTION
CIVIL EAST CONSTRUCTION
/OLUME 1 - EXISTING CONDITIONS
/OLUME 2 - CIVIL
/OLUME 3 - TRACKWORK
/OLUME 4A - BRIDGES
/OLUME 4B - BRIDGES
/OLUME 5 - TUNNELS
/OLUME 6 - RETAINING WALLS
/OLUME 7 - UTILITIES
/OLUME 8 - DRAINAGE
/OLUME 9 - URBAN DESIGN / LANDSCAPE
/OLUME 10 - TRAFFIC / LIGHTING
/OLUME 11A - STATIONS
/OLUME 11B - STATIONS
/OLUME 12 - SYSTEMS



International control         Laborational contro         Laborational control         Laboratio			CIVIL EAST					CIVIL EAST					CIVIL EAST	
	SHT #	SHEET NAME		STATION	STATION REV	SHT #	SHEET NAME		STATION STAT	TION REV	SHT #	SHEET NAME		N STATION REV
									5+00 11+	+50				
	1													
	2													
	3													
Image: 1	•													
	7					75	E4-TFC-SIGN-STRIPE-018		60+00 67+	+50				
1     1 <td>0</td> <td></td> <td>SIGNING AND STRIPING HENNEPIN COUNTY NOTES</td> <td></td> <td></td> <td>76</td> <td>E4-TFC-SIGN-STRIPE-019</td> <td>BORDER AVE SIGNING AND STRIPING</td> <td>67+50 73+</td> <td>+25</td> <td>149</td> <td>EO-TFC-SIG-DTL-010</td> <td>TRAFFIC SIGNAL MINNEAPOLIS DETAIL SHEET 2</td> <td></td>	0		SIGNING AND STRIPING HENNEPIN COUNTY NOTES			76	E4-TFC-SIGN-STRIPE-019	BORDER AVE SIGNING AND STRIPING	67+50 73+	+25	149	EO-TFC-SIG-DTL-010	TRAFFIC SIGNAL MINNEAPOLIS DETAIL SHEET 2	
	0	EO-TFC-SIGN-STRF-DTL-02	SHEET 1			77	E4-TFC-SIGN-STRIPE-020	5TH AVE N SIGNING AND STRIPING				EO-TFC-SIG-DTL-011	TRAFFIC SIGNAL MINNEAPOLIS DETAIL SHEET 3	
	9	EO-TFC-SIGN-STRP-DTL-03												
	-													
									106+00 113	3+00				
2)         0.1.0000000000000000000000000000000000	15													
	16	EO-TFC-SIGN-STRP-DTL-10	SIGNING AND STRIPING MNDOT DETAIL SHEET 3			86	E1-TFC-TRL-SIGN-005	CEDAR LAKE LRT REGIONAL TRAIL SIGNING	133+50 139	9+50	159	EO-TFC-SIG-DTL-020	TRAFFIC SIGNAL MINNEAPOLIS DETAIL SHEET 12	
	17	EO-TFC-SIGN-STRP-DTL-11	SIGNING AND STRIPING MNDOT DETAIL SHEET 4			87	E1-TFC-TRL-SIGN-006	CEDAR LAKE LRT REGIONAL TRAIL SIGNING	139+50 146	6+00	160	EO-TFC-SIG-DTL-021	TRAFFIC SIGNAL MINNEAPOLIS DETAIL SHEET 13	
2       UNINCENTIAL STATUS       NUM DESCRIPTION INTERCENTION ALL       INTERCENTION ALL       NUM DESCRIPTION ALL														
B         Control work														
B         C + TOCADA OFFICADE         ID OF LABORATING OF         ID OF					18+00									
<i>a a</i> <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>														
a)         b)         b)<														
0         1			,											
St.         Concentration         No. Note:         Concentration         No. Note:         Concentration         No. Note:         No.	29	E1-TFC-SIGN-STRIPE-005	5TH AVE S SIGNING AND STRIPING	10+00	17+50	99		CEDAR LAKE LRT REGIONAL TRAIL SIGNING	227+00 234	4+00	172	E2-TFC-SIG-INX-001	SIGNAL PLAN PLAN SHEET LAYOUT SHEET 2	
2)       Periodic-difference       Priod       Disk       D	30	E1-TFC-SIGN-STRIPE-006	EB CSAH 3 (EXCELSIOR BLVD) SIGNING AND STRIPING	136+00	143+00	100	E2-TFC-TRL-SIGN-006	CEDAR LAKE LRT REGIONAL TRAIL SIGNING	234+00 241	1+00	173	E3-TFC-SIG-INX-001	SIGNAL PLAN PLAN SHEET LAYOUT SHEET 3	
0       b)	31	E1-TFC-SIGN-STRIPE-007	NB CSAH 20 (BLAKE RD) SIGNING AND STRIPING	10+00	18+00	101	E2-TFC-TRL-SIGN-007	CEDAR LAKE LRT REGIONAL TRAIL SIGNING	241+00 248	3+00	174	E4-TFC-SIG-INX-001	SIGNAL PLAN PLAN SHEET LAYOUT SHEET 4	
Display         Display <t< td=""><td></td><td></td><td></td><td>-</td><td></td><td></td><td></td><td>CEDAR LAKE LRT REGIONAL TRAIL SIGNING</td><td></td><td></td><td>175</td><td>E1-TEC-SIG-8TH-001</td><td></td><td></td></t<>				-				CEDAR LAKE LRT REGIONAL TRAIL SIGNING			175	E1-TEC-SIG-8TH-001		
				-										
No.         Description         How Source is allowed and previne         How Source is allowed and previne and previne         How Source is allowed and previne and previne         How Source is allowed and previne and pre				_							176	E1-TFC-SIG-8TH-002		
B         Distribution         Distribution <thdistribution< th="">         Distribution</thdistribution<>											177	E1-TFC-SIG-8TH-003		
By Decision Field         Control State				_										
											178	E1-TFC-SIG-5TH-001		
00         PU-20024 SUBJECT         <				10,00	17:50									
11       CPTTO-GRUGATIONE CV       VOID NITE ALS BOUND AND STREPTION       2:000       FIG.00	40	E2-TFC-SIGN-STRIPE-006(A)									179	E1-TFC-SIG-5TH-002		
41       0.21       <	41	E2-TFC-SIGN-STRIPE-007	YOSEMITE AVE S SIGNING AND STRIPING	2+00.00	6+00.00	112	E2-TFC-TRL-SIGN-018				400		SIGNAL PLAN - SIGNAL SYSTEM "B" CSAH 3 (EXCELSIOR	
44       E-PTC-630E-8710F-000       CHONNEN AND STREPTING       110       P-PTC-630E-8710F-000       Strepting - Strepting	42	E2-TFC-SIGN-STRIPE-008	BELTLINE BLVD SIGNING AND STRIPING	112+00	118+00	113	E2-TFC-TRL-SIGN-019	CEDAR LAKE LRT REGIONAL TRAIL SIGNING	325+00 332	2+00	180	E1-TFC-SIG-5TH-003	BLVD) AND 5TH AVE S FOR INFORMATION ONLY	
46       BUTC dials STIREP22       CHOWNEN ARE 21 WISTER TO BORNAN ADD STIREPING       0+00       110       BUTC dials All and the rescale       State 2000       State 200	43	E2-TFC-SIGN-STRIPE-009	BELTLINE BLVD SIGNING AND STRIPING	118+00	121+38	114	E2-TFC-TRL-SIGN-020	CEDAR LAKE LRT REGIONAL TRAIL SIGNING	332+00 339	9+00			SIGNAL PLAN - SIGNAL SYSTEM "C" CSAH 3	
41       51/FC 30004 SINPEGU       40001       21/46       17/1       51/FC 30004 LARE LIVE RECOMME HAND SINPEND       47/10       50/FC 30004 LARE LIVE RECOMME HAND SINPEND       50/FC 30004 LARE LIVE RECOME HAND SINPEND       50/FC 300004 LARE LIVE											181	E1-TFC-SIG-EXC-001	(EXCELSIOR BLVD) AND MILWAUKEE ST/JACKSON AVE	
97       Select-Science-State-State       2900 ST Science AND STREPTION       9400 ST FERSO       9400 ST FERSO       1000 ST FERSO       9410 ST FERSO	10												N	
44       64       6547 CSENATTER-640       CSM47 2011 AKE 57 SIGNERA AND STREPTING       6-20       10       10       ESTFC/SIGNATTER-640       CSM47 2011 AKE 57 SIGNERA AND STREPTING       6-20       10       ESTFC/SIGNATTER-640       Strepting ALLARE ET REGIONAL TRUE SIGNERA       30640       30740       113       E-111C-SIGNATURE 400       Strepting ALLARE ET REGIONAL TRUE SIGNERA       Strepting ALLARE ET REGIONAL TRUE SIGNERA       30640       30740       113       E-111C-SIGNATURE 400       Strepting ALLARE ET REGIONAL TRUE SIGNERA       Strepting ALLARE ET REGIONAL TRUE SIGNERA       30640       30740       113       E-111C-SIGNATURE 400       Strepting ALLARE ET REGIONAL TRUE SIGNERA       Strepting ALLARE ET REGIONAL TRUE SIGNERAL ALLARE ET REGIONAL TRUE SIGNERAL       Strepting ALLARE ET REGIONAL TRUE SIGNERAL       Streping ALLARE ET REGIONAL TR											400			
											182	E1-TFC-SIG-EXC-002		
90       Extresponsitive-out       CSAH 25 W LARE 57 19 GANN AND STRIPTING       19 d0       19 d0       12 EXTERNATION CON       19 d0       19 d0       12 EXTERNATION CON       19 d0			, ,											
State       Extression       Schul State       Schul State       Schul State       NPGR NORMATED ONLY         State       Extression       State       St											183	E1-TEC-SIG-EXC-003		
12       ESTEC-SIGN-STRIPE-00       CSAM 3 EXCRESION RLVD JISUMS AND STRIPMO       27-00       34-00       12       ESTEC-SIGN-STRIPE-01       BURNEARING STRIPE-01       ESTEC-SIGN-STRIPE-01       BURNEARING STRIPE-01       BURNEARIN			, , , , , , , , , , , , , , , , , , ,											
51       ExTC-SIGLASTRIPE-00       CEDAR LARE PARY SIGLANCE ADD STRIPING       44-50       54-00       12       ExTC-SIGLASTRIPE-01       V2105       V2105 <td></td> <td></td> <td>, , , , , , , , , , , , , , , , , , ,</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>SIGNAL PLAN - SIGNAL SYSTEM "C" CSAH 3</td> <td></td>			, , , , , , , , , , , , , , , , , , ,										SIGNAL PLAN - SIGNAL SYSTEM "C" CSAH 3	
64       EstTC-SIGN-STRIPE-011       BURNAAR DS SIGNIG AND STRIPING       147 co.00       125 co.00											184	E1-TFC-SIG-EXC-004		
66       E3-TFC_SIGN_STRIPE-01       W 2411 STT1:0AM3 AVE \$SIGNNG AND STRIPING       127       E3-TFC_TR_SIGN-01       KENLWORTH TRAL SIGNING       422-r0       115       E1-TFC_SIG_PRC.00       KEXCELSIOR BLVD, NAMP PIECE AVE       SOURCE AVE       SOURCE BLVD, NAMP PIECE AVE       SOURCE BLVD, PIECE AVE       SOURCE BLVD, PIECE AVE       SOURCE BLVD, PIECE AVE ED       SOURCE BLVD, PIEC	54	E3-TFC-SIGN-STRIPE-011	BURNHAM RD SIGNING AND STRIPING	147+00.00	152+00.00	125	E3-TFC-TRL-SIGN-010	KENILWORTH TRAIL SIGNING	408+00 415	5+00			N FOR INFORMATION ONLY	
06       E3/FC_SIGNSTRIFE-013       W 24115 (11) (00AA AVE \$2 BIONNG AND STRIPING       127       E3/FC_SIGNSTRIFE-011       42/F00       42/F00       42/F00       E0/FC_SIGNSTRIFE-011       EXAMPLE STRIPE-011       EXAMPLE STRIPE-012       EXAMPLE STRIPE-022       EXAMPLE STRIPE-0222       EXAMPLE			W 21ST ST SIGNING AND STRIPING	11+00				KENILWORTH TRAIL SIGNING			185	E1-TEC-SIG-PRC-001		
58       E4-TFC-SGIASTRIPE-001       SWX2ATA BLVD SIGNING AND STRIPING       1+00       8+00       1-22       E3-TFC-TRL-SIGN-14       Kell-WORTH TRAL BIONING       43+16.31       43+6.90       1-86       E1-TFC-SIG-ARC-002       EXECUSION BLVD, AND PRENCE AVE EQUIPMENT       Image: Control of the control o				20+00	26+67.59								(EXCELSIOR BLVD) AND PIERCE AVE	
64-TFC-SIGN-STRIPE-003       SWY2ATA BLV0CSAH 2 (PENN AVE 5) SIGNING AND       9+00       15+50       100       E3-TFC-TR_SIGNING       441+50       441+50       441+50       441+50       Significance       S	01													
59       E4-TFC-SIGN-STRIPE-002       STRIPING       STRIPING       STRIPING       SIGNAL PLANT-SIGNAL SYSTEM 'E' CSAH 20 (BLAKE RD in the construction of the constructio	58	E4-TFC-SIGN-STRIPE-001		1+00	8+00						186	E1-TFC-SIG-PRC-002		
e0       EATEC-SIGNATSRIPE-003       CSAH 2 (PEN NAVE 5) SIGNING AND STRIPING       152       EATEC-TRL-SIGNAD2       KENLUNOSTH TRAL/GONNO       449-50       459-50       187       E1-TEC-SIGALSRUP       N) AND 2ND ST NE	59	E4-TFC-SIGN-STRIPE-002		8+00	15+50									
61       EATTC-SIGNASTRIPE-004       GSAH 2 (PENN AVE \$) SIGNING AND STRIPING       23+50       90+50       133       E4-TFC-TR_SIGNAD03       KENLWORTH TRAILCEDAR LAKE TRAIL SIGNING       451+50       188       E1-TFC-SIG-BLK-002       SIGNAL PLAN - SIGNAL SYSTEM "C SAH 20 BLAKE RD       N) AND 2ND ST NETON LSS SIGNING AND STRIPING       0+00       5+00       133       E4-TFC-TR_SIGNAD04       CEDAR LAKE TRAIL SIGNING       451+50       461+50       469+00       188       E1-TFC-SIG-BLK-002       SIGNAL PLAN - SIGNAL SYSTEM "C SAH 20 BLAKE RD       N) AND 2ND ST NETON LSS SIGNING AND STRIPING       0+00       5+00       135       E4-TFC-TR_SIGNAD04       CEDAR LAKE TRAIL SIGNING       461+50       469+00       188       E1-TFC-SIG-BLK-002       SIGNAL PLAN - SIGNAL SYSTEM "C SAH 20 BLAKE RD       N) AND 2ND ST NE FOR INFORMATION ONLY DISTNETS *C SAH 20 BLAKE RD       N) AND 2ND ST NE FOR INFORMATION ONLY DISTNETS *C SAH 20 BLAKE RD       N) AND 2ND ST NE FOR INFORMATION ONLY DISTNETS *C SAH 20 BLAKE RD       N) AND 2ND ST NE FOR INFORMATION ONLY DISTNETS *C SAH 20 BLAKE RD       N) AND 2ND ST NE FOR INFORMATION ONLY DISTNETS *C SAH 20 BLAKE RD       N) AND 2ND ST NE FOR INFORMATION ONLY DISTNETS *C SAH 20 BLAKE RD       N) AND 2ND ST NE FOR INFORMATION ONLY DISTNETS *C SAH 20 BLAKE RD       N) AND 2ND ST NE FOR INFORMATION ONLY DISTNETS *C SAH 20 BLAKE RD       N) AND 2ND ST NE FOR INFORMATION ONLY DISTNETS *C SAH 20 BLAKE RD       N) AND 2ND ST NE FOR INFORMATION ONLY DISTNETS *C SAH 20 BLAKE RD       N) AND 2ND ST NE FOR INFORMATION ONLY DISTNETS *C SAH 20 BLAKE RD	60			15+50	23+50						187	E1-TFC-SIG-BLK-001		
62       E4/TFC-SIG-NSTRIPE-005       PENN STATION KUSS AND RUES SIGNING AND STRIPING       0       134       E4-TFC-TRL-SIGN-004       CEDAR LAKE TRAIL SIGNING       461+00       188       E1-TFC-SIG-BLR-002       N) AND 2ND STN E EQUIPMENTS CSAHEDULE       0         63       E4-TFC-SIGN-STRIPE-005       VAN WHITE STATION ACCESS SIGNING AND STRIPING       0+00       5+00       5+00       648       135       E4-TFC-TRL-SIGN-005       CEDAR LAKE TRAIL SIGNING       468+00       478+02       4       189       E1-TFC-SIG-BLR-003       N) AND 2ND STN E FOR INFORMAL SYSTEM "E" CSAH 20 (BLAKE RD N)       N) AND 2ND STN E FOR INFORMAL SYSTEM "E" CSAH 20 (BLAKE RD N)       10       1				_									· ·	
63       E4-TFC-SIGN-STRIPE-006       VAN WHITE STATION ACCESS SIGNING AND STRIPING       0+00       5+00       135       E4-TFC-TRL-SIGN-005       CEDAR LAKE TRAIL SIGNING       469+00       474+50       199       E1-TFC-SIGN-STRIPE-007       N) AND 2ND THE PAR INFORMATION ONLY       N) AND 2ND THE PAR INFORMATION											188	E1-TFC-SIG-BLK-002		
64       E4-TFC-SIGN-STRIPE-007       VAN WHITE STATION ACCESS SIGNING AND STRIPING       5+00       8+68       136       E4-TFC-TRL-SIGN-066       CEDAR LAKE TRAIL SIGNING       474+50       478+20.24       199       E1-TFC-SIGN-STRIP-603       N) AND 2ND ST NE FOR INFORMATION ONLY       No AND 2ND 2ND ST NE FOR INFORMATION ONLY       No AND 2ND 2ND ST NE FOR INFORMATION ONLY       No AND 2ND 2ND 2ND 2ND 2ND 2ND 2ND 2ND 2ND 2					5+00								·	
66       E4-TFC-SIGN-STRIPE-008       DUNWOODY BLVD SIGNING AND STRIPING       10+00       17+00       137       E4-TFC-TRL-SIGN-007       CEDAR LAKE TRAIL SIGNING       449+71       504+26       190       E2-TFC-SIG-OXF-001       SIGNAL PLAN-SIGNAL SYSTEM "F" OXFORD ST AND LOUISIANA AVE ST       100       E2-TFC-SIG-OXF-001       SIGNAL PLAN-SIGNAL SYSTEM "F" OXFORD ST AND LOUISIANA AVE ST       100       E2-TFC-SIG-OXF-001       SIGNAL PLAN-SIGNAL SYSTEM "F" INTERSECTION       100       E2-TFC-SIG-OXF-002       SIGNAL PLAN-SIGNAL SYSTEM "F" INTERSECTION       100       E2-TFC-SI	••										189	E1-TFC-SIG-BLK-003		
66       E4-TFC-SIGN-STRIPE-009       DUMWOODY BLVD SIGNING AND STRIPING       17+00       21+61       138       E4-TFC-TRL-SIGN-008       NORTH CEDAR LAKE TRAIL SIGNING       550+10       550+10       550+10       100       E2-TFC-SIG-AR-OUT       LOUISIANA AVE S         67       E4-TFC-SIGN-STRIPE-010       VAN WHITE MEMORIAL BLVD SIGNING AND STRIPING       726+00       733+00       139       E4-TFC-TRL-SIGN-009       LUCE LINE REGIONAL TRAIL SIGNING       3+42       6+26       191       E2-TFC-SIG-OXF-002       Signal PLAN - SIGNAL SYSTEM "F" INTERSECTION	65										100		SIGNAL PLAN - SIGNAL SYSTEM "F" OXFORD ST AND	
68       E4-TFC-SIGN-STRIPE-011       VAN WHITE MEMORIAL BLVD SIGNING AND STRIPING       733+00       735+00       140       E0-TFC-SIG-DTL-001       TRAFFIC SIGNAL NOTES AND LEGEND       191       E2-TPC-SIG-OX002       Notes         No.       Date       BY       CHECK DESIGN REVISION / SUBMITTAL       Image: Check Design Revision / Submittal <td>66</td> <td>E4-TFC-SIGN-STRIPE-009</td> <td>DUNWOODY BLVD SIGNING AND STRIPING</td> <td>17+00</td> <td>21+61</td> <td>138</td> <td>E4-TFC-TRL-SIGN-008</td> <td>NORTH CEDAR LAKE TRAIL SIGNING</td> <td>550+10 555+</td> <td>+11.31</td> <td>190</td> <td>L2-1FG-SIG-OAF-001</td> <td></td> <td></td>	66	E4-TFC-SIGN-STRIPE-009	DUNWOODY BLVD SIGNING AND STRIPING	17+00	21+61	138	E4-TFC-TRL-SIGN-008	NORTH CEDAR LAKE TRAIL SIGNING	550+10 555+	+11.31	190	L2-1FG-SIG-OAF-001		
68       E4-TPC/SIGN/STRIPE-011       VAN WHITE MEMORIAL BLVD SIGNING AND STRIPING       733+00       735+00       140       E0-TPC/SIG-DIL-001       TRAFFIC SIGNAL NOTES AND LEGEND       NOTES         NO.       Date       BY       CHECK/DESIGN REVISION/SUBMITTAL       Image: Clock and striping       Clock and striping       733+00       735+00       140       E0-TPC/SIG-DIL-001       TRAFFIC SIGNAL NOTES AND LEGEND       Image: Clock and striping	0,								3+42 6+	+26	191	E2-TEC-SIG-OXE-002		
AECON     AECON     AECON     AECON     AECON     AECON     AECON     AECON     AECON     CIVIL EAST - VOLUME 10     TRAFFIC / LIGHTING   VOLUME INDEX OF PLAN SHEETS     SHEET 1     Discipline:     SHEET NAME:	68	E4-TFC-SIGN-STRIPE-011	VAN WHITE MEMORIAL BLVD SIGNING AND STRIPING	733+00	735+00	140	EO-TFC-SIG-DTL-001	TRAFFIC SIGNAL NOTES AND LEGEND					NOTES	
AECON     AECON     AECON     AECON     AECON     AECON     AECON     AECON     AECON     CIVIL EAST - VOLUME 10     TRAFFIC / LIGHTING   VOLUME INDEX OF PLAN SHEETS     SHEET 1     Discipline:     SHEET NAME:	NO.	DATE BY CHECK DESIGN REVISI	DN / SUBMITTAL											CULLT
AECON													CIVIL EAST - VOLUME 10	SHEET
ALCOM       SOUTHWEST       VOLUME INDEX OF PLAN SHEETS       SHEET 1         VOLUME INDEX OF PLAN SHEETS       SHEET 1       S											_			_
METROPOLITAN     SOUTHWEST       SOUTHWEST     SHEET 1       Discipline:     SHEET NAME:														2
METROPOLITAN     SOUTHWEST       SOUTHWEST     SHEET 1       Discipline:     SHEET NAME:										1 11 4 200			UME INDEX OF PLAN SHEFTS	
METROPOLITAN     COUNTING       COUNTING     SHEET NAME:									<u>50011</u>	HWES				OF
COV/ CLIDNISCION OD/20/4 F								METROPOLIT	AN Green Line Line	r=ach3bh			SHEEL 1	
60% SUBMISSION - 09/28/15 GENERAL E0-TFC-IDX - 001									1 L			DISCIPLINE:	SHEET NAME:	266
							60% SUBMISS	UN - U9/28/15				GE	NERAL E0-TFC-IDX	. = 001

By: IDX.dwg GEN LIST\E1 WING V: \3400\_ADC\CAD\CAD MANAGEMENT\DRA 09:07 25 2015

		CIVIL EAST				CIVIL EAST				CIVIL EAST	
SHT #	SHEET NAME	SHEET DESCRIPTION VOLUME 10 - TRAFFIC / LIGHTING (cont'd)	STATION STATION REV	SHT #	SHEET NAME	SHEET DESCRIPTION SIGNAL PLAN - SIGNAL SYSTEM "Q" CSAH 3	STATION STATION	REV SHT #	SHEET NAME	SHEET DESCRIPTION	STATION STATION R
192	E2-TFC-SIG-OXF-003	SIGNAL PLAN - SIGNAL SYSTEM "F" OXFORD ST AND LOUISIANA AVE S FOR INFORMATION ONLY		225	E3-TFC-SIG-EXC-009	(EXCELSIOR BLVD) AND MARKET PLAZA FOR INFORMATION ONLY					
193	E2-TFC-SIG-TH7W-001	SIGNAL PLAN - SIGNAL SYSTEM "G" TH 7 WB RAMPS AND WOODDALE AVE S		226	E3-TFC-SIG-CED-001	SIGNAL PLAN - FLASHER SYSTEM "R" CEDAR LAKE PKWY AND KENILWORTH TRAIL					
194	E2-TFC-SIG-TH7W-002	SIGNAL PLAN - SIGNAL SYSTEM "G" TH 7 WB RAMPS AND WOODDALE AVE S INTERSECTION NOTES		227	E3-TFC-SIG-CED-002	SIGNAL PLAN - FLASHER SYSTEM "R" CEDAR LAKE PKWY AND KENILWORTH TRAIL EQUIPMENT SCHEDULE					
195	E2-TFC-SIG-TH7W-003	SIGNAL PLAN - SIGNAL SYSTEM "G" TH 7 WB RAMPS AND WOODDALE AVE S TYPE "D" SIGN DETAILS		228	E4-TFC-SIG-ROY-001	SIGNAL PLAN - SIGNAL SYSTEM "S" ROYALSTON AVE AND HOLDEN ST					
196	E2-TFC-SIG-TH7W-004	SIGNAL PLAN - SIGNAL SYSTEM "G" & "H" TH 7 WB & EB RAMPS AND WOODDALE AVE S FOR INFORMATION		229	E4-TFC-SIG-ROY-002	SIGNAL PLAN - SIGNAL SYSTEM "S" ROYALSTON AVE AND HOLDEN ST EQUIPMENT SCHEDULE					
197	E2-TFC-SIG-TH7E-001	ONLY SIGNAL PLAN - SIGNAL SYSTEM "H" TH7 EB RAMPS AND	)	230	E4-TFC-SIG-7TH-001	SIGNAL PLAN - SIGNAL SYSTEM "T" 7TH ST N & 5TH AVE N					
198	E2-TFC-SIG-TH7E-002	WOODDALE AVE S SIGNAL PLAN - SIGNAL SYSTEM "H" TH7 EB RAMPS AND	)	231	E4-TFC-SIG-7TH-002	SIGNAL PLAN - SIGNAL SYSTEM "T" 7TH ST N & 5TH AVE N EQUIPMENT SCHEDULE					
199	E2-TFC-SIG-TH7E-003	WOODDALE AVE S INTERSECTION NOTES SIGNAL PLAN - SIGNAL SYSTEM "H" TH7 EB RAMPS AND WOODDALE AVE O THE INTERNAL DETAILS	)	232	E4-TFC-SIG-DUN-001	SIGNAL PLAN - SIGNAL SYSTEM "U" DUNWOODY BLVD AND PARADE STADIUM DR					
200	E2-TFC-SIG-WDL-001	WOODDALE AVE S TYPE "D" SIGN DETAILS SIGNAL PLAN SIGNAL SYSTEM "I" WOODDALE AVE S		233	E4-TFC-SIG-DUN-002	SIGNAL PLAN - SIGNAL SYSTEM "U" DUNWOODY BLVD AND PARADE STADIUM DR EQUIPMENT SCHEDULE					
201	E2-TFC-SIG-WDL-002	AND W 36TH ST SIGNAL PLAN SIGNAL SYSTEM "I" WOODDALE AVE S		234	E4-TFC-SIG-DUN-003	SIGNAL PLAN - SIGNAL SYSTEM "U" DUNWOODY BLVD AND PARADE STADIUM DR FOR INFORMATION ONLY					
202	E2-TFC-SIG-WDL-003	AND W 36TH ST SIGNAL PLAN SIGNAL SYSTEM "I" WOODDALE AVE S		235 236	E1-TFC-INT-01-001 E2-TFC-INT-01-001	INTERCONNECT PLAN INTERCONNECT PLAN					
203	E2-TFC-SIG-WDL-004	AND W 36TH ST FOR INFORMATION ONLY SIGNAL PLAN SIGNAL SYSTEM "I" WOODDALE AVE S		237 238	E2-TFC-INT-01-002 E4-TFC-INT-01-001	INTERCONNECT PLAN INTERCONNECT PLAN					
		AND W 36TH ST FOR INFORMATION ONLY SIGNAL PLAN - SIGNAL SYSTEM "J" CSAH 25 AND				LIGHTING					
204	E2-TFC-SIG-OTT-001	BELTLINE BLVD/OTTAWA AVE SIGNAL PLAN - SIGNAL SYSTEM "J" CSAH 25 AND		239 240	E1-HOP-ELE-PLN-101 E1-HOP-ELE-PLN-102	ELECTRICAL SITE PLAN (1 OF 2) ELECTRICAL SITE PLAN (2 OF 2)					
205	E2-TFC-SIG-OTT-002	BELTLINE BLVD/OTTAWA AVE EQUIPMENT SCHEDULE		240 241 242	E1-BLK-ELE-PLN-102 E1-BLK-ELE-PLN-101 E1-BLK-ELE-PLN-102	ELECTRICAL SITE PLAN (2 OF 2) ELECTRICAL SITE PLAN (1 OF 2) ELECTRICAL SITE PLAN (2 OF 2)					
206	E2-TFC-SIG-OTT-003	SIGNAL PLAN - SIGNAL SYSTEM "J" CSAH 25 AND BELTLINE BLVD/OTTAWA AVE FOR INFORMATION ONLY SIGNAL PLAN - SIGNAL SYSTEM "K" BELTLINE BLVD AT		242 243 244	E2-LOU-ELE-PLN-102 E2-LOU-ELE-PLN-101 E2-LOU-ELE-PLN-102	ELECTRICAL SITE PLAN (2 OF 2) ELECTRICAL SITE PLAN (1 OF 2) ELECTRICAL SITE PLAN (2 OF 2)					
207	E2-TFC-SIG-BLT-001	SIGNAL PLAN - SIGNAL STSTEM 'K' BELTLINE BLVD AT TRACK CROSSING SIGNAL PLAN - SIGNAL SYSTEM 'K'' BELTLINE BLVD AT		245 246	E2-WDL-ELE-PLN-101 E2-BLT-ELE-PLN-101	ELECTRICAL SITE PLAN ELECTRICAL SITE PLAN ELECTRICAL SITE PLAN (1 OF 3)					
208	E2-TFC-SIG-BLT-002	SIGNAL PLAN - SIGNAL STSTEM & DELILINE BLVD AT TRACK CROSSING INTERSECTION NOTES SIGNAL PLAN - SIGNAL SYSTEM "L" CSAH 25 AND LYNN		240 247 248	E2-BLT-ELE-PLN-102 E2-BLT-ELE-PLN-102 E2-BLT-ELE-PLN-103	ELECTRICAL SITE PLAN (2 OF 3) ELECTRICAL SITE PLAN (3 OF 3)					
209	E2-TFC-SIG-LYN-001	AVE SIGNAL PLAN - SIGNAL SYSTEM "L" CSAH 25 AND LYNN		249 250	E3-WST-ELE-PLN-101 E3-WST-ELE-PLN-102	ELECTRICAL SITE PLAN (1 OF 3) ELECTRICAL SITE PLAN (2 OF 3)					
210	E2-TFC-SIG-LYN-002	AVE EQUIPMENT SCHEDULE SIGNAL PLAN - SIGNAL SYSTEM "M" CSAH 25 (W LAKE		251 252	E3-WST-ELE-PLN-103 E3-21S-ELE-PLN-101	ELECTRICAL SITE PLAN (3 OF 3) ELECTRICAL SITE PLAN					
211	E3-TFC-SIG-WLK-001	SIGNAL PLAN - SIGNAL SISTEM MICSAH 25 (W LAKE ST) AND DREW AVE S SIGNAL PLAN - SIGNAL SYSTEM "M" CSAH 25 (W LAKE		253 253 254	E4-CHO-ELE-PLN-101 E4-CHO-ELE-PLN-101 E4-CHO-ELE-PLN-102	ELECTRICAL SITE PLAN (1 OF 2) ELECTRICAL SITE PLAN (2 OF 2)					
212	E3-TFC-SIG-WLK-002	SIGNAL PLAN - SIGNAL SISTEM MICSAH 25 (W LAKE ST) AND DREW AVE S EQUIPMENT SCHEDULE SIGNAL PLAN - SIGNAL SYSTEM "M" CSAH 25 (W LAKE		255 256	E3-CED-ELE-PLN-101 E4-PEN-ELE-PLN-101	ELECTRICAL SITE PLAN					
213	E3-TFC-SIG-WLK-003	SIGNAL FLAN - SIGNAL STSTEM MICSAH 25 (W LAKE ST) AND DREW AVE S FOR INFORMATION ONLY SIGNAL PLAN - SIGNAL SYSTEM "N" CSAH 25 (W LAKE		257 258	E4-VWT-ELE-PLN-101 E4-WAY-ELE-PLN-101	ELECTRICAL SITE PLAN ELECTRICAL SITE PLAN ELECTRICAL SITE PLAN (1 OF 2)					
214	E3-TFC-SIG-WLK-004	SIGNAL FLAN - SIGNAL STSTEM IN CSAH 25 (W LAKE ST) AND MARKET PLAZA SIGNAL PLAN - SIGNAL SYSTEM "N" CSAH 25 (W LAKE		259 260	E4-WAY-ELE-PLN-102 E4-FRE-ELE-PLN-101	ELECTRICAL SITE PLAN (2 OF 2) ELECTRICAL SITE PLAN					
215	E3-TFC-SIG-WLK-005	ST) AND MARKET PLAZA EQUIPMENT SCHEDULE SIGNAL PLAN - SIGNAL SYSTEM "N" CSAH 25 (W LAKE		261 262	E4-DUN-ELE-PLN-101 E4-GLN-ELE-PLN-101	ELECTRICAL SITE PLAN ELECTRICAL SITE PLAN					
216	E3-TFC-SIG-WLK-006	ST) AND MARKET PLAZA FOR INFORMATION ONLY SIGNAL PLAN - SIGNAL SYSTEM "O" CSAH 3		263 264	E4-BOR-ELE-PLN-101 E4-BOR-ELE-PLN-102	ELECTRICAL SITE PLAN (1 OF 2) ELECTRICAL SITE PLAN (2 OF 2)					
217	E3-TFC-SIG-EXC-001	(EXCELSIOR BLVD) AND W 32ND ST SIGNAL PLAN - SIGNAL SYSTEM "O" CSAH 3		265 266	E4-ROY-ELE-PLN-101 E4-ROY-ELE-PLN-102	ELECTRICAL SITE PLAN (1 OF 2) ELECTRICAL SITE PLAN (2 OF 2)					
218	E3-TFC-SIG-EXC-002	(EXCELSION BLVD) AND W 32ND ST EQUIPMENT SCHEDULE		266A 266B	E4-TRH-ELE-PLN-101 E0-ELE-SITE-SCH-501	ELECTRICAL SITE PLAN ELECTRICAL LUMINAIRE SCHEDULE (1 OF 3)					
219	E3-TFC-SIG-EXC-003	SIGNAL PLAN - SIGNAL SYSTEM "O" CSAH 3 (EXCELSIOR BLVD) AND W 32ND ST FOR INFORMATION		266C 266D	E0-ELE-SITE-SCH-502 E0-ELE-SITE-SCH-503	ELECTRICAL LUMINAIRE SCHEDULE (2 OF 3) ELECTRICAL LUMINAIRE SCHEDULE (3 OF 3)					
220	E3-TFC-SIG-EXC-004	ONLY SIGNAL PLAN - SIGNAL SYSTEM "P" CSAH 3 (EXCELSIO	२								
220	E3-TFC-SIG-EXC-004	BLVD) AND WHOLE FOODS DRIVEWAY SIGNAL PLAN - SIGNAL SYSTEM "P" CSAH 3 (EXCELSIO BLVD) AND WHOLE FOODS DRIVEWAY EQUIPMENT	2								
222	E3-TFC-SIG-EXC-006	SCHEDULE SIGNAL PLAN - SIGNAL SYSTEM "P" CSAH 3 (EXCELSIO BLVD) AND WHOLE FOODS DRIVEWAY FOR	R	-							
222	E3-TFC-SIG-EXC-007	INFORMATION ONLY SIGNAL PLAN - SIGNAL SYSTEM "Q" CSAH 3									
224	E3-TFC-SIG-EXC-008	(EXCELSIOR BLVD) AND MARKET PLAZA SIGNAL PLAN - SIGNAL SYSTEM "Q" CSAH 3 (EXCELSIOR BLVD) AND MARKET PLAZA EQUIPMENT SCHEDULE									
NO. DAT	E BY CHECK DESIGN RE	VISION / SUBMITTAL		I							SHEE
					ΔΞζ					TRAFFIC / LIGHTING	3
								ESŤ		ME INDEX OF PLAN SI SHEET 2	HEETS OF
					60% SURMISS	METROPOLIT	-1 1			SHEET NAME:	E0 TEC IDX 002 266
									GENER		E0-TFC-IDX - 002



ep. 21 2015 06:30 gm V:\3400\_ADC\CAD\CAD MANAGEMENT\DRAMING LIST\EO-GEN-KEY.dwg By: V-Kr

WHITE ATION	STA. B	STATION EQUA HEAD – 207+2 ACK – 2962+34 <u>VIL EAST CONTR</u> STA. 201+5	4.69 4.54 ACT 7.16	000 4000 IN FEET
2				
STATION A. AHEAD – 28 STA. BACK – 28	EQUATION 139+97.38 1337+00.01			
ଞ୍ଚିଡ଼ିଶିକ୍ଷିକ୍ଷିଡ଼ିଶିକ୍ତିକ୍ରିକ୍ଟିକ୍ଟିକ୍ଟିକ୍ଟିକ୍ଟିକ୍ଟିକ୍ଟିକ୍ଟିକ୍ଟିକ୍ଟ	MINNEHAHA CI MINNEHAHA CI LOUISIANA AVI LOUISIANA AVI LOUISIANA AVI SOUTHERLY CI SOUTHERLY CI SOUTHERLY CI XENWOOD AVE XENWOOD AVE XENWOOD AVE TH 100 BRIDGI CEDAR LAKE SI KENILWORTH T CEDAR LAKE SI S	VD BRIDGE REEK BRIDGE - FRI REEK BRIDGE - TR REEK BRIDGE - TR E BRIDGE - FREIGH E BRIDGE - TRAIL E BRIDGE - TRAIL E BRIDGE - TRAIL E BRIDGE - TRAIL TON UNDERPASS DNNECTOR BRIDGE O DNNECTOR BRIDGE O TRAIL C - TRAIL E RELOCATION - FI E - LRT BRIDGE - TRAIL F BRIDGE MODIFICAT UNNEL CHANNEL BRIDGE - CHANNEL BRIDGE - CHANNEL BRIDGE - DANNEL BRIDGE - CHANNEL BRIDGE - DANNEL BRIDGE -	AIL T DVER LRT OVER OXFORD ST REIGHT TONS FREIGHT LRT TRAIL	BRIDGE         NUMBER         27C10         R0688         R0687         R0689         27C12         27C11         27C13         R0690         R0691         27C14         XXXXX BA         XXXXX BA         27033         R0692         27037         27C15         R0693         R0693         R0693         R0693         R0695         27016         27017         27018         27J60 BA         27J61 BA
	BA – BID ALT	ERNATE		
CI	GE	Γ - VOLUMI NERAL Υ MAP	Ξ 10	SHEET 4 OF
NE: GENER	AL	SHEET NAME:	E0-GEN-KE	Y - 001 266


## TRACK LINETYPES

ROADWAY &
TRACK 🖗 (LRT)
TRACK 🦞 (FRT)
RETAINING WALL
BALLAST CURB
TUNNEL WALL
xx FENCE
EX ROW
PROP TCE
PROP PE
ID INTRUSION DETECTION

## CIVIL LINETYPES

	ROADWAY Q
	• TRACK Q (LRT)
	- TRACK Q (FRT)
	RETAINING WALL
	BALLAST CURB
	- TUNNEL WALL
	CONCRETE CURB AND GUTTER
	- TRAIL
	- SIDEWALK
	DRIVEWAY
	BRIDGE
	- SAWCUT
xxx	- FENCE
¥¥	DELINEATED WETLAND
_ · · · · ·	WATER EDGE
	EX ROW
	PROP ROW
	PROP TCE
	PROP PE
	CROSSWALK
_	STOP BAR
	MEDIAN NOSE

## TRACK SYMBOLS




NOTE: ALL TURNOUTS AND CROSSOVERS TO BE EQUIPPED WITH POWER SWITCH MACHINES AND SWITCH HEATERS

## CIVIL SYMBOLS

 $\boxtimes$ 

	ACCESSIBLE PEDESTRIAN CURB RAMP (DESIGN VARIES)
$\Rightarrow$	PROPOSED DIRECTIONAL LANE USE
र्यन्ट	EXISTING DIRECTIONAL LANE USE
1	AUTOMATIC GATE
<u>6</u> .	HANDICAP PARKING STALL
00000000000000000000000000000000000000	TACTILE WARNING STRIP
	TPSS BUILDING (TPSS-SW###)

SIGNAL OR INTERMEDIATE OR PLATFORM OR XING OR TUNNEL HOUSE OR ANY COMBINATION OF THESE



## SURVEY NOTES

- THE HORIZONTAL DATUM OF THIS MAP IS BASED ON THE HENNEPIN COUNTY COORDINATE SYSTEM WHICH IS RELATED TO THE MINNESOTA STATE PLANE COORDINATE SYSTEM NAD 83 (2007) ADJUSTMENT SOUTH ZONE.
- THE PLANIMETRIC FEATURES SHOWN ON THIS MAP ARE AS PREPARED BY AERO-METRIC, INC. FROM AERIAL DATA AND IMAGERY COLLECTED IN APRIL 2012, AS SUPPLEMENTED BY FIELD SURVEYS COMPLETED BY MFRA, INC.
- HORIZONTAL POSITIONAL ACCURACY: USING THE NATIONAL STANDARD FOR SPATIAL DATA ACCURACY, THE DATA SET TESTED 0.14 FEET HORIZONTAL ACCURACY AT A 95% CONFIDENCE LEVEL.
- VERTICAL POSITIONAL ACCURACY: USING THE NATIONAL STANDARD FOR SPATIAL DATA ACCURACY, THE DATA SET TESTED 0.10 FEET VERTICAL ACCURACY AT 95% CONFIDENCE LEVEL.

CIVIL EAST - VOLUME 10							
GENERAL							
LEGEND AND ABBREVIATIONS SHEET 1							
GENERAL	SHEET NAME: E0-GEN-NTS - 001	266					

## ABBREVIATIONS

AD	
A VE BGN	AVENUE BEGIN
BP	BEGINNING POINT
BVCE	BEGINNING VERTICAL CURVE ELEVATION
BVCS	BEGINNING VERTICAL CURVE STATION
BLVD BNSF	BOULEVARD BURLINGTON NORTHERN SANTA FE RAILWAY
C&G	CURB AND GUTTER
£	CENTERLINE
CIR CP	
CPRAIL	CANADIAN PACIFIC CANADIAN PACIFIC RAILWAY
CS	CURVE TO SPIRAL
CSAH	COUNTY STATE AID HIGHWAY
D&U DF	DRAINAGE AND UTILITY DIRECT FIXATION
DR	DRIVE
DTL	DETAIL
DWY E	DRIVEWAY
E	EAST ACTUAL SUPERELEVATION (INCHES)
EB	EAST BOUND
EL or ELEV	ELEVATION
EP ESMT	END POINT EASEMENT
Eu	UNBALANCED SUPERELEVATION (INCHES)
EVCE	ENDING VERTICAL CURVE ELEVATION
EVCS	ENDING VERTICAL CURVE STATION
EX HCRRA	EXISTING HENNEPIN COUNTY REGIONAL RAILROAD AUTHORITY
LH	LEFT HAND
LN	LANE
LRT	LIGHT RAIL TRANSIT
L <sub>C</sub> L <sub>S</sub>	CURVE LENGTH (FEET) SPIRAL LENGTH (FEET)
MIN	MINIMUM
MPH	MILES PER HOUR
MPLS MPRB	CITY OF MINNEAPOLIS MINNEAPOLIS PARK AND RECREATION BOARD
N	NORTH
NB	NORTH BOUND
NIC	NOT IN CONTRACT
NO OMF	NUMBER OPERATIONS AND MAINTENANCE FACILITY
OCS	OVERHEAD CONTACT SYSTEM
OH	OVERHEAD
PC PE	POINT OF CURVE PERMANENT EASEMENT
PITO	POINT OF INTERSECTION OF TURNOUT
PKWY	PARKWAY
POT	POINT ON TANGENT
PROP PS	PROPOSED POINT OF SWITCH
PT	POINT OF TANGENT
PVI	POINT OF VERTICAL INTERSECTION
R RD	RADIUS (FEET) ROAD
RL	RAIL LUBRICATOR
r	RATE OF CHANGE VERTICAL CURVE
RH	RIGHT HAND
ROW S	RIGHT OF WAY SOUTH
SB	SOUTH BOUND
SC	SPIRAL TO CURVE
SIG-COMM ST	SIGNAL COMMUNICATION STREET
ST	SPIRAL TO TANGENT
STA	STATION
TCE	TEMPORARY CONSTRUCTION EASEMENT
TH THRU	TRUNK HIGHWAY THROUGH
TOR	TOP OF RAIL
TPSS	TRACTION POWER SUBSTATION
TRK TS	TRACK TANGENT TO SPIRAL
TYP	TYPICAL
UG	UNDERGROUND
V	DESIGN VELOCITY (MPH)
VC W	VERTICAL CURVE WEST
wв	WEST BOUND

## TRAIL INDEX

ABBREVIATED NAME TRAIL 1 TRAIL 2 TRAIL 3 TRAIL 4 TRAIL 5 TRAIL 6	FULL NAME / LOCATION UNDER RED CIRCLE DR, LRT, AND YELLOW CIRCLE DR FROM TRAIL 1 TO GREEN CIRCLE DR OPUS STATION ACCESS FROM BREN RD E FROM BREN RD W TO TRAIL 5 FROM OPUS STATION TO GREEN CIRCLE DR FROM TRAIL 5 TO SMETANA RD
CEDAR LAKE TRAIL	CEDAR LAKE LRT REGIONAL TRAIL/FROM SHADY OAK STATION TO 11TH AVE
CEDAR LAKE TRAIL	CEDAR LAKE LRT REGIONAL TRAIL/WEST OF EXCELSIOR
CEDAR LAKE TRAIL	CEDAR LAKE LRT REGIONAL LRT TRAIL/BETWEEN EXCELSIOR AND KENILWORTH TRAIL CONNECTION
MIDTOWN GREENWAY	MIDTOWN GREENWAY/EAST OF KENILWORTH TRAIL CONNECTION
TRAIL A	KENILWORTH TRAIL (SECONDARY)/BETWEEN CEDAR-ISLES CHANNEL AND 21ST STREET STATION
TRAIL B	KENILWORTH TRAIL (SECONDARY)/BETWEEN 21ST STREET STATION AND PENN STATION
TRAIL B	CEDAR LAKE TRAIL (SECONDARY)/EAST OF PENN STATION
TRAIL C	10' CONNECTOR TRAIL FROM CEDAR LAKE LRT REGIONAL TRAIL TO TYLER AVE.
TRAIL D	10' CONNECTOR TRAIL/BELTLINE STATION TO CEDAR LAKE LRT REGIONAL TRAIL
KENILWORTH TRAIL	KENILWORTH TRAIL (MAIN)/W LAKE ST TO PENN STATION
CEDAR LAKE TRAIL	CEDAR LAKE TRAIL (MAIN)/PENN STATION TO TH 394
TRAIL E	KENILWORTH TRAIL (SECONDARY)/EAST OF W LAKE ST
TRAIL F	KENILWORTH TRAIL (SECONDARY)/WEST OF CEDAR LAKE PKWY
TRAIL G	KENILWORTH TRAIL (SECONDARY)/WEST OF PENN STATION
TRAIL G	CEDAR LAKE TRAIL (SECONDARY)/EAST OF PENN STATION
TRAIL H	10' CONNECTOR TRAIL/EAST OF PENN STATION TO KENWOOD PKWY
TRAIL I	NOT USED
CEDAR LAKE TRAIL	CEDAR LAKE TRAIL (MAIN)/AT-GRADE CROSSING AT PENN STATION
TRAIL J	CEDAR LAKE TRAIL (SECONDARY)/NORTHWEST OF PENN STATION
TRAIL K	CEDAR LAKE TRAIL (SECONDARY)/NORTHWEST OF PENN STATION
TRAIL L	CEDAR LAKE TRAIL (SECONDARY)/EAST OF PENN STATION
TRAIL M	NOT USED
TRAIL N	8' CONNECTOR TRAIL FROM CEDAR LAKE TRAIL TO EDGEBROOOK DRIVE
TRAIL O	8' CONNECTOR TRAIL FROM CEDAR LAKE TRAIL TO W LAKE STREET
TRAIL P	8' CONNECTOR TRAIL FROM CEDAR LAKE TRAIL TO LOUISIANA AVE
TRAIL Q	10' CONNECTOR TRAIL FROM CEDAR LAKE TRAIL TO TH 7 SERVICE ROAD
TRAIL R	20' CONNECTOR TRAIL FROM VAN WHITE STATION TO CEDAR LAKE TRAIL
TRAIL S TRAIL T	NOT USED 8' CONNECTOR TRAIL FROM VAN WHITE STATION TO VAN WHITE MEMORIAL BLVD
TRAIL U	10' TRAIL PARALLEL TO CEDAR LAKE PKWY
LUCE LINE TRAIL	LUCE LINE REGIONAL TRAIL/ON BRIDGE OVER LIGHT RAIL
TRAIL V	CONNECTOR TRAIL TO LUCE LINE REGIONAL TRAIL WEST OF LIGHT RAIL
TRAIL W	CONNECTOR TRAIL TO LUCE LINE REGIONAL TRAIL WEST OF LIGHT RAIL

3							-		
איי	NO. DATE	BY	CHECK	DESIGN REVISION / SUBMITTAL				<b>CIVIL EAST - VOLUME 10</b>	SHEET
:30 ai								GENERAL	6
15 06					AECOM			LEGEND AND ABBREVIATIONS	OF
21 201						METROPOLITAN C V V C V		SHEET 2	
Sep, 2					60% SUBMISSION - 09/28/15		DISCIPLINE:	GENERAL E0-GEN-NTS - (	266 002

2015 06:30 am V:\3400\_ADC\CAD\CAD MANAGEMENT\DRAWING LIST\EO-GEN-NTS.dwg By: V-Kri

## PERMANENT PAVEMENT MARKING PLAN

NOTES & GUIDELINES

#### GENERAL INFORMATION:

THE ENGINEER'S INVOLVEMENT IN THE APPLICATION OF THE MATERIAL SHALL BE LIMITED TO FIELD CONSULTATION AND INSPECTION. THE CONTRACTOR WILL PLACE NECESSARY "SPOTTING" AT APPROPRIATE POINTS TO PROVIDE HORIZONTAL CONTROL FOR STRIPING AND TO DETERMINE NECESSARY STARTING AND CUTOFF POINTS. LONGITUDINAL JOINTS, PAVEMENT EDGES AND EXISTING MARKINGS MAY SERVE AS HORIZONTAL CONTROL WHEN SO DIRECTED.

EDGE LINES AND LANE LINES ARE TO BE BROKEN ONLY AT INTERSECTIONS WITH PUBLIC ROADS AND AT PRIVATE ENTRANCES IF THEY ARE CONTROLLED BY A YIELD SIGN, STOP SIGN OR TRAFFIC SIGNAL. THE BREAK POINT IS TO BE AT THE START OF THE RADIUS FOR THE INTERSECTION OR AT MARKED STOP LINES OR CROSSWALKS.

A TOLERANCE OF 1/4 INCH UNDER OR 1/4 INCH OVER THE SPECIFIED WIDTH WILL BE ALLOWED FOR STRIPING PROVIDED THE VARIATION IS GRADUAL AND DOES NOT DETRACT FROM THE GENERAL APPEARANCE. BROKEN LINE SEGMENTS MAY VARY UP TO ONE-HALF FOOT FROM THE SPECIFIED LENGTHS PROVIDED THE OVER AND UNDER VARIATIONS ARE REASONABLY COMPENSATORY. ALIGNMENT DEVIATIONS FROM THE CONTROL GUIDE SHALL NOT EXCEED 1 INCH. MATERIAL SHALL NOT BE APPLIED OVER LONGITUDINAL JOINTS. ESTABLISHMENT OF APPLICATION TOLERANCES SHALL NOT RELIEVE THE CONTRACTOR OF THEIR RESPONSIBILITY TO COMPLY AS CLOSELY AS PRACTICABLE WITH THE PLANNED DIMENSIONS.

THE ROAD SURFACE SHALL BE CLEANED AT THE DIRECTION OF THE ENGINEER JUST PRIOR TO APPLICATION. PAVEMENT CLEANING SHALL CONSIST OF AT LEAST BRUSHING WITH A ROTARY BROOM (NON-METALLIC) OR AS RECOMMENDED BY THE MATERIAL MANUFACTURER AND ACCEPTABLE TO THE ENGINEER. NEW PORTLAND CEMENT CONCRETE SURFACES SHALL BE SANDBLAST CLEANED TO REMOVE ANY SURFACE TREATMENTS AND/OR LAITANCE. ON LOW SPEED (SPEED LIMIT 35 OR LESS) URBAN PORTLAND CEMENT CONCRETE ROADWAYS, SANDBLAST CLEANING SHALL BE USED FOR ALL EPOXY PAVEMENT MARKINGS.

THE EPOXY MARKING APPLICATION SHALL IMMEDIATELY FOLLOW THE PAVEMENT CLEANING. GLASS BEADS SHALL BE APPLIED IMMEDIATELY AFTER APPLICATION OF THE EPOXY RESIN LINE TO PROVIDE AN IMMEDIATE NO-TRACK SYSTEM.

FOR 20 MIL APPLICATIONS, GLASS BEADS SHALL BE APPLIED AT A RATE OF AT LEAST 25 LB/GAL. THE "NO-TRACKING" CONDITION SHALL BE DETERMINED ON AN APPLICATION OF SPECIFIED THICKNESS TO THE PAVEMENT AND COVERED WITH GLASS BEADS AT THE RATE OF AT LEAST 25 LB/GAL.

OPERATIONS SHALL BE CONDUCTED ONLY WHEN THE ROAD PAVEMENT SURFACE TEMPERATURES ARE 50 DEGREES 'F OR GREATER.

PERMANENT PAVEMENT MARKINGS SHALL NOT BE PLACED OVER TEMPORARY TAPE MARKINGS.

#### POLY PREFORM INLAY APPLICATION:

MAT TEMPERATURE SHALL BE CHECKED USING A THERMOMETER TO MAKE SURE THE INLAY IS BEING DONE IN THE PROPER TEMPERATURE RANGE. THE TEMPERATURE SHOULD MEASURE BETWEEN 150° F (ASPHALT FIRM ENOUGH TO WALK ON) AND 120° F. APPLICATION BELOW 120° F MAY NOT GET A PROPER INLAY. INLAYS ARE NOT RECOMMENDED AFTER SEPTEMBER 15th AS THE ASPHALT COOLS TOO FAST AT THIS TIME OF THE YEAR.

NO PRIMERS ARE USED FOR INLAY APPLICATION. DO NOT INSTALL LANE LINES ON AN ASPHALT SEAM. ROLLING OF ALL THE MARKINGS SHOULD BE LENGTHWISE IN THE DIRECTION THEY WERE LAID. FOR CROSSWALKS AND STOP BARS, INITIAL TAMPING WITH THE TAMPING CART IS RECOMMENDED USING ONLY 100 LBS. OF WEIGHT.

USE COMPACTION ROLLER TO EMBED (INLAY) MARKINGS INTO PAVEMENT SURFACE. USE MINIMUM SPEED AND WATER ON ROLLER. DO NOT USE VIBRATOR. IF MARKING BUCKLES OR DISTORTS SEVERELY IN FRONT OF ROLLER, MAT TEMPERATURE OR ROLLER SPEED MAY BE TOO HIGH.

#### POLY PREFORM GROOVED APPLICATION:

CONCRETE PAVEMENT SURFACES AND BITUMINOUS PAVEMENT SURFACES WHERE PAVEMENT MARKINGS CANNOT BE INLAID IN THE HOT MAT, SHALL BE GROOVED FOR THE INSTALLATION OF DURABLE REFLECTORIZED PAVEMENT MARKINGS. SEE SPECIAL PROVISIONS.

#### PAINT:

AT THE TIME OF APPLYING THE MARKING MATERIAL, THE APPLICATION AREA SHALL BE FREE OF CONTAMINATION. THE CONTRACTOR SHALL CLEAN THE ROADWAY SURFACE PRIOR TO THE LINE APPLICATION IN A MANNER AND TO THE EXTENT REQUIRED BY THE ENGINEER.

GLASS BEADS SHALL BE APPLIED IMMEDIATELY AFTER APPLICATION OF THE PAINT LINE.

EXCEPT WHEN USED AS A TEMPORARY MARKING, PAVEMENT MARKINGS SHALL ONLY BE APPLIED IN SEASONABLE WEATHER WHEN AIR TEMPERATURE IS 50°F OR HIGHER AND SHALL NOT BE APPLIED WHEN THE WIND OR OTHER CONDITIONS CAUSE A FILM OF DUST TO BE DEPOSITED ON THE PAVEMENT SURFACE AFTER CLEANING AND BEFORE THE MARKING MATERIAL CAN BE APPLIED.

THE FILLING OF TANKS, POURING OF MATERIALS OR CLEANING OF EQUIPMENT SHALL NOT BE PERFORMED ON UNPROTECTED PAVEMENT SURFACES UNLESS ADEQUATE PROVISIONS ARE MADE TO PREVENT SPILLAGE OF MATERIAL.

-	-							1		
NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL					
						<b>AECOM</b> Kimley				
									SOUTHWEST	
								METROPOLITAN	Green Line LRT Extension	
								METROPOLITAN	-	
						60% SUBMISSION - 09/2	28/15			DISCIPLINE
						00 /8 SOBINISSICIA - 05/2	20/13			

	SYMBOLS & MATERIALS LEGEND	
	CROSSWALK BLOCK WHITE-PREFORM	
	PAVEMENT MESSAGE (LEFT ARROW) POLY PREFORM	
	STRIPING KEY	
	CIRCLE-EPOXY SQUARE-POLY PREFORM	И
	PENTAGON-REMOVEABLE-PREFORMED PLASTIC MARKING	
	1ST DIGIT 2ND DIGIT 3RD DIGIT WIDTH PATTERN COLOR	
	4", 8", ETC. S – SOLID W – WHITE B – BROKEN Y – YELLO'	
	D – DOTTED/DOUBLE B – BLACK	
	EXAMPLE: $(4SW) = 4"$ SOLID LINE WHITE-EPOXY	
	I HEREBY CERTIFY THAT SHEETS 000 THROUGH 000 OF THIS PLAN WERE PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY LICEN PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MINNESOTA. PRINT NAME:ENGR NAME HERE LICENSE #	ISED
	DATE: \$!DATE!\$ SIGNATURE:	
	DESIGNER TECH NAME HERE	
	CIVIL EAST - VOLUME 10	SHEET
	SIGNING AND STRIPING	7
	MNDOT NOTES AND LEGEND	OF
:	TRAFFIC E0-TFC-SIGN-STRP-DTL - 001	266

ALL TRAFFIC CONTROL DEVICES SHALL CONFORM AND BE INSTALLED IN ACCORDANCE	GENERAL
	ZONE LAYOUTS" WITH THE FOLLOWING EXCEPTIONS AND AS DIRECTED BY THE ENGINEER. NDITIONS OR TO CONFORM TO THE REQUIREMENTS OF OTHER AGENCIES.
SIGNING TYPE C	PERMANENT STRIPING AND PAVEMENT MARKINGS
ALL SIGNING SHALL USE DG3 SIGN SHEETING.	ALL LONGITUDINAL LINES SHALL BE 4" WIDE EPOXY GROUND IN (GROOVED) EXCEPT WHITE EDGE LINES WHICH SHALL BE 6". UNLESS NOTED.
ALL SIGNS SHALL BE CONVENTIONAL ROAD SIZE AS SHOWN IN THE MN MUTCD APPENDIX C EXCEPT AS FOLLOWS: ALL STOP SIGNS (R1-1) SHALL BE A MINIMUM OF 36" X 36" ALL NO PARKING SIGNS (R8-3) SHALL BE 18" X 18" ALL PEDESTRIAN CROSSING SIGNS (W11-2) SHALL BE A MINIMUM OF 36" X 36"	A BROKEN LINE SHALL BE A 4" WDE EPOXY GROUND IN (GROOVED) LINE AND SHALL HAVE A 10' LENGTH AND 30' GAP.
ALL SIGNS SHALL HAVE HOLES PUNCHED ONLY FOR THE NUMBER OF POSTS REQUIRED.	A DOTTED LINE (CAT TRACKS) SHALL BE A 4" WIDE THERMOPLASTIC GROUND IN (GROOVED) LINE AND SHALL HAVE A 2' LENGTH AND 6' GAP.
ALL SIGN POSTS SHALL BE 3 POUNDS PER FOOT, GALVANIZED "U" POSTS.	CROSSHATCHING (HASH MARKS) SHALL BE 24" WIDE EPOXY GROUND IN (GROOVED) LINE. INSTALLED AT 45" WITH AN 20' PERPENDICULAR GAP. THEY SHALL ONLY BE PLACED WHEN AT LEAST 2 BARS OF
NUMBER OF POSTS: SIGN WIDTH 35" OR LESS USE 1 POST SIGN WIDTH 36" – 70" USE 2 POSTS WITN BACK BRACE SIGN WIDTH OVER 70" PLACE A POST APPROXIMATELY EVERY 2' WITH BACK BRACE	MINIMUM 6' LENGTH CAN BE INSTALLED AT STANDARD SPACING. ON BITUMINOUS PAVEMENTS LONGITUDINAL LINES SHALL NOT BE PLACED IMMEDIATELY ADJACENT (2' OR LESS FROM THE FACE OF CURB) TO CONCRETE CURB AND GUTTER, RAISED CONCRETE OR MONOLITHIC ISLANDS EXCEPT RIGHT TURN ISLANDS.
LATERAL BRACES MAY BE USED AS A STIFFENER FOR SIGNS IF REQUIRED BY THE ENGINEER.	STOP LINES SHALL NOT BE PLACED EXCEPT AT RAILROAD CROSSINGS, SIGNALIZED INTERSECTION APPROACHES
KNEE BRACES SHALL NOT BE USED UNLESS REQUIRED BY THE ENGINEER.	WITHOUT CROSSWALK MARKINGS AND AT "MINNEAPOLIS" STYLE CROSSWALK MARKINGS. PERMANENT PAVEMENT MARKINGS, STRIPING AND MESSAGES SHALL NOT BE PLACED ONTO A CONCRETE GUTTER.
OBJECT MARKERS AND SNOW PLOW MARKERS 5.0' OBJECT MARKER IF MOUNTED BELOW A KEEP RIGHT 4.0'	ALL PAVEMENT MESSAGES SHALL BE THERMOPLASTIC GROUND IN (GROOVED). ALL BIKE LANE AND SHARED LANE SYMBOLS SHALL HAVE A WHITE LEGEND CENTERED ON A BLACK RECTANGULAR BACKGROUND.
ALL SIGNS MOUNTED IN CONCRETE OR LANDSCAPE PAVER SURFACING SHALL USE A SIGN SOCKET WHICH SHALL BE PLACED IN CONCRETE. ALL SIGN SOCKETS LOCATED ON RAISED ISLANDS SHALL USE DOUBLE SIGN SOCKETS. SEE TYPICAL SIGN SOCKET DETAIL.	THE INSTALLERS OF ALL THERMOPLASTIC MATERIALS MUST CARRY A CARD CERTIFYING THAT THEY HAVE ATTENDED A TRAINING SESSION THAT ADDRESSES SURFACE PREPARATIONS AND ALL APPLICATION REQUIREMENTS AND TECHNIQUES NECESSARY FOR SUCCESSFUL APPLICATIONS.
ALL KEEP RIGHT SIGNS (R4–7) SHALL HAVE REAR DELINEATION AS SHOWN IN THE REAR DELINEATION DETAIL AND AN OM1–3 MOUNTED BELOW THE KEEP RIGHT SIGN.	IF THERMOPLASTIC MATERIAL IS TO BE INSTALLED ON CONCRETE PAVEMENT THE CONCRETE PAVEMENT SHALL HAVE A SEALER APPLIED THAT IS IN ACCORDANCE WITH ALL OF THE MANUFACTURE'S SPECIFICATIONS AFTER THE GROUND IN
NO PARKING SIGNS SHALL WHERE POSSIBLE BE GROUPED WITH OTHER SIGNS TO REDUCE THE NUMBER OF SIGN POSTS.	PROCESS (GROOVED) AND BEFORE ANY THERMOPLASTIC MATERIAL IS APPLIED, AS DIRECTED BY THE ENGINEER.
ADOPT A HIGHWAY SIGN (I–X1) SHALL NOT BE USED. IF REQUIRED 36" X 24" ADOPT A HIGHWAY SIGNS SHALL BE FURNISHED BY HENNEPIN COUNTY FOR INSTALLATION BY THE CONTRACTOR.	PAVEMENT MESSAGE SPECIAL SHALL NOT BE PLACED WITHIN ANY MARKED CROSSWALK.
A SCHOOL CROSSING SIGN (S1-1) WITH AHEAD PLAQUE (W16-9P) MOUNTED BELOW THE SCHOOL CROSSING SIGN SHALL BE IN ADVANCE OF ALL SCHOOL CROSSING SIGNS (S1-1).	PAVEMENT MESSAGE SPECIAL SHALL HAVE ALL THERMOPLASTIC MATERIAL OMITTED THAT WOULD BE PLACED ONTO A CONCRETE GUTTER, AS DIRECTED BY THE ENGINEER.
ALL SIGNS SHOWN IN THE MN MUTCD WITH OPTIONAL FLUORESCENT YELLOW-GREEN BACKGROUND COLOR SHALL USE THE FLUORESCENT YELLOW-GREEN BACKGROUND COLOR.	FULL WIDTH TURN LANES: UNDER 250' USE 1 ARROW PLACED AT THE CENTER OF THE TURN LANE. OVER 250' USE 2 ARROWS PLACED AS SHOWN IN THE MN/DOT "TRAFFIC ENGINEERING MANUAL" PAVEMENT MESSAGE "ONLY" SHALL NOT BE USED.
NO PASSING ZONE SIGN (W14-3) SHALL BE USED ON THE LEFT WITH A DO NOT PASS SIGN (R4-1) ON THE RIGHT. MERGE WITH DEMOUNTABLE ARROW SIGN (W20-X3) SHALL NOT BE USED. A LANE ENDS MERGE SIGN (W9-2) FOLLOWED BY A LANE REDUCTION SIGN (W4-2) SHALL BE USED. ALL INPLACE SIGNS WITHIN THE CONSTRUCTION LIMITS SHALL BE PROTECTED INPLACE, SALVAGED OR SALVAGED AND REINSTALLED AS SHOWN IN THE PLANS AND AS DIRECTED BY THE ENGINEER. SALVAGED SIGNS SHALL NOT BE REINSTALLED UNLESS THEY ARE IN GOOD CONDITION, HAVE DG3 SIGN SHEETING AND ARE STILL APPLICABLE.	CROSSWALK MARKINGS OUTSIDE THE CITY OF MINNEAPOLIS SHALL BE WHITE THERMOPLASTIC "ZEBRA" STYLE. THEY SHALL MATCH IN WIDTH THE FACILITY THAT ENTERS THE CROSSWALK MARKINGS WITH A MINIMUM WIDTH OF 6' OR AS DIRECTED BY THE ENGINEER. CROSSWALK MARKINGS WITHIN THE CITY OF MINNEAPOLIS AND THE UNIVERSITY OF MINNESOTA CAMPUS SHALL BE TWO PARALLEL 12" WIDE WHITE THERMOPLASTIC LINES GROUND IN (GROOVED) INSTALLED A MINIMUM OF 10' APART, WITH A 24" WHITE THERMOPLASTIC STOP LINE GROUND IN (GROOVED) INSTALLED WITH A 10' PERPENDICULAR GAP FROM THE NEAR SIDE CROSSWALK MARKING, ACROSS ALL LANES OF APPROACHING TRAFFIC. AS DIRECTED BY THE ENGINEER.
ALL SALVAGED SIGNS NOT REINSTALLED SHALL BE COMPLETELY DISASSEMBLED BY THE CONTRACTOR AND BROKEN DOWN INTO THEIR BASIC COMPONENTS (SIGN PANELS, POST, NUTS AND BOLTS) WHICH SHALL BE RETURNED TO THEIR OWNERS.	CROSSWALK MARKINGS SHALL WHERE POSSIBLE CONNECT PEDESTRIAN CURB RAMPS WITH A STRAIGHT LINE, AT 90^ TO THE ROADWAY AND BE PLACED IN FRONT OF MEDIAN NOSES. CROSSWALK MARKINGS SHALL NOT BE PLACED ACROSS FREE RIGHT TURN LANES, SLIP LANES OR AT SIGNED TRAIL CROSSING LOCATIONS.
BY CHECK DESIGN REVISION / SUBMITTAL	Kimley »Horn

60% SUBMISSION - 09/28/15

NO. DATE

**CIVIL EAST - VOLUME 10** SIGNING AND STRIPING 8 **HENNEPIN COUNTY NOTES** OF SHEET 1 DISCIPLINE: HEET NAME: 266 TRAFFIC E0-TFC-SIGN-STRP-DTL - 002

SHEET

#### GENERAL INFORMATION:

THE ENGINEER'S INVOLVEMENT IN THE APPLICATION OF THE MATERIAL SHALL BE LIMITED TO FIELD CONSULTATION AND INSPECTION. THE CONTRACTOR WILL PLACE NECESSARY "SPOTTING" AT APPROPRIATE POINTS TO PROVIDE HORIZONTAL CONTROL FOR STRIPING AND TO DETERMINE NECESSARY STARTING AND CUTOFF POINTS. LONGITUDINAL JOINTS, PAVEMENT EDGES AND EXISTING MARKINGS MAY SERVE AS HORIZONTAL CONTROL WHEN SO DIRECTED.

EDGE LINES AND LANE LINES ARE TO BE BROKEN ONLY AT INTERSECTIONS WITH PUBLIC ROADS AND AT PRIVATE ENTRANCES IF THEY ARE CONTROLLED BY A YIELD SIGN, STOP SIGN OR TRAFFIC SIGNAL. THE BREAK POINT IS TO BE AT THE START OF THE RADIUS FOR THE INTERSECTION OR AT MARKED STOP LINES OR CROSSWALK

A TOLERANCE OF 1/4" UNDER OR 1/4" OVER THE SPECIFIED WIDTH WILL BE ALLOWED FOR STRIPING PROVIDED THE VARIATION IS GRADUAL AND DOES NOT DETRACT FROM THE GENERAL APPEARANCE. BROKEN LINE SEGMENTS MAY VARY UP TO 6" FROM THE SPECIFIED LENGTHS PROVIDED THE OVER AND UNDER VARIATIONS ARE REASONABLY COMPENSATORY. ALIGNMENT DEVIATIONS FROM THE CONTROL GUIDE SHALL NOT EXCEED 1" MATERIAL SHALL NOT BE APPLIED OVER LONGITUDINAL JOINTS. ESTABLISHMENT OF APPLICATION TOLERANCES SHALL NOT RELEVE THE CONTRACTOR OF HIS RESPONSIBILITY TO COMPLY AS CLOSELY AS PRACTICABLE WITH THE PLANNED DIMENSIONS.

#### EPOXY

THE ROAD SURFACE SHALL BE CLEANED AT THE DIRECTION OF THE ENGINEER JUST PRIOR TO APPLICATION. PAVEMENT CLEANING SHALL CONSIST OF AT LEAST BRUSHING WITH A ROTARY BROOM (NON-METALLIC) OR AS RECOMMENDED BY THE MATERIAL MANUFACTURER AND ACCEPTABLE TO THE ENGINEER. NEW PORTLAND CEMENT CONCRETE SURFACES SHALL BE SANDBLAST CLEANED TO REMOVE ANY SURFACE TREATMENTS AND/OR LAITANCE. ON LOW SPEED (SPEED LIMIT 35 OR LESS) URBAN PORTLAND CEMENT CONCRETE ROADWAYS, SANDBLAST CLEANING SHALL BE USED FOR ALL EPOXY PAVEMENT MARKINGS.

THE EPOXY MARKING APPLICATION SHALL IMMEDIATELY FOLLOW THE PAVEMENT CLEANING. GLASS BEADS SHALL BE APPLIED IMMEDIATELY AFTER APPLICATION OF THE EPOXY RESIN LINE TO PROVIDE AN IMMEDIATE NO-TRACK SYSTEM.

AN EPOXY RESIN LINE 4 INCHES WIDE AND 15 MILL THICKNESS (WET), REQUIRES AN APPLICATION RATE OF ONE (1) GALLON OF COMPONENTS FOR 320 FEET OF LINE. GLASS BEADS SHALL BE APPLIED AT A POUND PER GALLON RATE SUFFICIENT TO ACHIEVE AN ACCEPTABLE NO-TRACK SYSTEM

OPERATIONS SHALL BE CONDUCTED ONLY WHEN THE ROAD PAVEMENT SURFACE TEMPERATURES ARE 50 DEGREES F OR GREATER.

DO NOT APPLY OVER INPLACE PAINT, INPLACE EPOXY OR INPLACE THERMOPLASTIC UNLESS VERY WELL WORN (AT LEAST 75% - 80% WORN AWAY) AND WELL ADHERED TO THE PAVEMENT. GRIND OR SANDBLAST OLD MARKINGS AND SWEEP OR BLOW AREA CLEAN.

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL

#### THERMOPLASTIC AND POLY PREFORM

THE INSTALLERS OF THIS MATERIAL MUST CARRY A CARD CERTIFYING THAT THEY HAVE ATTENDED A TRAINING SESSION THAT ADDRESSES SURFACE PREPARATIONS AND ALL APPLICATION REQUIREMENTS AND TECHNIQUES NECESSARY FOR SUCCESSFUL APPLICATION.

ALL MARKINGS SHALL BE OF THE "INLAY" METHOD UNLESS THE "GROUND IN" (GROOVED) OR "OVERLAY" PROCEDURE IS SPECIFIED.

#### GROOVE SPECIFICATIONS

THE PAVEMENT SURFACE SHALL BE GROUND (GROOVED) TO DIMENSIONS THAT ARE EQUAL OR GREATER THAN 1" LARGER (ALL DIRECTIONS) THAN THE DIMENSIONS OF THE MARKING TO BE INSTALLED (NOT TO EXCEED 2" GREATER THAN THE MARKING DIMENSIONS). THE DEPTH OF THE GROOVE SHALL BE 100 MILLS (+/- 10 MILLS). NOTE: 1000 MILLS = 1 INCH.

THE RECOMMENDED POSITION OF THE GROOVE EDGE IS A MINIMUM OF 2 INCHES FROM THE EDGE OF CONCRETE JOINTS OR ASPHALT SEAMS ALONG EDGE OR CENTERLINES.

INTERSECTION MARKINGS, LEGENDS, AND SYMBOLS MAY REQUIRE USE OF WIDER CUTTING HEADS TO REDUCE THE NUMBER OF RIDGES FORMED BY MULTIPLE PASSES WITH THE CUTTING HEAD. THE HEIGHT OF THE RIDGES SHOULD BE LESS THAN 20% OF THE GROOVE DEPTH. SMALLER EQUIPMENT MAY BE REQUIRED TO ACHIEVE A GROOVE AT THE RECOMMENDED DEPTH WHEN WORKING NEAR OBSTACLES SUCH AS CURBS OR MEDIANS.

NEW BITUMINOUS PAVEMENT SHOULD NOT BE GROOVED UNTIL AFTER 10 DAYS OF THE PLACEMENT OF THE FINAL COURSE OF PAVEMENT. INTERIM DEVICES (TEMP. TAPE, RAISED TABS, OR OTHER DELINEATION OR CHANNELIZATION DEVICES) SHALL DELINEATE THE PROPOSED MARKING AREAS IF THE ROADWAY IS OPEN TO TRAFFIC.

#### APPLICATION OF MARKING IN GROUND IN (GROOVED) PAVEMENT

THE GROOVE SHALL BE ALLOWED TO DRY A MINIMUM OF 24 HOURS AFTER GROOVE CLEANING, REMOVAL OF WATER, AND PRIOR TO PAVEMENT MARKING APPLICATION IF WATER IS USED IN THE GROOVING PROCESS. THE GROOVE MUST BE CLEAN AND DRY FOR PROPER APPLICATION OF THE PAVEMENT MARKING. CLEAN THE GROOVE COMPLETELY PRIOR TO PAVEMENT APPLICATION USING AN AIR COMPRESSOR WITH AT LEAST 185 CFM AIR FLOW AND 90 PSI AIR PRESSURE. ONE DRY PASS WITH A PICKUP SWEEPER WILL BE REQUIRED PRIOR TO AIRBLASTING THE GROOVE IF TRAFFIC IS PRESENT.

AIR TEMPERATURE SHALL BE A MINIMUM OF 40 DEGREES F. SURFACE TEMPERATURE SHALL BE A MINIMUM OF 40 DEGREES F.

A SURFACE PREPARATION ADHESIVE IS REQUIRED WHEN PAVEMENT MARKING APPLICATION OCCURS OUTSIDE OF THE SEASON BETWEEN JUNE 1 AND SEPTEMBER 1. SURFACE PREPARATION ADHESIVE SHALL BE APPLIED ACCORDING TO PRODUCT RECOMMENDATIONS.

PAVEMENT MARKING SHALL BE INSTALLED AND TAMPED AS PER MANUFACTURES RECOMMENDATIONS. USE TAMPER CARTS WITH A 200-POUND LOAD. PAVEMENT MARKING APPLICATION IN A GROOVE WILL REQUIRE TAMPING WITH A TAMPER CART ROLLER CUT TO FIT IN THE GROOVE. USE A MODIFIED TAMPER CART ROLLER IF NECESSARY. A TYPICAL MODIFIED ROLLER WILL HAVE A 4" WIDTH AND A 1/4 DEPTH. USE OF A VEHICLE TIRE TO TAMP TAPE IN A GROOVE IS ACCEPTABLE FOR WAFFLE PATTERN TYPES.

NO PRIMERS ARE USED FOR INLAY APPLICATION, DO NOT INSTALL LANE LINES ON AN ASPHALT SEAM, ROLLING OF ALL THE MARKINGS SHOULD BE LENGTHWISE IN THE DIRECTION THEY WERE LAID. FOR CROSSWALKS AND STOP LINES, INITIAL TAMPING WITH THE TAMPING CART IS RECOMMENDED USING ONLY 100 LBS. OF WEIGHT.

NEW CONCRETE (LESS THAN 3 MONTHS OLD): REMOVE CURING COMPOUND BY SANDBLASTING, HYDROBLASTING OR SHOT BLASTING WHERE TAPE IS TO BE APPLIED. HYDROBLASTING LEAVES SURFACE WET, TIME SHALL BE ALLOWED FOR PAVEMENT TO DRY. SWEEP OR BLOW THE BLASTED AREAS CLEAN. APPLY REQUIRED PRIMER (SEE MANUFACTURERS SPECIFICATIONS).

ASPHALT (0 - 3 DAYS OLD): SWEEP OR BLOW AREA CLEAN. NO PRIMER IS REQUIRED.

ASPHALT (4 DAYS OLD OR OLDER): SWEEP OR BLOW AREA CLEAN. APPLY REQUIRED PRIMER. (SEE MANUFACTURERS SPECIFICATIONS).

OLD CONCRETE: SWEEP OR BLOW AREA CLEAN. APPLY REQUIRED PRIMER (SEE MANUFACTURES SPECIFICATIONS).

OLD MARKINGS: DO NOT APPLY OVER PAINT, EPOXY OR THERMOPLASTIC UNLESS VERY WELL WORN (AT LEAST 75% - 80% WORN AWAY) AND WELL ADHERED TO THE PAVEMENT. GRIND OR SANDBLAST OLD MARKING AND SWEEP OR BLOW AREA CLEAN. APPLY REQUIRED PRIMER (SEE MANUFACTURERS SPECIFICATIONS).

<b>AECOM</b> Kimley»Horn	METROPOLITAN	SOUTHWEST	
60% SUBMISSION - 09/28/15			DISCIPLIN

#### INLAY SPECIFICATIONS

MAT TEMPERATURE SHALL BE CHECKED USING A THERMOMETER TO MAKE SURE THE INLAY IS BEING DONE IN THE PROPER TEMPERATURE RANGE, THE TEMPERATURE SHOULD MEASURE BETWEEN 150 DEGREES F (ASPHALT FIRM ENOUGH TO WALK ON) AND 120 DEGREES F, APPLICATION BELOW 120 DEGREES F MAY NOT GET A PROPER INLAY. INLAYS ARE NOT RECOMMENDED AFTER SEPTEMBER 15TH AS THE ASPHALT COOLS TOO FAST AT THIS TIME OF YEAR.

USE COMPACTION ROLLER TO EMBED (INLAY) MARKINGS INTO PAVEMENT SURFACE. USE MINIMUM SPEED AND WATER ON ROLLER. DO NOT USE VIBRATOR. IF MARKING BUCKLES OR DISTORTS SEVERELY IN FRONT OF ROLLER, MAT TEMPERATURE OR ROLLER SPEED MAY BE TOO HIGH.

#### OVERLAY SPECIFICATIONS

WORN POLY PREFORM MARKINGS: OK TO APPLY NEW MATERIAL OVER WORN POLY PREFORM MARKINGS. REMOVE ALL LOOSE MATERIAL WITH SCRAPER OR KNIFE. SWEEP OR BLOW AREA CLEAN. APPLY REQUIRED PRIMER (SEE MANUFACTURES SPECIFICATIONS)


### **CIVIL EAST - VOLUME 10** SIGNING AND STRIPING **HENNEPIN COUNTY NOTES** SHEET 2


SHEET 9

OF

266


TRAFFIC E0-TFC-SIGN-STRP-DTL - 003





### MARKINGS FOR PEDESTRIAN CROSSWALKS


#### ALTERNATE (S) ALTERNATE (L) (W) (S) (W) WIDTH OF WIDTH OF WIDTH OF WIDTH OF WIDTH OF INSIDE LANE PAINTED AREA SPACE PAINTED AREA PAINTED AREA 9' 2.0 2.5' \_ \_\_\_\_ 10' 2.5' 2.5' 2.0' 3.0' 11' 2.5' 3.0' 2.0' 3.5' 12' 3.0' 3.0' 2.5' 3.5' 13' 3.0' 3.5' \_ \_




#### NOTES:

- 1. PAINTED AREAS TO BE CENTERED ON CENTERLINE AND LANE LINES.
- A MINIMUM OF 1.5 FT. CLEAR DISTANCE SHALL BE LEFT ADJACENT TO THE 2. CURB. IF LAST PAINTED AREA FALLS INTO THIS DISTANCE IT MUST BE OMITTED
- ON TWO LANE TWO WAY STREETS, USE SPACING SHOWN FOR AN 11 FT. INSIDE 3. LANE.
- FOR DIVIDED ROADWAYS. ADJUSTMENTS IN SPACING OF THE BLOCKS SHOULD 4. BE MADE IN THE MEDIAN SO THAT THE BLOCKS ARE MAINTAINED IN THEIR PROPER LOCATION ACROSS THE TRAVELED PORTION OF THE ROADWAY.
- AT SKEWED CROSSWALKS, THE BLOCKS ARE TO REMAIN PARALLEL TO THE 5. LANE LINES AS SHOWN.
- THE BLOCKS SHALL BE PLACED SO THAT THEY ARE NOT LOCATED IN THE 6. WHEEL PATH OF THE VEHICLES
- THE BLOCKS SHALL BE A MINIMUM OF 6' LONG AND AT LEAST AS LONG AS 7. THE TRUNCATED DOMES. FOR FANNED TRUNCATED DOMES THE BLOCKS SHALL BE AT LEAST AS LONG AS THE APPROACHING SIDEWALK OR SHARED USE PATH.
- 8. THE ALTERNATE (W) AND (S) MAY BE USED WHEN BLOCKS LONGER THAN 6' (H) ARE USED


#### REVISED: 10-JULY-2014




#### PLACEMENT FOR "STOP AHEAD" MARKINGS AND STOP LINES



55 MPH SPEED LIMIT




### MARKINGS FOR RAILROAD CROSSINGS








SIGNING AND STRIPING MINNEAPOLIS DETAIL	
MINNEAPOLIS DETAIL	IEET
SHEET NAME: 2	13
SHEET NAME: 2	OF
TRAFFIC E0-TFC-SIGN-STRP-DTL - 007	266




LB/FT STUB POSTS <u>. SHALL CONFORM TO MNDOT 34</u> 01.	
5 LB/FT RISER POSTS, STRINGERS, KNEE BRACES RAL BRACES. <u>ALL SHALL CONFORM TO MNDOT 3401</u> .	
N DATA SHEETS FOR NUMBER OF POSTS, KNEE BRACES, GTHS AND SPACINGS, AS DETERMINED FROM TEM 5.3 AND 6.4.	
E THAN TWO POSTS ARE NEEDED, THE MINIMUM SPACING 545" BETWEEN POSTS.	
SIGN PANELS SHALL BE BOLTED TO STRINGERS AXIMUM INTERVALS IN ACCORDANCE WITH D STRINGER AND PANEL—JOINT DETAIL (SEE SIGNS MANUAL).	
NG (PUNCH CODE) FOR TYPE C SIGN PANELS E AS INDICATED IN THE STANDARD SIGNS MANUAL DTHERWISE SPECIFIED.	
R (VERTICAL) U POSTS SHALL BE SPLICED. DRIVEN STS SHALL BE AT LEAST 7' LONG.	
ILESS STEEL 5/16" BOLTS, WASHERS AND SERT LOCK NUTS AS SHOWN FOR ALL GROUND AND OVERHEAD MOUNTED SIGNS.	
S STEEL WASHER WITH SAME DIMENSIONS PROVIDED BETWEEN ALL NYLON WASHERS AND DS.	
G STUBS SHALL BE NO MORE THAN 4" ABOVE AND EMBEDDED AT LEAST 42".	
E BRACKET SHALL BE STEEL CONFORMING TO 306 AND GALVANIZED IN ACCORDANCE WITH 394.	
S SHALL BE USED TO SHIM OVERLAYS AND COMPONENTS AWAY FROM PANEL WHERE INTER— WITH BOLT HEADS IS ENCOUNTERED. 352.2A6.	
T TYPE C SIGNS SHALL BE REINFORCED WITH ONE LATERAL BRACE. INSTALLATIONS WHERE AL PANEL HEIGHT IS 60" OR MORE SHALL HAVE ERAL BRACES LOCATED APPROXIMATELY AT RTER POINTS.	
2 SINGLE POST TYPE C SIGNS ARE INSTALLED SIDE, THEY SHALL BE REINFORCED LATERALLY EAST 2 BRACES, BOLTED AT EACH POST AND APPROXIMATELY AT THE QUARTER POINTS.	
3 OR MORE TYPE C SIGNS ARE INSTALLED SIDE, THEY SHALL BE REINFORCED LATERALLY AST 2 BRACES, BOLTED AT EACH POST AND POST AND LOCATED APPROXIMATELY AT THE QUARTER AND S SHOWN IN MODIFIED TYPE C INSTALLATION.	
TYPE C & D SIGN	
STRUCTURAL DETAILS	
Sheet 1 of 3	
CIVIL EAST - VOLUME 10	SHEET
SIGNING AND STRIPING	14
MNDOT DETAIL SHEET 1	OF
TRAFFIC SIGN-STRP-DTL - 008	266










(1) 6" FOR WARNING PLAQUE (18"×18") 12" FOR WARNING PLAQUE (30"×30")








**AECOM** Kimley»Horn METROPOLITAN 60% SUBMISSION - 09/28/15




IDEV	VALK		
	CIVIL EAS	T - VOLUME 10	SHEET
	SIGNING A	AND STRIPING	17
	_	OT DETAIL IEET 4	OF
INE:	TRAFFIC	SHEET NAME: E0-TFC-SIGN-STRP-DTL - 011	266
		•	

.



#### NOTES;

- 1. DRILL AN 8" DIAMETER HOLE THE FULL DEPTH OF THE ANCHOR.
- 2. DRILL 3/8" HOLES ON OPPOSITE SIDES OF THE UNPUNCHED GALVANIZED STEEL SQUARE TUBE ANCHOR APPROX. 1" FROM THE BOTTOM OF THE ANCHOR. INSERT A 5/16" STAINLESS STEEL BOLT THROUGH THE HOLES AND SECURE WITH A STAINLESS STEEL LOCK NUT WITH NYLON INSERT. THE PREPUNCHED GALVANIZED STEEL SQUARE TUBE RISER (TO BE INSERTED INSIDE THE UNPUNCHED GALVANIZED SQUARE TUBE ANCHOR) WILL REST ON BOLT.
- 3. INSERT THE ANCHOR IN THE HOLE.
- 4. AFTER INSTALLATION OF THE UNPUNCHED GALVANIZED STEEL SQUARE TUBE ANCHOR, FILL THE HOLE WITH A CONCRETE MIX APPROVED BY THE ENGINEER AND LEVEL OFF THE TOP OF CONCRETE.
- 5. MAXIMUM SIGN PANEL SIZE IS 42" WIDE X 48" HIGH.
- 6. SIGN PANEL TO BE MOUNTED 7 FT ABOVE THE GROUND.




10.	DATE	BY	CHE	ECK DI	SIGN	REVISION / SUBMITTAL				
								4		
							<b>AECOM</b> Kimley »Horn			
									SOUTHWEST	
							NETROP	OUTIN	Green Line LRT Extension	
							METROP	CITAN		
							60% SUBMISSION - 09/28/15		-	DISCIPLI
							60 / SOBMISSION - 09/26/15			
								-		


sep, 21 2015 06:37 am V:\3400\_ADC\CAD\00\_EAST\PLANSHEETS\TRAFFIC\DETAILS\EO-TFC-SIGN-STRP-DTL.dwg By: brian.vi


CIVIL EAS	T - VOLUME 10	SHEET
	AND STRIPING	18
-	OT DETAIL HEET 5	OF
	SHEET NAME: E0-TFC-SIGN-STRP-DTL - 012	266

## TYPE C SIGNS, DELINEATORS & MARKERS IN CONCRETE




TRAFFIC SHEET NAME: E0-TFC-SIGN-STRP-DTL - 013	266
SHEET 6	OF
MNDOT DETAIL	19 05
CIVIL EAST - VOLUME 10 SIGNING AND STRIPING	SHEET
	<u></u>
POST SUPPORT IN CONCRETE	
GNPOST SUPPORTS SHALL BE INSTALLED LUMB AND APPROXIMATELY 1/2" ABOVE THE DP OF THE CONCRETE SURFACE.	
EAL BOTTOM OF SIGNPOST SUPPORT WITH JCT TAPE BEFORE INSTALLATION IN NEW DNCRETE.	
TRAL NOTES:	
LOW	
- LOW	
AS SHUWN BELUW:	
WEDGE SHOULD ALIGN PARALLEL TO THE ROAD	
EDIAN PLACEMENT ) U CHANNEL SOCKETS	





#### REAR DELINEATION FOR R4-7 (NO SCALE)



RE	EAR DELNEATIO DIMENSI		
SIZE	12"x 30"	15 <b>"</b> x 36"	18"x 48"
MOUNT ON	24"x 30"	30"× 36"	36"x 48"
RADIUS	1.50"	1.88"	2.25"
A	5.00"	6.00"	6.00"
В	2.50"	3.00"	3.00"

COLOR: YELLOW & BLACK DG3 SIGN SHEETING ONLY.





SHEET

21

OF


266







DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL			
							-
					<b>AECOM</b> Kimley »Horn		COUTURATE
					-		Green Line LRT Extension
						METROPOLITAN	Green Line LRT Extension
					60% SUBMISSION - 09/28/15		


2			
	(4) (5)		
	3		
	4		
	)		
i			
RTNAME	DET	AILS	
Q. HD., CUP PT.	5/8"-11"x1 1/2" ZINC OF	R CAD PI	
	#4x8" 2		
	30" PRECAST FOUNDA		
WITH WIDE FACE TOWAR SSEMBLY.	RDS		
PPROX. 90° AT APPROX.			
D.		NO SCALE	
COLLAR	≀- SIGN	STANDARD	
2" SIGN POST	- ASSEMBLY	PLATE NO.	
TRAF-5120,	TRAF-5130	TRAF-5110-R1	
	AST - VOLUM		SHEET
	IG AND STRIP		23
MINN	EAPOLIS DET/ SHEET 2	AIL	OF
	SHEET NAME:	GN-STRP-DTL -	017 266






 NO.	DATE	BY CHECK DESIGN REVISION / SUBMITTAL	<b>AECOM</b> Kimley »Horn		
			60% SUBMISSION - 09/28/15	DIS	SCIPLI







STA	L							
Ξ	BY	CHECK DESIGN	REVISION / SUBMITTAL					
				1				
				-				
				1	<b>AECOM</b> Kimley»Horn			
				1			SOUTHWEST	
				1		AUTTRODOL ITAN	Green Line LRT Extension	
				-		METROPOLITAN		
				-				DISCIPLINE:
				1	60% SUBMISSION - 09/28/15			

	0 15	30 60
		ZONTAL N FEET
	=======================================	
	「 - VOLUME 10 H AVE S	SHEET 25
SIGNING A	ND STRIPING	25 OF
PLINE:	SHEET NAME:	266
TRAFFIC	E1-TFC-SIGN-STRIPE -	001





		0 15 30 HORIZONT/	60 AL
S 6+00	T-+00	SCALE IN	FEET
			SHEET
8TH SIGNING A	F - VOLUME 10 I AVE S AND STRIPING		26 OF
STA. 1+00	TO STA. 7+00	I-STRIPE - 002	266







DATE












о» <b>\</b> • <b>\</b>	t total	
N		
	15+tao	
		$\setminus$
	15100 25100 t 000	
\ \		
16+0C		$\mathbf{N}$
		$\setminus$
NOTES: 1. SIGNS SHALL BE PLACEI ON SIGNING AND STRIPII SHEETS.	D AS DETAILED NG DETAIL	
1 FURNISH & INSTALL 2 INPLACE		- 4
3 SALVAGE	0 15 30	60
4 REMOVE	HORIZONTA	
5 INSTALL	SCALE IN	FEET
		SHEET
		32
	ND STRIPING TO STA. 17+00	OF
	SHEET NAME: E1-TFC-SIGN-STRIPE - 008	266








NOTES: 1. SIGNS SHALL BE PLACED AS DETAILED ON SIGNING AND STRIPING DETAIL SHEETS.		
1FURNISH & INSTALL2INPLACE3SALVAGE4REMOVE5INSTALL		
NO.         DATE         BY         CHECK DESIGN REVISION / SUBMITTAL	60% SUBMISSION - 09/28/15	METROPOLITAN SOUTHWEST
	80% SUBMISSION - 09/28/15	




CIVIL EAST - VOLUME 10			SHEET
LOUISIANA AVE S			
SIGNING AND STRIPING			OF
STA. 10+00 TO STA. 14+50			
:		SHEET NAME:	266
	TRAFFIC	E2-TFC-SIGN-STRIPE - 001	230










. 21 2015 09:52 gm V: \3400\_ADC\CAD\00\_EAST\PLANSHEETS\TRAFFIC\SIGNING\_STRIPING\E2-TFC-SIGN-STRIPE.dwg By. brian.v





× čo	
	SHEET
CIVIL EAST - VOLUME 10 EDGEWOOD AVE	38
SIGNING AND STRIPING STA. 0+00.00 TO STA. 2+05.43	OF
TRAFFIC SHEET NAME: E2-TFC-SIGN-STRIPE - 005	266















CIVIL EAST	۲ - VOLUME 10	SHEET
BELTL	INE BLVD	42
SIGNING A	ND STRIPING	OF
STA. 112+00	TO STA. 118+00	UF
	SHEET NAME:	266
TRAFFIC	E2-TFC-SIGN-STRIPE - 008	













NOTES:           1.         SIGNS SHALL BE PLACED AS DETAILED ON SIGNING AND STRIPING DETAIL           1.         FURNISH & INSTALL           2.         INPLACE           3.         SALVAGE           4.         REMOVE           5.         INSTALL		
NO.         DATE         BY         CHECK DESIGN REVISION / SUBMITTAL           6         -         -         -           75         -         -         -           80         -         -         -           91         -         -         -           92         -         -         -           93         -         -         -           94         -         -         -           95         -         -         -           96         -         -         -           97         -         -         -           98         -         -         -           99         -         -         -           90         -         -         -           90         -         -         -           90         -         -         -           91         -         -         -           92         -         -         -           93         -         -         -           94         -         -         -           95         -         -         -	AECOM Kimley »Horn	
See	60% SUBMISSION - 09/28/15	DISCIPLIN




				CHOWEN AVE S	
		<u>12+00</u>	13+00	<u>14+00</u>	<u>15+00</u>
		2+00	3+00	4+00 CSAH 2	25 (W LAKE ST)
	DREW AVE S	A A A A A A A A A A A A A A A A A A A			
NOTES: 1. SIGNS SHALL BE PLACED AS DETAILED ON SIGNING AND STRIPING DETAIL SHEETS. 1 FURNISH & INSTALL 2 INPLACE 3 SALVAGE 4 REMOVE 5 INSTALL					
NO. DATE BY CHECK DESIGN REVISION / SUBMITTAL					
		AECOM Kimle			
		60% SUBMISSION - 0			DISCIPLINE









		SCALE	IN	FEET
	- VOLUME 10			SHEE
				50
CSAH 25	(W LARE 31)			
SIGNING A	ND STRIPING			OF
SIGNING A				OF 266




DATE






CIVIL EAST	- VOLUME 10	SHEET
	AKE PKWY	53
	ND STRIPING	
	TO STA. 52+00	OF
	SHEET NAME: E3-TFC-SIGN-STRIPE - 010	266




l l l		
	<	
152+00		
154		
	, 	
00		
$\mathcal{T}$		
	_	
	_	
	-	
	_	
	<b>`</b>	
	~	
======	_	
		SHEET
CIVIL EAST - VOL		JHEEI
BURNHAM R		54
SIGNING AND ST		OF
STA. 147+00.00 TO ST	A. 152+00.00	
LINE: SHEET NAME: SHEET NAME:	E3-TFC-SIGN-STRIPE - 011	266


V: \3400_ADC\CAD\00_EAST\PLANSHEETS\TRAFFIC\SIGNING_STRIPING\E3-TFC-SIGN-STRIPE.dwg By: caitlin.wotruba	NUTES: 1. SIGNIS SHALL BE PLACED AS DETAILED ON BISINING AND STRIPING DETAIL 2. INFLACE 3. SALVAGE 4. REMOVE 3. INSTALL 1. INFLACE 3. SALVAGE 4. REMOVE 3. INSTALL 1. INFLACE 4. REMOVE 5. INSTALL 1. INFLACE 5. INSTALL 1. INFLACE 1. INFLACE 5. INSTALL 1. INFLACE 5. INSTALL 1. INFLACE 5. INSTALL 1. INFLACE 5. INSTALL 1. INFLACE 1. INFLA	3538+00 3538+00 3538+00 1825400 1825400 1825400 1825400 1825400 1825400 1825400 18264000 18264000 182640000 182640000 18264000000000000000000000000000000000000	$\frac{1}{10}$
21 2015 08:25 am		<b>AECOM</b> Kimley»Horn	METROPOLITAN SOUTHWEST
Sep,		60% SUBMISSION - 09/28/15	

8 ó č V: \3400 25 08: 2015



RIPING (E3-TFC-SIGN-STRIPE.dwg By: cattin.wotruba	NO PARCINE → → → → → → → → → → → → → → → → → → →	3+00 AVE S		NO 000000000000000000000000000000000000
NOTES: 1. SIGNS SHALL BE PLACED AS D ON SIGNING AND STRIPING DET SHEETS. 1. FURNISH & INSTALL 2. INPLACE 3. SALVAGE 4. REMOVE 5. INSTALL 1. SIGNS SHALL BE PLACED AS D SHEETS. 1. FURNISH & INSTALL 2. INPLACE 3. SALVAGE 4. REMOVE 5. INSTALL 1. SIGNS SHALL BE PLACED AS D SHEETS. 1. SIGNS SHALL SHEETS. 1. SIGNS SHEETS. 1. SI		SUBMISSION -	METROPOLITAN	







## FOR REFERENCE ONLY

D. DATE	BY CHECK DESIGN REVISION / SUBMITTAL	<b>AECOM</b> Kimley»Horn	s a der
		60% SUBMISSION - 09/28/15	DISCIPLI

360+00		
		ter t
	SCALE	15 30 60 HORIZONTAL E IN FEET
W 22ND ST	ST - VOLUME 10 / THOMAS AVE S AND STRIPING	SHEET 57 OF
	SHEET NAME: E3-TFC-SIGN-STR	266







, 21 2015 08:29 am V:\3400\_ADC\CAD\00\_EAST\PLANSHEETS\TRAFFIC\SIGNING\_STRIPING\E4-TFC-SIGN-STRIPE.dwg By: (

(2) (2) TH 394 ON RAMP **← EAST ♦**EAST 2R (n)(n) $\mathbf{A}$ 15+50 STA. 16+00 \_<u>17+00</u>\_ 18+00 Y \_\_\_\_\_\_ 19+00 20+00 21+00 MATCH LINE  $\sim$ CSAH 2 (PENN AVE S) OFF RAMP (N) $(\mathcal{E})$ SOLUCIONALIED BANALED BANALED BANALED BANALED BANALES BANALES BANALES BANALES **ONEWAY** 2 TH 394 (N)NOTES: 1. SIGNS SHALL BE PLACED AS DETAILED ON SIGNING AND STRIPING DETAIL SHEETS. 1 FURNISH & INSTALL 2 INPLACE 3 SALVAGE (4) REMOVE 5 INSTALL NO. DATE BY CHECK DESIGN REVISION / SUBMITTAI **AECOM** Kimley»Horn METROPOLITAN 60% SUBMISSION - 09/28/15


1il

ii






21 2015 08:30 am V: \3400\_ADC\CAD\00\_EAST\PLANSHEETS\TRAFFIC\SIGNING\_STRIPING\E4-TFC-SIGN-STRIPE.dwg BY:





	VAN WHITE STATION
caitlin.wotruba	
V: \3400_ADC\CAD\00_EAST\PLANSHEETS\TRAFFIC\SIGNING_STRIPING\E4-TFC-SIGN-STRIPE.dwg By:	
NG_STRIPING∖E4-	
S\TRAFFIC\SIGNI	NOTES:
<b>VSHEET</b>	1. SIGNS SHALL BE PLACED AS DETAILED ON SIGNING AND STRIPING DETAIL SHEETS.
0_EAST\PLAN	1 FURNISH & INSTALL 2 INPLACE
\CAD\0	3 SALVAGE
400_ADC	(4)     REMOVE       (5)     INSTALL
am V: \34	NO. DATE BY CHECK DESIGN REVISION / SUBMITTAL
2015 08: 31	
Sep, 21	60% SUBMISSION - 09/28/15
.,	

A SSENCE D STATE		→ AL FEET
CIVIL EAST	- VOLUME 10	SHEET
VAN WHITE S	TATION ACCESS	63
	ND STRIPING	OF
	TO STA. 5+00	
	E4-TFC-SIGN-STRIPE - 006	266



	t.	
	0 15 30 HORIZONT. SCALE IN	AL FEET
VAN WHITE S SIGNING A STA. 5+00	- VOLUME 10 TATION ACCESS ND STRIPING TO STA. 8+68	SHEET 64 OF
	SHEET NAME: E4-TFC-SIGN-STRIPE - 007	266






.ep. 21 2015 08:32 am V: \3400\_ADC\CAD\00\_EAST\PLANSHEETS\TRAFFIC\SIGNING\_STRIPING\E4-TFC-SIGN-STRIPE.dwg By: cai


	AST - VOLUME 10	SHE
DUN	WOODY BLVD	SHE 66
DUN SIGNIN		

HORIZONTAL IN


FEET


SCALE







CIVIL EAS	- VOLUME 10	SHEET
VAN WHITE N	IEMORIAL BLVD	68
SIGNING A	ND STRIPING	OF
STA. 733+00	TO STA. 735+00	UF
TRAFFIC	SHEET NAME: E4-TFC-SIGN-STRIPE - 011	266









CIVIL EAST - VOLUME 10 ROYALSTON AVE N SIGNING AND STRIPING CLINE: TRAFFIC SHEET NAME: E4-TFC-SIGN-STRIPE - 013









HORIZONTAL IN


SCALE

FEET


NOTES: 1. SIGNS SHALL BE PLACED AS DETAILED ON SIGNING AND STRIPING DETAIL SHEETS.









, 21 2015 08:35 am V:\3400\_ADC\CAD\00\_EAST\PLANSHEETS\TRAFFIC\SIGNING\_STRIPING\E4-TFC-SIGN-STRIPE.dwg By: (





CIVIL EAST - VOLUME 10						
BORDER AVE						
SIGNING AND STRIPING STA. 67+50 TO STA. 73+25						







0 15 30	
0 15 30	
	60
HORIZONTAL SCALE IN	FEET
CIVIL EAST - VOLUIVIE TU	IEET
SIGNING AND STRIPING	77
	OF









A A A A A A A A A A A A A A A A A A A		0 25 50 HORIZONTA SCALE IN	100 AL FEET
		0 25 50 HORIZONTA SCALE IN	100 AL FEET
7 <b>T</b> I	T - VOLUME 10 H ST N IKEWAY STRIP		SHEET 80
	SHEET NAME: E4-TFC-7TH-SIGI		OF 266




	0 25 50 HORIZONTA	100 NL FEET
(GLE VINDOD) ALE		
Г - VOLUME 10 Н ST N		SHEET 81
IKEWAY STRIPIN	IG	OF
SHEET NAME: E4-TFC-7TH-SIGN-	STRIPE - 004	266




2015 07:49 am V: \3400\_ADC\CAD\00\_EAST\PLANSHETS\TRAFFIC\SIGNING\_STRIPING\E1-TFC-TRL-SIGN.dwg By: cai




21 2015 07:50 am V:\3400\_ADC\CAD\00\_EAST\PLANSHEETS\TRAFFIC\SIGNING\_STRIPING\E1-TFC-TRL-SIGN.dwg By: caitlin







21 2015 07:53 am V: \3400\_ADC\CAD\00\_EAST\PLANSHEETS\TRAFFIC\SIGNING\_STRIPING\E1-TFC-TRL-SIGN.dwg By: caitlin.wot





NO.	DATE	BY		REVISION / SUBMITTAL	<b>AECOM</b> Kimley»Horr	METROPOLITAN	SOUTHWEST Green Line LAT Extension	
					60% SUBMISSION - 09/28/15			DIS




NO.	DATE	BY	CHEC	KDESIC	GN REVISION / SUBMITTAL		
						<b>AECOM</b> Kimley »Horn	
						60% SUBMISSION - 09/28/15	










AECOM Kimley»Hor	 
60% SUBMISSION - 09/28/15	








Ś	NO. DATE BY CHECK DESIGN REVISION / SUBMITTAL			
Ê				
: 29		<b>AECOM</b> Kimley»Horn		
07:				
2015		-		
21 2				
d,		60% SUBMISSION - 09/28/15	Di	DISCIPL
ů,				




















L						
	NO. DATE	BY	CHECK DESIGN REVISION / SUBMITTAL	<b>AECOM</b> Kimley»Horr		
				60% SUBMISSION - 09/28/15	DIS	SCIP







бх
ð.
ß
S I
e TFC – TRI
ပ်
F
EZ
6
N N
Ч Ч
LN N
ല്
≨
8
IC/SI
Ĕ
₹AF
0_ADC\CAD\00_EAST\PLANSHEETS\TRAFFI
NSH
¥.
Ļ
EAST
Х
0_EA
Š
Ā
>
B
٩
8
/34
~
2 am <:
42
80
0
21 2015 08:
й
2





NC	. DATE	BY CHECK DESIGN REVISION / SUBMITTAL		
			AECOM Kimley »Horn	
			METROPOLITAN Dream Line Litt Estension	
-				
			60% SUBMISSION - 09/28/15	




NO	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL				—
		_							
						<b>AECOM</b> Kimley»Ho	n A		
								SOUTHWEST	
							METROPOLITAN	Green Line LRT Extension	
								DI	DISCIP
						60% SUBMISSION - 09/28/15			








	AECOM Kimley »Horn SOUTHWEST	AECOM Kimley »Horn SOUTHWEST	AECOM Kimley »Horn SOUTHWEST	N	NO.	DATE	BY C	HECK	DESIGN	REVISION / SUBMITTAL	
AECOM Kimley »Horn											
AECOM Kimley »Horn											




	DATE	DV	CUECK	DECION			1		
NO	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL	<b>AECOM</b> Kimley»Horr		SOUTHWEST	
						60% SUBMISSION - 09/28/15	METROPOLITAN	Green Line LRT Extension	DISCIP



# FOR REFERENCE ONLY


NO.	DATE	BY CHECK DESIGN REVISION / SUBMITTAL	<b>AECOM</b> Kimley»Horr	
			60% SUBMISSION - 09/28/15	DISCIPL

$\circ$			
0	Ň,		
<b>с</b>			
		۲.	
┌─ & CEDAR LAKE LRT REGIONAL	TRAIL	ЛТСН	
		MATCH LINE - STA 297+00	
296+00	297	ш ' '	
		TA 2	
		297+(	
		30	
			*
• •	+	E	[
	+	l V	
		0 15 30	60
0		HORIZONTA	
		SCALE IN	FEET
			<u></u>
			SHEET
CEDAR LAKE LR SIC	SNING		108
			OF
STA 290+00			266




ADC\CAD\00_EAST\PLANSHEETS\TRAFFIC	ON SI SHEET	GNING AND	PLACED AS DETAILED STRIPING DETAIL						
\3400_ADC\CAD\00_EA	<ul> <li>2) INPLA</li> <li>3) SALV</li> <li>4) REMC</li> <li>5) INSTA</li> </ul>	/AGE DVE							
2015 08:47 am V	NO. DATE	BY CHEC	K DESIGN REVISION / SUBN	ITTAL		<b>AECOM</b> Kimley»Horn	METROPOLITAN	SOUTHWEST Green Line Lift Estimation	
Sep, 21					-	60% SUBMISSION - 09/28/15			DISCIPLINE:


CIVIL EAST - VOLUME 10					
CEDAR LAKE LRT REGIONAL TRAIL					
SIGNING					
STA 297+00 TO STA 304+00					
	E2-TFC-TRL-SIGN - 015	266			





caitlir
ВŻ
FIC\SIGNING_STRIPING\E2-TFC-TRL-SIGN.dwg
UING_STRIPING
FIC\SIGNIN
<b>TRAF</b>
<pre>H7 am V: \3400_ADC\CAD\00_EAST\PLANSHEETS\TRAFFIC</pre>
\00_EAST
\CAD\0
00_ADC
V: \340
Ê
08: 47
21 2015 08:47
'n


DATE














NO	. DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL		-
NU		BY				AECOM Kimley »Horn	
						METROPOLITAN SOUTHWEST	
						60% SUBMISSION - 09/28/15	DISCIPLINE

	<i>J.</i>
F	
0 15 30 HORIZONT SCALE IN	60 AL FEET
CIVIL EAST - VOLUME 10 CEDAR LAKE LRT REGIONAL TRAIL	SHEET
SIGNING	OF
STA 339+00 TO STA 340+51.85 TRAFFIC E2-TFC-TRL-SIGN - 021	266
E2-IFC-IRL-SIGN - 021	







//////////////////////////////////////	MATCH LINE - STA 354+50	
354+00	STA	
	354+5	
L	50	x
0 0		
	HORIZONT SCALE IN	60 AL FEET
	T - VOLUME 10 RT REGIONAL TRAIL	SHEET 117
	GNING ) TO STA 354+50	OF
	SHEET NAME: E3-TFC-TRL-SIGN - 002	266





21 2015 08:56 am V: \3400\_ADC\CAD\00\_EAST\PLANSHEETS\TRAFFIC\SIGNING\_STRIPING\E3-TFC-TRL-SIGN.dwg By: caitin.







	0 15 30 HORIZONTA SCALE IN	60 FEET
CEDAR LAKE LF	Γ - VOLUME 10 RT REGIONAL TRAIL GNING	SHEET 120
	O STA 372+08.19 SHEET NAME: E3-TFC-TRL-SIGN - 005	OF 266











L						
	NO. DATE	BY		N REVISION / SUBMITTAL	<b>AECOM</b> Kimley»Horn	
					60% SUBMISSION - 09/28/15	DISCIPI

NOTES: 1. SIGNS SHALL BE PLACED AS DETAILED ON SIGNING AND STRIPING DETAIL 3. FURNISH & INSTALL 4. INPLACE 5. INSTALL 5. INSTALL				
		$\begin{array}{c} + & - & \frac{411+00}{+} \\ \hline & + & - & - & - & - \\ \hline 511 + & 00 & & - & - & - \\ \hline & & & 512 + 00 \\ \hline \\ & & & & & & \\ \\ & & & & & & \\ \\ & & & & & & \\ \end{array}$	412+00	ENILWORTH TRAIL
	0728	411+00	412+00	13+00
- STA 408+00	2805+00 	• •	٠	


4

NARROWS







CIVIL EAST - VOLUME 10					
KENILWORTH TRAIL					
SIGNING					
STA 415+00 TO STA 422+00					
NE:	SHEET NAME:	266			
TRAFFIC	E3-TFC-TRL-SIGN - 011	200			




DISCIPLINE




CIVIL EAS	CIVIL EAST - VOLUME 10					
KENILWORTH TRAIL						
SIGNING						
STA 422+00	STA 422+00 TO STA 427+50					
IE:	SHEET NAME:	266				
TRAFFIC	E3-TFC-TRL-SIGN - 012	200				




E3-TFC-TRL-SIGN - 013 TRAFFIC







NO.	DATE	BY	CHECK	DESIGN	N REVISION / SUBMITTAL				
						<b>AECOM</b> Kimley»Horn			
								SOUTHWEST	
							METROBOLITAN	Green Line LRT Extension	
							METROPOLITAN		
						60% SUBMISSION - 09/28/15			DISCIPLINE
						00 /0 30 BINI 3310 N - 09/20/15			




CIVIL EAST - VOLUME 10					
KENILWORTH TRAIL					
SIGNING					
STA 441+50 TO STA 443+18.31					
TRAFFIC E3-TFC-TRL-SIGN - 015					




MATCHLINE - STA 449+50 		FEET
	- VOLUME 10 DRTH TRAIL	SHEET 131
SIC	SNING	OF
INE:	1 TO STA 449+50 Sheet name:	266
TRAFFIC	E4-TFC-TRL-SIGN - 001	




ep, 21 2015 08:50 am V:\3400\_ADC\CAD\00\_EAST\PLANSHEETS\TRAFFIC\SIGNING\_STRIPING\E4-TFC-TRL-SIGN.dwg By: bri




L						
	NO. DAT	E BY		REVISION / SUBMITTAL	AECOM Kimley »Horn	r
F					60% SUBMISSION - 09/28/15	DISCIPLI






21 2015 08:51 am V: \3400\_ADC\CAD\00\_EAST\PLANSHEETS\TRAFFIC\SIGNING\_STRIPING\E4-TFC-TRL-SIGN.dwg By: |





NO.	DATE	BY	CHECK	DESIGN REVISION / SUBMITTAL	AECOM Kimley »Horn	
					60% SUBMISSION - 09/28/15	DISC



NO.	DATE	BY	CHECK	DESIGN	N REVISION / SUBMITTAL				
						<b>AECOM</b> Kimley»Horn			
								SOUTHWEST	
							METROPOLITANI	Green Line LRT Extension	
							METROPOLITAN		
						60% SUBMISSION - 09/28/15			DISCIPLIN
						00 /0 30 BINI 3310 N - 09/20/13			

r		
<u></u>	×	
1	<u>  N  </u>	
<u></u>		
<u> </u>	505+00	
		1
	x x	×
	<i>.</i>	/ I
	P	
	V	
8	,	
	0 15 30	60
		ITAL
	HORIZON SCALE IN	FEET
		1
		1
		1
_		
Y		
-		1
		SHEET
	۲ - VOLUME 10	
CEDAR I	LAKE TRAIL	137
	GNING	
		OF
STA 449+71	TO STA 504+26	
IPLINE:		266
TRAFFIC	E4-TFC-TRL-SIGN - 00	7





×, ∖		
\.\		-4-
`\ <b>\</b>		<b>N</b>
``\		5 30 60 HORIZONTAL IN FEET
	SCALE	IN FEET
CIVIL EAS	ST - VOLUME 10	SHEET
LUCE LINE I	REGIONAL TRAIL	SHEET 139
LUCE LINE I Si		

			TRAFFIC LEGEN	ID		
INPL	LACE	FURN	IISH & INSTALL	INPL	ACE EQUIPMENT LABELS	
-0-	POWER POLE		POWER POLE		OT AND CITY OF MINNEAPOLIS	
Ч	PUSHBUTTON PEDESTAL	●⊣	PUSHBUTTON PEDESTAL	$\langle \underline{3} \rangle$	SIGNAL BASE NO.	
——×́+	LUMINAIRE		LUMINAIRE	(3-2)	SIGNAL HEAD NO./FLASHER HEAD NO	).
	SIG. POLE W/MASTARM	<b></b>	SIG. POLE W/MASTARM	<u>/2</u>	LUMINAIRE NO.	
$\boxtimes$	PEDESTAL POLE		PEDESTAL POLE	(A)	CONTROLLER CABINET	
$\rightarrow$	SIGNAL FACE	+	SIGNAL FACE W/BACKSHIELD	( <u>B</u> )	SIGNAL SERVICE CABINET	
$\rightarrow$	WARNING FLASHER	$\rightarrow$	WARNING FLASHER	(C)	SOURCE OF POWER	
	TRAFFIC PAD W/CONTROLLER AND CABINET, AND SERVICE PANEL W/METER AND DISCONNECT	$\prec \forall$	VIDEO DETECTOR		NEPIN COUNTY	
/		<del><ir-< del=""></ir-<></del>	INFRARED DETECTOR		CONTROLLER AND CABINET	
-< _			TRAFFIC PAD W/CONTROLLER AND CABINET, AND SERVICE PANEL W/METER AND DISCONNECT	(SP) 1	SERVICE PANEL WITH METER AND DIS	CONNECT
-	PUSHBUTTON	,		$\left< \frac{MA}{1} \right>$	MAST ARM	
D—	EVP CONFIRMATORY LIGHT	→	PEDESTRIAN INDICATION	$\langle \overline{SA} \\ 1 \rangle$	PEDESTAL POLE	
//~<	EVP DETECTOR	-		$\begin{pmatrix} D1\\ 1 \end{pmatrix}$	DETECTOR LOOP	
_(//-< ▽▽	EVP DETECTOR AND CONFIRMATORY LIGHT	-4	EVP CONFIRMATORY LIGHT	APS 1	PUSHBUTTON STATION	
	RAIL AUTOMATIC GATE	_#>	EVP DETECTOR	$\begin{pmatrix} HH \\ 1 \end{pmatrix}$	HANDHOLE	
	LOOP DETECTOR WIRE	_ <b>€</b> // →	EVP DETECTOR AND CONFIRMATORY LIGHT			
	NMC CONDUIT		RAIL AUTOMATIC GATE			
$\top$	POST-MOUNTED SIGN	H	RAIL CROSSING FLASHER		ABE	BREVIATIONS
工 _	POST-MOUNTED SIGNS - BACK TO BACK		LOOP DETECTOR WIRE		3-2 (EG) AWF	SIGNAL HEAD NUMBI
	HANDHOLE	=====	NMC CONDUIT		EVP FYA GRN	EMERGENCY VEHICLE FLASHING YELLOW A GREEN INDICATION
	LOOP DETECTOR		POST-MOUNTED SIGN		GR. RD. IP	GROUND ROD INPLACE
Ň	TRAFFIC FLOW ARROW		POST-MOUNTED SIGNS - BACK TO BACK		INS. GR. LED	INSULATED GROUND
+	ARROW PAVEMENT MARKING		HANDHOLE		LUM P1–1 (EG) PB2–1 (EG)	LUMINAIRE PEDESTRIAN HEAD ( PUSHBUTTON (PHAS
		$\bigcirc$	VIDEO DETECTION ZONE		PED SOP	PEDESTRIAN SOURCE OF POWER
			LOOP DETECTOR		STA WLK	STATION WALK INDICATION YELLOW INDICATION
			TRAFFIC FLOW ARROW		YEL RED F&I	RED INDICATION FURNISH AND INSTA
		7	ARROW PAVEMENT MARKING		Ø2 HH-2 (EG)	SIGNAL PHASE NUME HANDHOLE NUMBER
					D2-1 (ÈG) NMC C.D.	DETECTION ZONE (P NON METALLIC CONE COUNTDOWN
					С.Д.	COONTDOWN
BY CHECK DESIGN	REVISION / SUBMITTAL					
			<b>AECOM</b> Kimley»Hor	n 🛛	SOUTHWEST	
				MET		

~

60% SUBMISSION - 09/28/15

METROPOLITAN

DISCIPLINE:

FURNISH AND INSTALL EQUIPMENT LABELS					
MNDC	T AND CITY OF MINNEAPOLIS				
$\langle 3 \rangle$	SIGNAL BASE NO.				
3-2	SIGNAL HEAD NO./FLASHER HEAD NO.				
$\overline{2}$	LUMINAIRE NO.				
(A)	CONTROLLER CABINET				
B	SIGNAL SERVICE CABINET				
$\overline{\mathbb{O}}$	SOURCE OF POWER				
HENN	EPIN COUNTY				
	CONTROLLER AND CABINET				
SP 1	SERVICE PANEL WITH METER AND DISCONNECT				
MA 1	MAST ARM				
(SA) 1	PEDESTAL POLE				
	DETECTOR LOOP				
APS 1	PUSHBUTTON STATION				
HH 1	HANDHOLE				
	E 3, NO. 2)				
FLASHER E PRE-EM					
ARROW					
)					
DE					
(PHASE 1, SE 2, NO.					

ICATION NDICATION ATION CATION AND INSTALL HASE NUMBER E NUMBER (NO. 2) N ZONE (PHASE 2, NO. 1) ALLIC CONDUIT WN

<b>CIVIL EAST - VOLUME 10</b>
TRAFFIC SIGNAL
NOTES AND LEGEND


SHEET 140


OF

266

TRAFFIC


SHEET NAME: E0-TFC-SIG-DTL - 001





GNAL CON	TROL POINT	rs	DISTANCE TO FRONT OF	DISTANCE TO BACK OF
IAL NO.	Х	Y	LANDING (FT)	
PB2—1	-	-	А	В
°B4-2	-	-	С	D

OF



4	Position DT (	Connector	(3 Section Head/DWK/WLK)
Wire to Control Cabinet	Connector pin #	Wire to Signal Indication	Signal Indication
R or R/BLK or BLK	1	R	RED or DWK
O or O/BLK or BLK/WH or BLK	2	BLK/R	YEL or WLK
BL or BL/BLK or BLK/R or BLK	3	BLK	GRN or SPR
WH or WH/BLK or WH/R	4	WH	NEU

4 Position DT Connector (EVP LHT/LUM/ (Used with 3 Conductor Cable Only) VID CAM/ENF LHT)			
Wire to Control Cabinet	Connector pin #	Wire to Signal Indication	Signal Indication
BLK	1	BLK	EVP LHT or LUM or RED or YEL or VID CAM or ENF LHT
(Not Used)	2	(Not Used)	(Not Used) (See Note #8)
G	3	G	EQ.G
WH	4	WH	NEU

4 Position DT Connectors (Use Two Connectors for 5 Section FYA Cluster Heads)				
12 Conductor Wire to Control Cabinet	Connector pin #	4 Conductor to Signal Indication	Signal Indication	
R	1	R	RED	
0	2	BLK/R	YEL	
BL	3	BLK	GRN	
WH	4	WH	NEU	
R/BLK	1	R	FYA	
0/BLK	2	BLK/R	YLA	
BL/BLK	3	BLK	GLA	
WH/BLK	4	WH	NEU	

	6 Position DT Connector		
Wire to Control Cabinet	Connector pin #	Wire to Signal Indication	Signal Indication
R	1	R	RED
0	2	0	YEL
BL	3	BL	GRN
WH	4	WH	NEU
0/BLK or BLK/R (6/C)	5	BLK/R	YLA or FYLA
BL/BLK or BLK (6/C)	6	BLK	GLA

WIRE COLOR CODE KEY		
R	Red	
0	Orange	
BL	Blue	
WH	White	
BLK	Black	
BRN	Brown	
CL	Clear	
G	Green	
R/BLK	Red with Black Stripe	
0/BLK	Orange with Black Stripe	
BL/BLK	Blue with Black Stripe	
WH/BLK	White with Black Stripe	
WH/R	White with Red Stripe	
BLK/WH	Black with White Stripe	
BLK/R	Black with Red Stripe	

BLK BLK BLK	/WH /R R
DLE CO	DNNECTIC
	Тур
	1/C#2
	1/C#6
	1/C#6
	2/C#14
	3/C#14
	4/C#14
	6/C#14

12/C#1 6PR#19 3/C#20

WH BLK

BLK


WH

₩ŀ

R/BLK O/BLK BL/BLK WH/BLK

N	OTES:
1.	DT04-P RECE
	BASE/JUNCT
2	DT06- S PU

- 2. D106
- 3.
- /JUNCTION BOX. 4.
- 6.
- 7.
- 8.
- (PART # 114017).
- NO. DATE BY CHECK DESIGN REVISION / SUBMITTAL **AECOM** Kimley»Horn **SOUTHWEST** METROPOLITAN DISCIPLIN 60% SUBMISSION - 09/28/15





WIRE SPECIFICATION CHART			
pe	Name	Specification Number	
	Power Conductors	3815.2B.1	
	Power Conductors	3815.2B.1	
INS.GR.	Grounding Conductors	3815.2B.5	
1	Loop Detector Lead—In Cable	3815.2C.4	
1	Signal Control Cable	3815.2C.3	
1	Signal Control Cable	3815.2C.3	
1	Signal Control Cable	3815.2C.3	
4	Signal Control Cable	3815.2C.3	
)	Telephone Cables Outdoor	3815.2C.6.b	
C	EVP Detector Cable	3815.2C.5	

EPTACLE SHALL BE TERMINATED TO THE WIRING HARNESS RUNNING FROM THE TION BOX OF THE POLE TO SIGNAL INDICATIONS. PLUG SHALL BE TERMINATED TO THE CABLES RUNNING FROM THE TRAFFIC SIGNAL CABINET TO THE BASE/JUNCTION BOX OF THE POLE. THERE SHALL BE A MINIMUM OF 24 INCHES OF SLACK ON EACH CABLE IN EVERY POLE BASE STRIP A MAXIMUM OF 6 INCHES OF THE OUTER JACKET OF EACH SIGNAL CABLE. 5. STRIP .250 INCHES OF INSULATION FROM EACH INDIVIDUAL CONDUCTOR. CRIMP PINS OR SOCKETS USING RATCHETING TYPE CRIMPING TOOL HDT-48-00. NO OTHER CRIMPING TOOL WILL BE ALLOWED. WIRES MUST BE TERMINATED AS DETAILED IN TABLES DEPENDING ON WIRE COUNT. ANY UNUSED PIN MUST HAVE A SEALING PLUG PLACED IN BOTH THE PLUG & RECEPTACLE

9. LABEL EACH HALF OF THE CONNECTOR (PLUG AND RECEPTACLE) WITH THE DEVICE DESIGNATION (AS INDICATED IN THE WIRING DIAGRAM) USING A PERMANENT BLACK MARKER.

CIVIL EAST - VOLUME 10			SHEET
	TRAFFIC SIGNAL		
	MNDOT DETAIL SHEET 3		OF
INE:	TRAFFIC	BO-TFC-SIG-DTL - 004	266
		•	





## NOTES:


1.) POLE SHAFT SHALL BE BACK RAKED TO SET PLUMB UNDER NORMAL LOAD.


2.) SEE SPECIAL PROVISIONS FOR PAINTING AND GALVANIZING REQUIREMENTS


OF MAST ARM SIGNAL POLES.


; [	NO.	DATE	BY	CHECH	DESIG	N REVISION / SUBMITTAL				
-										
5										
3										
i T							<b>AECOM</b> Kimley»Horn			
5									SOUTHWEST	
								METROPOLITANI	Green Line LRT Extension	
								METROPOLITAN	$\mathbf{i}$	
							60% SUBMISSION - 09/28/15			DISCIP
							60% SUBMISSION - 09/26/15			


	<b>CIVIL EAST - VOLUME 10</b>				
	TRAFFIC SIGNAL				
		OUNTY DETAIL	OF		
LINE:	TRAFFIC	SHEET NAME: E0-TFC-SIG-DTL - 006	266		














ħ									
; [	NO.	DATE	BY	CHECK DES	SIGN REVISION / SUBMITTAL				
ε									
								_	
ñ.						<b>AECOM</b> Kimley»Horn			
5									
0								SOUTHWEST	
۲ ۲							METROPOLITAN	Green Line LRT Extension	
<b>.</b>							COUNCIL		
, ,						60% SUBMISSION - 09/28/15			DISCIPLINE:
Ne Ne									




NO.	DATE	BY	CHEC	K DESIGN	REVISION / SUBMITTAL				
						<b>AECOM</b> Kimley »Horr			
								SOUTHWEST	
								Green Line LRT Extension	
							METROPOLITAN		
						60% SUBMISSION - 09/28/15			DISCIP





NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL	<b>AECOM</b> Kimley»Horn	METROPOLITAN	
						60% SUBMISSION - 09/28/15		DISCIPLINE
						00 /0 SODIMISSION - 03/20/13		

OW FOUNDATION DETAIL CLUDED IN 90% SUBMITTAL	
CIVIL EAST - VOLUME 10	SHEET
TRAFFIC SIGNAL	SHEET 150




60% SUBMISSION - 09/28/15




DISCIPLIN

METROPOLITAN


7		
	NOTES:	
	<ol> <li>MATERIALL - STEEL, ASTM A576, AISI COLD DRAWN 1018 - 55,000 PSI MIN. YIELD.</li> <li>FINISH - HOT DIP GALVANIZED, LENGTH</li> </ol>	
	INDICATED. NUTS SHALL RUN FREE AFTER PLATING.	
	HEX NUTS ASTM A563, ASSEMBLED AFTER ROD PLATING.	
	NO SCALE	
	ANCHOR ROD - SIGNAL STANDARD PLATE NO.	
_	1 3/4" X 71" TYPE "B" - MA TRAF-1130	
	CIVIL EAST - VOLUME 10 TRAFFIC SIGNAL	SHEET
	MINNEAPOLIS DETAIL	151
	SHEET 4	OF
.INE:	TRAFFIC E0-TFC-SIG-DTL - 012	266



NO.	DATE	BY	CHEC	K DESIGN	N REVISION / SUBMITTAL					
							<b>AECOM</b> Kimley»Horn			
									SOUTHWEST	
								METRODOLITAN	Green Line LRT Extension	
								METROPOLITAN		
						1	60% SUBMISSION - 09/28/15			DISCIPI
							60% SUBINISSION - 09/20/15			



5 7/8"	
16" ANNEL	
1 X 1/2" X CHANNEL	
SOCKET HEAVY DUTY 18NC X 2" LONG WELDED TO LATCH) EEL 5/8" DIA. X 1"	
a. X 1 5/8" Ed to door)	
EEL ONG PIN DR)	
<ol> <li>NOTES:</li> <li>SKIRT &amp; BOTTOM PLATE MATERIAL - STAINLESS STEEL (TYPE 201) 60,000 PSI MIN. YIELD AFTER FABRICATION. TOP PLATE MATERIAL - LOW CARBON STEEL 36,000 PSI MIN. YIELD.</li> <li>FINISH - EPOXY PRIMER.</li> <li>FINISH - UPS BROWN THERMO-SET ACRYLIC.</li> </ol>	
CIVIL EAST - VOLUME 10	SHEET
TRAFFIC SIGNAL MINNEAPOLIS DETAIL	153
SHEET 6	OF
TRAFFIC SHEET NAME: E0-TFC-SIG-DTL -	014 266




DISCIPLINE:

METROPOLITAN

60% SUBMISSION - 09/28/15

**AECOM** Kimley»Horn

19 5/8"					
- /					
5/16" :HANNEL					
721 X 1/2" X CHANNEL					
el NC X 2" long T (Welded					
TEEL					
'RING & LONG PIN POR)					
STEEL " LONG PIN OOR)					
NOTES: 1. SKIRT & BOTTOM PLATE MATERIAL - STAINLESS STEEL (TYPE 201) 60,000 PSI MIN. YIELD AFTER FABRICATION. TOP PLATE MATERIAL - LOW CARBON STEEL 36,000					
PSI MIN. YIELD. 2. FINISH - EPOXY PRIMER 3. FINISH - UPS BROWN TH					
	「- VOLUME 10 IC SIGNAL	SHEET			
	OLIS DETAIL	154			
SI	HEET 7	OF			
	BO-TFC-SIG-DTL - 015	266			




NO.	DATE	BY	CHECK	DESIGN	N REVISION / SUBMITTAL				
							<b>N</b>		
						<b>AECOM</b> Kimley »Horn			
								SOUTHWEST	
							METROPOLITAN	Green Line LRT Extension	
							METROPOLITAN	$\mathbf{i}$	
									DISCIPLI
						60% SUBMISSION - 09/28/15			


Sep,

IPLINE


	CIVIL EAS	Γ - VOLUME 10	SHEET		
	TRAFFIC SIGNAL				
	MINNEAPOLIS DETAIL SHEET 8				
IPLINE:	TRAFFIC	SHEET NAME: E0-TFC-SIG-DTL - 016	266		



10. D	ATE	BY	CHECK	DESIG	REVISION / SUBMITTAL					
									_	
						-	<b>AECOM</b> Kimley»Horn			
									COLITEINA/ECT	
						-			Green Line LRT Extension	
								METROPOLITAN		
							60% SUBMISSION - 09/28/15			DISCIPLIN
							0070 00 Dimit 01014 - 03/20/13			



NO.	DATE	BY	CHE	CK DESIG	N REVISION / SUBMITTAL					
				-		-				
				_			<b>AECOM</b> Kimley»Horn			
									SOUTHWEST	
						-		METROPOLITAN		
				_		. ⊢		COUNCIL		DISC
							60% SUBMISSION - 09/28/15			DISC
							00 /0 SUBINISSION - 09/20/15			
						l l				




60% SUBMISSION - 09/28/15


DISCIPLIN

METROPOLITAN

TRAFF MINNEAP	Γ - VOLUME 10 IC SIGNAL OLIS DETAIL EET 11	SHEET 158 OF
	BHEET NAME: E0-TFC-SIG-DTL - 019	266









.44"


DATE: 1/1/11

DATE: 1/1/11






	CIVIL EAST - VOLUME 10				
	TRAFFIC SIGNAL				
	MINNEAPOLIS DETAIL SHEET 13				
NE:	TRAFFIC	SHEET NAME: E0-TFC-SIG-DTL - 021	266		





DATE	BY	CHECK DESIGN	REVISION / SUBMITTAL					
					<b>AECOM</b> Kimley»Horn			
							SOUTHWEST	
							Green Line LRT Extension	
						METROPOLITAN		
				1				DISCIPLIN
					60% SUBMISSION - 09/28/15			
			1					


NO.











DISCIPLINE

METROPOLITAN


60% SUBMISSION - 09/28/15


	CIVIL EAST - VOLUME 10			
	TRAFFIC SIGNAL			
	MINNEAPOLIS DETAIL SHEET 17			
NE:	TRAFFIC	SHEET NAME: E0-TFC-SIG-DTL - 025	266	

Y	DESCRIPTION	EST. WEIGHT	
ring; f	POLYMER CONCRETE	50 LBS	
OVER	POLYMER CONCRETE	42.3 LBS	


1 RING & COVER SHALL MEET TIER 22 RATING (ANSI/SCTE 77-2007)

2 COVER & LID SHALL BE POLYMER CONCRETE






	<b>CIVIL EAST - VOLUME 10</b>				
	TRAFFIC SIGNAL				
		APOLIS DETAIL SHEET 18	OF		
INE:	TRAFFIC	SHEET NAME: E0-TFC-SIG-DTL - 026	266		





NO.	DATE	BY	CHECK DE	SIGN REVISION / SUBMITTAL			
					<b>AECOM</b> Kimley»Horn	METROPOLITAN	
					60% SUBMISSION - 09/28/15		DISCIPLI



~						
	NO. DATE	BY	CHECK DE	SIGN REVISION / SUBMITTAL		
F						
Þ						
5G						
ë					AECOM Kimley »Horn	
n					SOUTHWE	ST
					Green Line Lift Estension	
-						
N.					60% SUBMISSION - 09/28/15	DISCIPLINE
уер Сер					60 /0 30 BINI 3310N - 09/20/15	
~ •						


<u>~</u>	/IDEO DETECTOR MITH PENDANT MOUNT BRACKET		
À			
D D D D D D D D D D D D D D D D D D D			
CTOR			
E STAINLESS STEEL			
LAMP MOUNTING			
NG BRACKET IFACTURER			
JM PIPE			
CIVIL EAS	Γ-VOLUME 10		SHEET
	IC SIGNAL		167
	OLIS DETAIL IEET 20		OF
TRAFFIC	SHEET NAME: E0-TFC-SIG	-DTL - 028	266






NO	DATE	BY CHE	SIGN REVISION / SUBMITTAL				
	27.12						
				<b>AECOM</b> Kimley»Horr			
				*		Green Line LRT Extension	
					METROPOLITAN		
					_ 5 U U N 5 I L		DISCIPLI
				60% SUBMISSION - 09/28/15			


HINGES SHALL BE LIFTOFF SOUTHCO MODEL 96-10-500-50. PROVIDED WITH NEOPRENE GASKET DOINT PEDESTAL CABINET SHALL BE NEMA 3R LOSURE, U.L. LISTED AND LABELED "SUITABLE USED AS SERVICE ENTRANCE GUIPMENT." D POINT PEDESTAL CABINET MATERIAL SHALL BE '5052-0 ALUMINUM. ITY APPROVED METER SOCKET WITH DISCONNECT. METER SOCKET BACK PANEL DEAD FRONT ON RAILS HINGES SHALL BE LIFTOFF SOUTHCO MODEL 96-10-500-50. PRS SHALL BE PROVIDED WITH NEOPRENE GASKET D POINT PEDESTAL CABINET SHALL BE NEMA 3R LOSURE, U.L. LISTED AND LABELED "SUITABLE USED AS SERVICE ENTRANCE GUIPMENT." D POINT PEDESTAL CABINET MATERIAL SHALL BE '5052-0 ALUMINUM. ITY APPROVED METER SOCKET WITH DISCONNECT. METER COMPARTMENT DOOR AND THE CIRCUIT AKER COMPARTMENT DOOR SHALL BE EVENDOR. ATTACHMENTS TO CABINET SHALL BE WELDED OR USE INESS STELES STREED & INSTALLED BY VENDOR. ATTACHMENTS TO CABINET SHALL BE WELDED OR USE INESS STELES STREED TO FOR THE ON OFFS. VENS SHALL BE CENTERED IN UPPER COMPARTMENT UOVES SHALL BE CENTERED IN UPPER COMPARTMENT DOWN AND FOR THE SHALL BE VENDOR. ATTACHMENTS TO CABINET SHALL BE WELDED OR USE INESS STELES STREET. UDOWS SHALL BE CENTERED IN UPPER COMPARTMENT	
METER SOCKETS. NTILATION HOLES (1/8") SHALL BE PROVIDED IN CABINET ONT AT 1/2" CENTERS AT ROOF CAP. UIPMENT SHALL BE ARRANGED WITHIN CABINET AS PROXIMATELY SHOWN. NELBOARD DEAD FRONTS SHALL BE PUNCHED	
MATCH FULL CAPACITY OF BREAKER PANEL.	
<b>CIVIL EAST - VOLUME 10</b>	SHEET
TRAFFIC SIGNAL	169
MINNEAPOLIS DETAIL	OF
INE: ISHEET NAME:	
TRAFFIC E0-TFC-SIG-DTL - 03	60 <sup>266</sup>






DISCIPLIN


CIVIL EAST - VOLUME 10					
TRAFFIC SIGNAL					
MINNEAPOLIS DETAIL SHEET 23					
NE:	TRAFFIC	SHEET NAME: E0-TFC-SIG-DTL - 031	266		




Sep. 21 2015 06:46 am V:\3400\_ADC\CAD\SEGMENT E1\PLAN SHEETS\TRAFFIC\E1-TFC-SIG-IDX.dwg By: brian.v

	0 100 200 SCALE IN F	400 
MILWAUKEE SI		
<u>2598+8825</u>		
	SHEET NAME LEGEND	)
	TFC = TRAFFIC	
Pr H	01 = SEGMENT 1 SIG = SIGNAL PLAN SHE	
A LAND	001 = SEQUENCE NUMBE	
CIVIL EA	ST - VOLUME 10	SHEET
		171
		OF
I INE:	SHEET 1	266
TRAFFIC	E1-TFC-SIG-IDX-001	200






BUILTING RESUSTEM "R" ENLIWORTH TRAIL DEAM BUDO	
SHEET NAME LEGEND	r
C = TRAFFIC $3 = SEGMENT 3$ $G = SIGNAL PLAN SHEETS$ $0 = SEQUENCE NUMBER$	400 FEET
SIGNAL PLAN PLAN SHEET LAYOUT SHEET 3	SHEET 173 OF 266
TRAFFIC E3-TFC-SIG-IDX - 001	



SHEET 230 PLAN - SCHAL SYSTEM "T" TH ST N & STH AVE-N		
HEET NAME LEGEND		
= TRAFFIC = SEGMENT 4 = SIGNAL PLAN SHEETS = SEQUENCE NUMBER	0 100 200 SCALE IN	400 FEET
CIVIL EAST - VOL	UME 10	SHEET
SIGNAL PLA		174
PLAN SHEET LA SHEET 4	YOUT	OF
LINE:SHEET NAME:		266
	4-TFC-SIG-IDX-001	



- 1.) SEE DIVISION "SS" OF SPECIAL PROVISIONS FOR EMERGENCY VEHICLE PREEMPTION (EVP) SYSTEM, ACCESSIBLE PEDESTRIAN SIGNAL (APS), AND FIBER OPTIC COMMUNICATION EQUIPMENT.
- ONE APS PEDESTRIAN PUSH BUTTON WITH SIGN R10-3E (9"X15") SHALL BE INSTALLED ON MA-1, MA-2, AND MA-3 AND ON EACH PUSH BUTTON STATION AS DIRECTED BY THE ENGINEER FOR 2.) OPERATION AS SHOWN IN THE PHASING LAYOUT.
- PEDESTRIAN INDICATIONS SHALL BE ONE SECTION LED WITH 3.) COUNTDOWN TIMERS UTILIZING INTERNATIONAL SYMBOL (HAND AND WALKING PERSON) INDICATIONS. SEE SPECIAL PROVISIONS.
- ONE LED LUMINAIRE SHALL BE INSTALLED ON MA-2 LUMINAIRE 4.) SHAFT EXTENSION. SEE SPECIAL PROVISIONS.
- 5.) LUMINAIRE SYMBOL IS SHOWN ROTATED ON THE PLAN TO INCREASE LEGIBILITY. MOUNTING POSITION SHALL BE 0 DEGREES.
- 6.) THE CONTRACTOR SHALL FURNISH AND INSTALL ONE R10-X12 SIGN (36"X42") ON THE MAST ARM OF MA-1, MA-2, AND MA-3 AND MOUNTED TO SIGN BRACKET "D" AS DIRECTED BY THE ENGINEER.
- THE CONTRACTOR SHALL PLACE COMMON BACK FILL AND RESTORE 7.) ALL DISTURBED TURF, CONCRETE OR BITUMINOUS WALK, ETC. TO ITS ORIGINAL CONDITION OR BETTER. ALL COSTS FOR THIS WORK SHALL BE INCIDENTAL.
- 8.) SHALL BE INCIDENTAL.
- 9.) CONSTRUCTION.
- CABINETS, AND BASES SHALL BE DETERMINED IN THE FIELD.
- CONDUITS UNDER THE ROADWAY REQUIRE BORING.
- BE EXTENDED BRACKETING. SEE SPECIAL PROVISIONS.
- PUSH BUTTON LOCATIONS AND REMOVE INPLACE 2/C #12 (SHLD) PFR THE PLAN
- INCIDENTAL
- MA-1.
- ON MA-2.



D4

 $\left(1\right)$ 

 $\frac{PBS}{1}$ 

/MA`

¥.

Ϋ́

80

Ø3

′нн`

5

D5

201+0r

¥

Ø2 + Ø5 EVP

′нн`

D

А

14'

0

 $\begin{pmatrix} HH \\ 2 \end{pmatrix}$ 

200+00

 $\rightarrow$ 

-₩-<

PBS

′нн∖

В

/ма

4

 $\binom{\mathsf{PBS}}{4}$ 

A

====;

EXISTING INTERCONNECT TO CSAH 3

(EXCELSIOR BLVD) AND 11TH AVE S

SEE INTERCONNECT PLAN

CSAH 3 (EXCELSIOR BLVD)/HH

(40 M.P.H.)

\_\_**L**\_


13'

13

 $\triangleleft$ 

199+00

			Ĩ	
		INTERCONNECT TO C		
	(EXCELS	SIOR BLVD) AND 5TH	AVE S	40
14'		/HH	SCALE IN	FEET
12'		G/	[]	$\begin{pmatrix} D2\\ 2 \end{pmatrix}$
12 202+00	)		203+00 /HH\	
12'	5		4	1
102+00	)	13'	103+00	I
		12'		-
		14'		
			ALL SIGNAL EQUIPMENT SHEET IS INPLACE & S REMAIN INPLACE UNLES OTHERWISE NOTED. A WORK TO BE COMPLETE CONTRACTOR.	HALL S DENOTES
	<ul> <li>INPLACE.</li> <li>EXISTING CON INPLACE.</li> <li>EXISTING CON INPLACE.</li> <li>EXISTING CON ABANDONED I</li> <li>EXISTING CON INPLACE.</li> <li>EXISTING PHA AND CONDUIT ABANDONED I</li> <li>EXISTING PHA AND CONDUIT ABANDONED I</li> <li>EXISTING PHA AND CONDUIT ABANDONED I</li> <li>EXISTING HAT</li> <li>EXISTING HH</li> <li>EXISTING PHA IN THE NORTI</li> <li>EXISTING PHA IN THE NORTI</li> <li>EXISTING PHA</li> </ul>	IDUIT RUN BETWEEN H IDUIT RUN BETWEEN H IDUIT RUN BETWEEN H INPLACE. IDUIT RUN BETWEEN H SE 4 DETECTOR LOOF RUN BETWEEN HH 2 INPLACE. INPLACE. INPLACE. INPLACE. INPLACE. IN THE SOUTHEAST F IN THE SOUTHEA	HH A AND HH 2 TO BE AND HH E AND HH F TO BE AND HH F AND HH 3 TO BE AND HH F AND MAST ARM 2 TO HH F AND HH C TO BE AND PS ALONG THE NORTH API AND THE DETECTOR LOOD PS ALONG THE SOUTH API AND THE DETECTOR LOOD DITHEAST CORNER, POLE, A OVED. I CORNER TO BE REMOVED CORNER TO BE REMOVED CORNER TO BE REMOVED TO BE RELOCATED ON MAST ON MAST ARM 4 IN THE IN THE SOUTHWEST CORN	BANDONED BANDONED D BE BANDONED PROACH PS TO BE PROACH PS TO BE ND D. CATIONS ST ARM 1
ON 2	LRT TRACK CLEARAN ACCOMMODATE FLAS	NCE AND PREEMPTION HING YELLOW ARROWS LEFT-TURNS, PROVIDE	O ACCOMMODATE A CHANG SIGNAL PHASING CHANGE , SIGNAL PHASING CHANGE S FOR THE EASTBOUND, W PEDESTRIAN PUSH BUTTO	ES TO ESTBOUND
	SIGNAL SYSTEM OPE			
	<ul> <li>NORMAL OPERATION PHASE 5 BEING</li> </ul>	FLASHING YELLOW AF	ALL RED. ASE, WITH PHASE 1, PHASI RROWS BY TIME OF DAY. DN, INCLUDING TRACK CLE/	
	CIVIL EAS	ST - VOLUME	E 10	SHEET
			-	175
594 <b>1</b> 3		IR DLVU) AN	ID 8TH AVE S	OF
IPLINE:	TRAFFIC	SHEET NAME: E1-TF(	C-SIG-8TH-001	266



NO.	LOCATION (1)	NO.	LOCATION	(1)
HH-2		PBS-1		
HH-3		PBS-2		
HH-6		PBS-3		
HH-7		PBS-4		
HH-F		PBS-5		
	L	OCATION		МА
NO	FOUNDATION (1)		AIM ARM TO	AF
MA-2				3


(1) TO THE CENTER OF THE HANDHOLE OR CONCRETE FOUNDATION.

ALL SIGNAL EQUIPMENT ON THIS SHEET IS INPLACE & SHALL REMAIN INPLACE UNLESS OTHERWISE NOTED. A DENOTES WORK TO BE COMPLETED BY THE CONTRACTOR.


		SIGN	IAL IN	
SIG. POLE NO.	FACE NO.	SIGNAL FACE MOUNT	SIG. Ø	RED
-				
	3–1	MAST ARM (END)	3	-
			4	
	8-2	MAST ARM (INSIDE)	8	•
MA-1	8–1	POLE MOUNT	8	0
			1	-
	1-2	POLE MOUNT	2	
			2	
			1	-
	1-1	MAST ARM (END)	2	
	6-3	MAST ARM (MID)	6	٠
MA-2	6-2	MAST ARM (INSIDE)	6	•
	6-1	POLE MOUNT	6	٠
			4	•
	4-3	POLE MOUNT	8	
	4-2	MAST ARM (END)	4	0
	4-1	POLE MOUNT	4	0
MA-3			5	-
	5-2	POLE MOUNT	6	
			6	
			5	-
	5–1	MAST ARM (END)	6	
[	2-3	MAST ARM (MID)	2	0
	2-3	MAST ARM (MID) MAST ARM (INSIDE)	2	0
MA-4	2-2	POLE MOUNT	2	0
MA-4	2-1	PULE MOUNT	_	0
			3	-
	3–2	POLE MOUNT	4	
			4	

PEDESTRIAN INDICATIONS SHALL BE INTERNATIONAL SYMBOLS COUNTDOWN TIMER.
 STRAIGHT MOUNT PLUMBIZER, SEE SPECIAL PROVISIONS.


INPLACE STRUCTURES							
NO.	REMARKS	NO.	REMARKS				
MA-1	REMAIN INPLACE	HH-4	REMAIN INPLACE				
MA-2	REMOVE	HH-5	REMAIN INPLACE				
MA-3	REMAIN INPLACE	HH-A	REMAIN INPLACE				
MA-4	REMAIN INPLACE	HH-B	REMAIN INPLACE				
CAC-1	REMAIN INPLACE	HH-C	REMAIN INPLACE				
SP-1	REMAIN INPLACE	HH-D	REMAIN INPLACE				
HH-1	REMAIN INPLACE	HH-E	REMAIN INPLACE				
HH-2	REMOVE	HH-F	REMOVE				
HH-3	REMOVE	HH-G	REMAIN INPLACE				
		SOP-1	REMAIN INPLACE				



TIONS AND BRACKETING								
		INDICAT			BRACKET MOUNTING			
		CATIONS		PED	ANGLE, TYPE, AND			
)	YEL	FYA	GRN	SYM.	STANDARD PLATE NO.			
-	-		-		**			
		-						
	•		•	*	** INPLACE			
-	-		-					
		-			90° PLATE 8110E, TYPE 10B			
				*				
	-		-					
		-			**			
	•		•		**			
	•		•	*	** 180° PLATE 8110E, TYPE 10B	▲		
	•		•					
				*	90° PLATE 8110E, TYPE 10B			
	0		0	*	INPLACE INPLACE			
-	-		-					
		-			90° PLATE 8110E, TYPE 10B			
				*				
-	-		-					
		-			**			
	0		0	*				
	0		0	*	INPLACE INPLACE			
	-		-					
		-		*	90° PLATE 8110E, TYPE 10B	▲		
	TYPICAL 4-SECTION SIGNAL HEAD PHASING WITH FLASHING YELLOW ARROWSIGNAL FACE 1-1 AND 1-2SIGNAL FACE 3-1 AND 3-2SIGNAL FACE 5-1 AND 5-2							
	CIVIL EAST - VOLUME 10 SIGNAL PLAN - SIGNAL SYSTEM "A" SAH 3 (EXCELSIOR BLVD) AND 8TH AVE S OF						6	
IE:	EQUIPMENT SCHEDULE     Or       TRAFFIC     SHEET NAME: E1-TFC-SIG-8TH - 002     266				6			



p, 21 2015 07:18 am V:\3400\_ADC\CAD\SEGMENT E1\PLAN SHEETS\TRAFFIC\E1-TFC-SIG-8TH.dwg By: br




	SIGNAL STRUC	TURE LOCAT	TIONS		ALL SIGNAL EQUIPMENT ON THIS SHEET IS INPLACE & SHALL			SIG	NAL IN	DICAT
NO.	LOCATION (1)	NO.	LOCATION	(1)	REMAIN INPLACE UNLESS OTHERWISE NOTED. A ▲ DENOTES	SIG.	FACE		SIG.	
HH-14					WORK TO BE COMPLETED BY THE CONTRACTOR.	POLE	NO.	SIGNAL FACE MOUNT	Ø	
HH-15					CONTRACTOR.	NO.	NO.		<u>ل</u>	RED
HH-16										
							3–1	MAST ARM (END)	3	-
							5-1		4	
						MA-1	8-2	MAST ARM (INSIDE)	8	0
							8-1	POLE MOUNT	8	0
							-	POLE MOUNT	2	
							1-1	MAST ARM (END)	1	
							6-3	MAST ARM (MID)	6	0
							6-2	MAST ARM (INSIDE)	6	0
						MA-2	6-1	POLE MOUNT	6	0
									7	-
10	LOC	CATION		MAST			7–2	POLE MOUNT	8	
NO. –	FOUNDATION (1)	AIM	I ARM TO	ARM					8	
							7–1	MAST ARM (END)	7	-
							/-1		8	
						MA-3	4-2	MAST ARM (INSIDE)	4	0
) IO THE (	CENTER OF THE HANDHOLE OR CO	NCREIE FOUNDAT	IION.			MA-3	4-1	POLE MOUNT	4	0
						1			-	1

	INPLACE STRUCTURES								
NO.	REMARKS	NO.	REMARKS						
MA-1	REMAIN INPLACE	HH-5	REMAIN INPLACE						
MA-2	REMAIN INPLACE	HH-6	REMAIN INPLACE						
MA-3	REMAIN INPLACE	HH-7	REMAIN INPLACE						
MA-4	REMAIN INPLACE	HH-8	REMAIN INPLACE						
CAC-1	REMAIN INPLACE	HH-9	REMAIN INPLACE						
SP-1	REMAIN INPLACE	HH-10	REMAIN INPLACE						
HH-1	REMAIN INPLACE	HH-11	REMAIN INPLACE						
HH-2	REMAIN INPLACE	HH-12	REMAIN INPLACE						
HH-3	REMAIN INPLACE	HH-13	REMAIN INPLACE						
HH-4	REMAIN INPLACE	SOP-1	REMAIN INPLACE						


LOOP DE	TECTOR	CHART		
DESIGNATION	FUNCTION LOCATION			
D1-1	INPLACE			
D2-1	INPLACE			
D2-2	INPLACE			
D3-1	INPLACE			
D3-2	INPLACE			
D4-1	INPLACE			
D4-2	INPLACE INPLACE			
D5-1				
D6-1	INPLACE			
D6-2	D6-2 INPLACE			
D7-1	D7-1 INPLACE			
D7-2	INPLACE			
D8-1	INPLACE			
D8-2	INPLACE			


NO.	DATE	BY	CHEC	K DESIG	N REVISION / SUBMITTAL					T
						<b>AECOM</b> Kimley»Horn				
									SOUTHWEST Green Line LRT Extension	'
								METROBOLITAN	Green Line LRT Extension	
								METROPOLITAN	<u> </u>	
						6	0% SUBMISSION - 09/28/15			DISC
						0	0 /6 30BINII331014 - 09/20/15			

SHEET **CIVIL EAST - VOLUME 10** SIGNAL PLAN - SIGNAL SYSTEM "B" 179 SAH 3 (EXCELSIOR BLVD) AND 5TH AVE S OF EQUIPMENT SCHEDULE E1-TFC-SIG-5TH - 002 INE: 266 TRAFFIC




, 21 2015 07:21 am V:\3400\_ADC\CAD\SEGMENT E1\PLAN SHEETS\TRAFFIC\E1-TFC-SIG-5TH.dwg E







D INDICATIONS BRACKET MOUNTING IDICATIONS PED ANGLE, TYPE, AND			
ANGLE, TYF	TYPE, AND		
STANDARD P	RD PLATE NO.		
INPLAC	IPLACE		
INPLAC	IPLACE		
INPLAC	IPLACE		
INPLACE			
INPLAC	IPLACE		
INPLAC	IPLACE		
**	**		
**	**		
180° PLATE 8110	8110E, TYPE 10B		
90° PLATE 8110E	8110E, TYPE 10B		
	IPLACE		
	IPLACE		
	IPLACE		
INPLACE FL	CE FLASHER		
INPLAC	IPLACE		
RELOCA	LOCATE		
90° PLATE 8111	8111E, TYPE 4A		
INPLAC	IPLACE		

SHEET **CIVIL EAST - VOLUME 10** SIGNAL PLAN - SIGNAL SYSTEM "C" 182 **CSAH 3 (EXCELSIOR BLVD) AND MILWAUKEE** OF **ST/JACKSON AVE N - EQUIPMENT SCHEDULE** SHEET NAM 266 TRAFFIC E1-TFC-SIG-EXC - 002









CIVIL EAST - VOLUME 10					
SIGNAL PLAN - SIGNAL SYSTEM "D"					
AH 3 (EXCELSIOR BLVD) AND PIERCE AVE					
NE:	TRAFFIC	SHEET NAME: E1-TFC-SIG-PRC-001	266		

\3400_ADC\CAD\SEGMENT	NOTES: 1. SEE SIGNAL MAST ARM DETAIL SHEET FOR SIGN MOUNTING PLATE 2. COLOR — WHITE LEGEND AND BORDER ON GREEN BACKGROUND. AL SIGN SHEETING. 3. ALL COSTS TO PROVIDE AND INSTALL MAST ARM MOUNTED SIGN P INCIDENTAL.	L SIGNING SHALL USE DG3	<ul> <li>LOCATION: DISTANCE FROM CROSSWALK/ STOP BAR IN FEET</li> <li>(1)-CALL AND EXTEND</li> </ul>
÷ E	NO. DATE BY CHECK DESIGN REVISION / SUBMITTAL		
': 28 o	Image: Image in the second s	<b>AECOM</b> Kimley»Horn	
15 07:	Image: Image in the second s		SUULTIVESING I
21 201			
Sep.		60% SUBMISSION - 09/28/15	DISCIP



AN ĥ



CENTER OF THE HANDHOLE OR C	ONCRETE FOU	JNDATION.
INPLACE	STRUCTL	JRES
REMARKS	NO.	REMA
REMAIN INPLACE	HH-5	REMAIN INPLACE
	INPLACE REMARKS	

	SIGNAL STRU	CTURE LO	CATIONS	
NO.	LOCATION (1)	NO.	LOCATION	(1)
HH-1		SP-1		
HH-2		CAC-2		
HH-3				
HH-4				
HH-5				
NO. —	L	OCATION		MAST
NO.	FOUNDATION (1)		AIM ARM TO	ARM
MA-1				XX,
MA-2				XX,
MA-3				XX,
MA-4				XX,
MA-5				XX'

REMARKS


SIG. POLE NO.	FACE NO.	SIGNAL FACE MOUNT	SIG. Ø	RE
	1-1	MAST ARM (END)	1	-
			2	
	6-3	MAST ARM (MID)	6	•
MA-1	6-2	MAST ARM (INSIDE)	6	•
	6-1	POLE MOUNT	6	•
	4-3	POLE MOUNT	4	•
	+ 0		8	
	4-2	MAST ARM (END)	4	•
	4-1	POLE MOUNT	4	•
MA-2	2 5-2 POLE MOUNT		5	-
		6		
			6	
	5-1	MAST ARM (END)	5	-
			6	
	2-3	MAST ARM (MID)	2	•
MA-3	2-2	MAST ARM (INSIDE)	2	•
	2-1	POLE MOUNT	2	•
	8–3	POLE MOUNT	8	•
	0-5		4	
	8-2	MAST ARM (END)	8	•
	8–1	POLE MOUNT	8	•
MA-4			1	-
	1-2	POLE MOUNT	2	
			2	

PEDESTRIAN INDICATIONS SHALL BE INTERNATIONAL SYM COUNTDOWN TIMER.
 \*\* STRAIGHT MOUNT PLUMBIZER, SEE SPECIAL PROVISIONS.


VIDEO DETECTOR CHART						
DESIGNATION	NO.	FUNCTION	LOCATION			
D1-1	VIDEO (V-1)	(1)	20 & 50			
D1-2	VIDEO (V-1)	(1)	5 & 35			
D2-1, D2-2	VIDEO (V-3)	(1)	180			
D2-3, D2-4	VIDEO (V-3)	(1)	5 & 20			
D4-1	VIDEO (V-2)	(1)	120			
D4-2	VIDEO (V-2)	(1)	5 & 20			
D5-1	VIDEO (V-3)	(1)	20 & 50			
D5-2	VIDEO (V-3)	(1)	5 & 35			
D6-1, D6-2	VIDEO (V-1)	(1)	180			
D6-3, D6-4	VIDEO (V-1)	(1)	5 & 20			
D8-1	VIDEO (V-4)	(1)	50			
D8-2	VIDEO (V-4)	(1)	5 & 20			


LOCATION: DISTANCE FROM CROSSWALK/ STOP BAR IN FEET
 (1)-CALL AND EXTEND

	SIG.			INDICAT		BRACKET MOUNTING	
Г	ø		1	ICATIONS		PED	ANGLE, TYPE, AND
	~	RED	YEL	FYA	GRN	SYM.	STANDARD PLATE NO.
	1	-	-		-		**
	2	-	-	-	-		
	6	•	•		•		**
	6	•	•		•		**
	6	•	•		•	*	180° PLATE 8110E, TYPE 10B
	4	•	•		•		90° PLATE 8110E, TYPE 10B
	8					*	
	4	•	•		•		**
	4	•	•		•	*	180° PLATE 8110E, TYPE 10B
	5	-	-		-		
	6			-			90° PLATE 8110E, TYPE 10B
	6					*	
	5	-	-		-		**
	6			-			T T
	2	•	•		•		**
	2	۲	٠		۲		**
	2	•	•		•	*	180° PLATE 8110E, TYPE 10B
	8	۲	٠		۲		90° PLATE 8110E, TYPE 10B
	4					*	SO TEXTE OTIOE, THE TOB
	8	•	•		•		**
	8	٠	•		٠	*	180° PLATE 8110E, TYPE 10B
	1	-	-		-		
	2						90° PLATE 8110E, TYPE 10B
						*	
	2						



CIVIL EAST	- VOLUME 10	SHEET
	IGNAL SYSTEM "D"	186
•	BLVD) AND PIERCE AVE	OF
	IT SCHEDULE	
	SHEET NAME: E1-TFC-SIG-PRC - 002	266





	SIGNAL INDICATIONS AND BRACKETING								
SIG. POLE	FACE SIGNAL FACE MOUNT SIG. 12" INDICATIONS PED					PED	BRACKET MOUNTING ANGLE, TYPE, AND		
NO.	NO.		ø	RED	YEL	FYA	GRN	SYM.	STANDARD PLATE NO.
	1-1	MAST ARM (END)	1						INPLACE
	6-3	MAST ARM (END)	6	0	0		0		INPLACE
MA-1	6-2	MAST ARM (INSIDE)	6	0	0		0		INPLACE
	6-1	POLE MOUNT	6	0	0		0	*	INPLACE
	8-5	POLE MOUNT	8					*	INPLACE
	8-4	MAST ARM (END)	8	0	0		0	*	INPLACE
MA-2	8-3	POLE MOUNT POLE MOUNT	8	0	0		0	*	INPLACE
	_		0						INFLACE
	5-1	MAST ARM (END)	5	<b>—</b>	<b>_</b>		<b>_</b>		INPLACE
МА-3	2-3	MAST ARM (MID)	2	0	0		0		INPLACE
MA-J	2-2	MAST ARM (INSIDE)	2	0	0		0		INPLACE
	2-1	POLE MOUNT	2	0	0		0	*	INPLACE
	8-2	POLE MOUNT	8	0	0		0	*	INPLACE
	0.1			0				*	
SA-1	8-1	POLE MOUNT	8		0		0	*	INPLACE INPLACE

\* EXISTING PEDESTRIAN INDICATIONS SHALL REMAIN INPLACE.

SIGNAL STRUCTURE LOCATIONS					
NO.	LOCATION (1)	NO.	LOCATION (1)	)	
HH-10					
HH-11					
HH-12					
NO.	LOCA	TION		MAST	
NO.	FOUNDATION (1)		AIM ARM TO	ARM	


(1) TO THE CENTER OF THE HANDHOLE OR CONCRETE FOUNDATION.


	INPLACE STRUCTURES						
NO.	REMARKS	NO.	REMARKS				
MA-1	REMAIN INPLACE	HH-3	REMAIN INPLACE				
MA-2	REMAIN INPLACE	HH-4	REMAIN INPLACE				
MA-3	REMAIN INPLACE	HH-5	REMAIN INPLACE				
SA-4	REMAIN INPLACE	HH-6	REMAIN INPLACE				
CAC-1	REMAIN INPLACE	HH-7	REMAIN INPLACE				
SP-1	REMAIN INPLACE	HH-8	REMAIN INPLACE				
HH-1	REMAIN INPLACE	HH-9	REMAIN INPLACE				
HH-2	REMAIN INPLACE	SOP-1	REMAIN INPLACE				

METROPOLITAN SOUTHWESTER
-----------------------------

LOOP DE	TECTOR	CHART	
DESIGNATION	FUNCTION	LOCATION	
D1-1	INPL	ACE	
D1-2	INPL	ACE	
D2-1	INPL	ACE	
D2-2	INPL	ACE	
D5-1	INPL	ACE	
D5-2	INPL	ACE	
D6-1	INPLACE		
D6-2	INPL	ACE	
D6-3	INPL	ACE	
D6-4	INPL	ACE	
D8-1	INPL	ACE	
D8-2	INPL	ACE	
D8-3	INPL	ACE	
D8-4	INPL	ACE	
D8-5	INPL	ACE	
D8-6	INPL	ACE	


	CIVIL EAS	- VOLUME 10	SHEET
SI	GNAL PLAN - S	SIGNAL SYSTEM "E"	188
CSAH 20 (BLAKE RD N) AND 2ND ST NE EQUIPMENT SCHEDULE			
LINE:	TRAFFIC	SHEET NAME: E1-TFC-SIG-BLK - 002	266





TRAFFIC
---------

E CHAF	۲T		
Y F	r A	Y	SIGNAL SYSTEM "F" IS BEING MODIFIED TO ACCOMMODATE PEDESTRIAN CROSSINGS ON THE NORTH APPROACH, SIGNAL
┥ く	$\vdash$	←	PHASING CHANGES TO ACCOMMODATE FLASHING YELLOW ARROWS
0		0	FOR THE SOUTHBOUND LEFT-TURN, AND TO REPLACE LOOP DETECTORS.
		$\circ$	
0		0	SIGNAL SYSTEM OPERATIONS
0		0	– THE SIGNAL SYSTEM FLASH MODE IS ALL RED.
E 12" LED ACK ND SHIELDS	6		<ul> <li>NORMAL OPERATION IS 5 PHASE WITH PHASE 1 BEING FLASHING YELLOW ARROWS BY TIME OF DAY.</li> <li>PHASE 2 AND 6 SHALL BE ON MINIMUM RECALL.</li> <li>SIGNAL SYSTEM SHALL BE FULLY ACTUATED.</li> </ul>
	(	CIV	IL EAST - VOLUME 10




ALL SIGNAL EQUIPMENT ON THIS
SHEET IS INPLACE & SHALL
REMAIN INPLACE UNLESS
OTHERWISE NOTED. A 🛦 DENOTES
WORK TO BE COMPLETED BY THE
CONTRACTOR.


NAL	AT	45	DEG	
NAL	AT	45	DEG	

CIVIL EAST - VOLUME 10				
SIGNAL PLAN - SIGNAL SYSTEM "F" INTERSECTION NOTES				
INTERSEC	TION NOTES	OF		
TRAFFIC		266		

E2-TFC-SIG-OXF - 002



NO.	DATE	BY	CHECK	DESIGN	N REVISION / SUBMITTAL				
									1
									1
						<b>AECOM</b> Kimley»Horn			1
									1
								SOUTHWEST	1
							METROPOLITAN	Green Line LRT Extension	1
							METROPOLITAN		
						60% SUBMISSION - 09/28/15			DISC
						60 % SOBMISSION - 09/20/15			





TRAFFIC SIG-TH7W-001	266
	OF
TH 7 WB RAMPS AND WOODDALE AVE S	193
CIVIL EAST - VOLUME 10 SIGNAL PLAN - SIGNAL SYSTEM "G"	SHEET
<ul> <li>NORMAL OPERATION SHALL BE 4 PHASE, WITH PH BEING FLASHING YELLOW ARROWS BY TIME OF DA</li> <li>SIGNAL SYSTEM SHALL BE FULLY ACTUATED.</li> </ul>	Y.
- THE SIGNAL SYSTEM FLASH MODE IS ALL RED.	
SIGNAL SYSTEM OPERATIONS	
SCALE IN FEET	
WB OFF-RAMP D8-1	
 ===============================	
N	
NG AND STRIPING PLANS. ONAL DETAIL.	
E "D" SIGN PANELS SHALL BE INCIDENTAL. FOR TYPE "D" SIGNS SEE TYPE "I	)" SIGN
, TYPES, AND GENERAL LOCATIONS. THE EXACT LOCATION WILL BE DETERMINE ADWAY REQUIRE BORING. SCHEDULE 80 OR HDPE SCHEDULE 80 AND SHALL CARRY 1/C #6 GREEN IN: N THE PLAN. ONS SHALL BE LED AND SHALL HAVE BACKGROUND SHIELDS. ALL POLE MOU ACKETING. SEE SPECIAL PROVISIONS.	SULATED
UTILITY LOCATIONS PRIOR TO CONSTRUCTION. OLES, DETECTION ZONES, CABINETS, AND BASES SHALL BE DETERMINED IN T	HE
E VIDEO DETECTION CAMERA ON THE MAST ARM MA-2 DAVIT ARM. VIDEO A 6-FT HEIGHT EXTENSION BRACKET. ND INSTALL ONE R10-X12 SIGN (36"X42") ON THE MAST ARM OF MA-2. ND INSTALL ONE R9-3 SIGN (18"X18") ON THE UPRIGHT POLE OF PEDESTAL POLE OF MA-4 FACING PEDESTAL POLE 3 AS DIRECTED BY THE ENGINEER. MON BACK FILL AND RESTORE ALL DISTURBED TURF, CONCRETE OR BITUMING ON OR BETTER. ALL COSTS FOR THIS WORK SHALL BE INCIDENTAL. SIBLE FOR COORDINATING THE CONNECTION OF THE POWER FOR THE TRAFFIC	US
LLED ON EACH MAST ARM LIMINAIRE SHAFT EXTENSION. SEE SPECIAL PROVIS ED ON THE PLAN TO INCREASE LEGIBILITY. MOUNTING POSITION SHALL BE 0	IONS.
DNE SECTION LED WITH COUNTDOWN TIMERS UTILIZING INTERNATIONAL SYMBOI SEE SPECIAL PROVISIONS.	(HAND
WITH SIGN R10-3E (9"X15") SHALL BE INSTALLED ON EACH SIGNAL MAST A H BUTTON STATION AS DIRECTED BY THE ENGINEER FOR OPERATION AS SHOW	


## INTERSECTION NOTES

 PA90 POLE FOUNDATION TYPE PA90-A-35 (DAVIT AT 350 DEG) 1-ANGLE MOUNT SIGNAL-OVERHEAD AT 0' 1-STRAIGHT MOUNT SIGNAL OVERHEAD AT 11' 1-ANGLE MOUNT SIGNAL AT 180 DEG 2-ANGLE MOUNT C.D. PED HEADS AT 90 AND 180 DEG 1 ONE WAY FOR DETECTOR AND CONCENTRATORY LICET  $\left< \underline{1} \right>$  pass pole foundation type pass-a-15 (davit at 350 deg)  $\left< \frac{3}{3} \right>$  PEDESTAL FOUNDATION  $\langle 4 \rangle$  PA85 POLE FOUNDATION TYPE PA85-A-20 (DAVIT AT 350 DEG) 1-ANGLE MOUNT SIGNAL-OVERHEAD AT 0' 2-ANGLE MOUNT SIGNALS AT 90 AND 180 DEG 10' PEDESTAL POLE PLUS BASE 1-ANGLE MOUNT SIGNAL-OVERHEAD AT O' 1-STRAIGHT MOUNT C.D. PED HEAD AT 0 DEG 2-ANGLE MOUNT SIGNALS AT 90 AND 180 DEG 2-ANGLE MOUNT C.D. PED HEADS AT 90 AND 180 DEG 1-APS PB AND SIGN (LT ARROW) (PB2-1) 1-R9-3 SIGN FACING POLE 4 1-ANGLE MOUNT C.D. PED HEAD AT 180 DEG 1-APS PB AND SIGN (LT ARROW) (PB6-1) 1-ONE WAY EVP DETECTOR AND CONFIRMATORY LIGHT 1-APS PB AND SIGN (LT ARROW) (PB6-2) 1-ONE WAY EVP DETECTOR AND CONFIRMATORY LIGHT X" CONDUIT TO HH 8: 1-ONE WAY EVP DETECTOR AND CONFIRMATORY LIGHT (PHASE 6) (PHASE 8) (PHASES 2 & 5) LUMINAIRE-LED (FOR 40' MOUNTING HEIGHT) 1-TYPE D SIGN (D-1) (SEE SIGN DETAILS) LUMINAIRE-LED (FOR 40' MOUNTING HEIGHT) LUMINAIRE-LED (FOR 40' MOUNTING HEIGHT) 1-TYPE D SIGN (D-3) (SEE SIGN DETAILS) 1-R9-3 SIGN FACING POLE 3 1-VIDEO DETECTOR (MOUNTED ON DAVIT ARM) 1-R10-X12 SIGN ADJACENT TO HEAD (5-1) 1-TYPE D SIGN (D-2) (SEE SIGN DETAILS) X" CONDUIT TO HH 3: X" CONDUIT TO HH 9: X" CONDUIT TO HH 5: B EQUIPMENT PAD (SEE DETAIL SHEET) SERVICE CABINET (SSB) CONTROLLER AND CABINET (A)(C) SOP-POLE MOUNTED TRANSFORMER (XCEL ENERGY) X" CONDUIT INTO SERVICE CABINET: X" CONDUIT TO HH 1: NO. DATE BY CHECK DESIGN REVISION / SUBMITTAL **AECOM** Kimley»Horn SOUTHWEST METROPOLITAN DISCIPLINE: 60% SUBMISSION - 09/28/15 TRAFFIC E2-TFC-SIG-TH7W - 002

### SHEET **CIVIL EAST - VOLUME 10** SIGNAL PLAN - SIGNAL SYSTEM "G" 194 TH 7 WB RAMPS AND WOODDALE AVE S OF INTERSECTION NOTES 266








Arrow 14 - 18.0" 0°;

## D-1



D-1; 3.0" Radius, 1.0" Border, White on Green; "Wooddale Ave S" E Mod;

SIGN POLE and g ANEL MOUNTING PANEL	
SIGN FOLL OTY SIZE AREA FOLL SUBJECT OF A	
NO NO UTT SIZE AREA AREA NUMBER SPACING LEGEND	
FEET INCH SQ FT SQ FT (1)	
D-1 1 1 2 114 x 24 19.00 19.00 4 36 WOODDALE A	VE S
D-2 2 1 6 42 x 66 19.25 19.25 2 36 WEST MN 7 LEFT	T ARROW
D-3 4 1 2 90 x 66 41.25 41.25 5 36 EAST MN 7 UP ARROW, WEST	MN 7 RIGHT ARROW


SPECIFIC NOTES:


SPACING BETWEEN STIFFENERS SHALL NOT EXCEED 36 INCHES AND SHALL BE UNIFORMLY SPACED. SEE STANDARD SIGNS MANUAL, PAGE 105A FOR BRACKET SPACING REQUIREMENTS.

GENERAL NOTES: 1. CORNERS OF STANDARD SIGN PANELS WITH MARGINS SHALL BE TRIMMED. 2. TYPE D SIGN PANELS EXTENDING BEYOND THE BORDER SHALL NOT BE TRIMMED. 3. FOR STRUCTURAL DETAILS OF MAST ARM MOUNTED SIGNS SEE STANDARD SIGN MANUAL, PAGE 105A. 4. FOR TYPE D STRINGER AND PANEL JOINT DETAILS SEE STANDARD SIGNS MANUAL, PAGE 105. 5. THE MAST ARM MOUNTED SIGNS ARE INCIDENTAL.

NO.	DATE	BY	CHECK	DESIGN	N REVISION / SUBMITTAL				
						<b>AECOM</b> Kimley»Hor	n		7
								Green Line LTT Extension	DISCIPLI
						60% SUBMISSION - 09/28/15			

CIVIL EAST - V	OLUME 10	SHEET
SIGNAL PLAN - SIGN		195
TH 7 WB RAMPS AND TYPE "D" SIGI		OF
	DETAILS	
	E2-TFC-SIG-TH7W - 003	266





TENSION BRACKET. ALL ONE R10-12 SIGN (36"X42") ON THE MAST ARM OF MA-1 AND MOUNTEI IGINEER. ALL ONE R9-3 SIGN (18"X18") ON THE UPRIGHT POLE OF PEDESTAL POLE 2 3 FACING PEDESTAL POLE 2 AS DIRECTED BY THE ENGINEER. ACK FILL AND RESTORE ALL DISTURBED TURF, CONCRETE OR BITUMINOUS WAL COSTS FOR THIS WORK SHALL BE INCIDENTAL. OR COORDINATING THE CONNECTION OF THE POWER FOR THE TRAFFIC SIGNAL Y LOCATIONS PRIOR TO CONSTRUCTION. DETECTION ZONES, CABINETS, AND BASES SHALL BE DETERMINED IN THE FIELD	FACING .K, ETC. D.
G, AND GENERAL LOCATIONS. THE EXACT LOCATION WILL BE DETERMINED IN TH UIRE BORING. JLE 80 OR HDPE SCHEDULE 80 AND SHALL CARRY 1/C #6 GREEN INSULATED PLAN. HALL BE LED AND SHALL HAVE BACKGROUND SHIELDS. ALL POLE MOUNTED NG. SEE SPECIAL PROVISIONS.	
GIGN PANELS SHALL BE INCIDENTAL. FOR TYPE "D" SIGNS SEE TYPE "D" SIGN D STRIPING PLANS. DETAIL.	DETAIL
7 EB ON-RAMP 	
SCALE IN FEET	
SIGNAL SYSTEM OPERATIONS - THE SIGNAL SYSTEM FLASH MODE IS ALL RED. - NORMAL OPERATION SHALL BE 4 PHASE, WITH PH BEING PROTECTED-PERMISSIVE BY TIME OF DAY. - SIGNAL SYSTEM SHALL BE FULLY ACTUATED. - LRT AND FREIGHT RAIL SHALL OPERATE WITH PRE INCLUDING TRACK CLEARANCE.	
CIVIL EAST - VOLUME 10 SIGNAL PLAN - SIGNAL SYSTEM "H"	SHEET 197
TH 7 EB RAMPS AND WOODDALE AVE S	OF
TRAFFIC SHEET NAME: E2-TFC-SIG-TH7E-001	266

 SEE DIVISION "SS" OF SPECIAL PROVISIONS FOR EMERGENCY VEHICLE PREEMPTION (EVP) SYSTEM, VIDEO DETECTION SYSTEM, BATTERY BACK-UP SYSTEM, ACCESSIBLE PEDESTRIAN SIGNAL (APS), AND FIBER OPTIC COMMUNICATION EQUIPMENT.
 ONE APS PEDESTRIAN PUSH BUTTON WITH SIGN R10-3E (9"X15") SHALL BE INSTALLED ON EACH SIGNAL MAST ARM, PEDESTAL POLE, AND ON EACH PUSH BUTTON STATION AS DIRECTED BY THE ENGINEER FOR OPERATION AS SHOWN IN THE PHASING

PEDESTRIAN INDICATIONS SHALL BE ONE SECTION LED WITH COUNTDOWN TIMERS UTILIZING INTERNATIONAL SYMBOL (HAND AND

ONE LED LUMINAIRE SHALL BE INSTALLED ON EACH MAST ARM LIMINAIRE SHAFT EXTENSION. SEE SPECIAL PROVISIONS.

LUMINAIRE SYMBOL IS SHOWN ROTATED ON THE PLAN TO INCREASE LEGIBILITY. MOUNTING POSITION SHALL BE 0 DEGREES. THE CONTRACTOR SHALL INSTALL ONE VIDEO DETECTION CAMERA ON THE MAST ARM MA-1 DAVIT ARM. VIDEO DETECTION

## INTERSECTION NOTES

PA85 POLE FOUNDATION TYPE PA85-A-25 (DAVIT AT 350 DEG) 1-ANGLE MOUNT SIGNAL-OVERHEAD AT O' 2-ANGLE MOUNT SIGNALS AT 90 AND 180 DEG 1-ANGLE MOUNT C.D. PED HEAD AT 180 DEG 1-APS PB AND SIGN (RT ARROW) (PB2-2)
1-ONE WAY EVP DETECTOR AND CONFIRMATORY LIGHT (PHASE 2)
LUMINAIRE-LED (FOR 40' MOUNTING HEIGHT)
1-TYPE D SIGN (D-2) (SEE SIGN DETAILS)
1-R9-3 SIGN FACING POLE 2 X" CONDUIT TO HH 4:

PA85 POLE FOUNDATION TYPE PA85-A-30 (DAVIT AT 350 DEG) 1-ANGLE MOUNT SIGNAL-OVERHEAD AT 0' 1-STRAIGHT MOUNT SIGNAL OVERHEAD AT 12' 1-ANGLE MOUNT SIGNAL OVERHEAD AT 12' 1-ANGLE MOUNT C.D. PED HEADS AT 90 AND 180 DEG 2-ANGLE MOUNT C.D. PED HEADS AT 90 AND 180 DEG 1-APS PB AND SIGN (LT ARROW) (PB4-1) 1-ONE WAY EVP DETECTOR AND CONFIRMATORY LIGHT (PHASES 1 & 6) LUMINAIRE-LED (FOR 40' MOUNTING HEIGHT) 1-VIDEO DETECTOR (MOUNTED ON DAVIT ARM) 1-R10-12 SIGN ADJACENT TO HEAD (1-1) 1-TYPE D SIGN (D-1) (SEE SIGN DETAILS) X" CONDUIT TO HH 10:

A B EQUIPMENT PAD (SEE DETAIL SHEET) SERVICE CABINET (SSB) CONTROLLER AND CABINET X" CONDUIT TO HH 10:

C SOP-GROUND MOUNTED TRANSFORMER (XCEL ENERGY) X" CONDUIT TO HH 9:

2 PEDESTAL FOUNDATION

X" CONDUIT TO HH 3:

10' PEDESTAL FOUNDATION 10' PEDESTAL POLE PLUS BASE 1-STRAIGHT MOUNT C.D. PED HEAD AT 0 DEG 1-APS PB AND SIGN (LT ARROW) (PB6-1) 1-R9-3 SIGN FACING POLE 3

-		-								
Ο.	DATE	BA	CHECK	DESIGN	REVISION / SUBMITTAL					
						A=C	<b>OM</b> Kimley»Horn			-
							-		Green Line LAT Extension	
								METROPOLITAN	_	DISCIPLI
						60%	% SUBMISSION - 09/28/15			DISCIPLI


CIVIL EAS	۲ - VOLUME 10	SHEET
SIGNAL PLAN - S	SIGNAL SYSTEM "H"	198
_	ND WOODDALE AVE S CTION NOTES	OF
	SHEET NAME: E2-TFC-SIG-TH7E - 002	266


(PHASE 4) LUMINAIRE-LED (FOR 40' MOUNTING HEIGHT) 1-TYPE D SIGN (D-3) (SEE SIGN DETAILS) X" CONDUIT TO HH 8:


 $\langle 4 \rangle$  PA85 POLE FOUNDATION

TYPE PA85-A-20 (DAVIT AT 350 DEG)


1-ANGLE MOUNT SIGNAL-OVERHEAD AT O' 2-ANGLE MOUNT SIGNALS AT 90 AND 180 DEG 2-ANGLE MOUNT C.D. PED HEADS AT 90 AND 180 DEG 1-APS PB AND SIGN (RT ARROW) (PB4-2) 1-ONE WAY EVP DETECTOR AND CONFIRMATORY LIGHT







D-3



"Wooddale Ave S" E Mod;

PANEL MOUNTING SIGN POLE TOTAL PANEL a QTY SIZE AREA NO NO AREA NUMBER SPACING LEGEND SQ FT FEET INCH SQ FT (1) EAST MN 7 LEFT ARROW 66 19.25 D-1 1 6 42 x 19.25 36 1 2 
 66
 41.25

 24
 19.00
 3 4 D-2 2 90 x 41.25 36 WEST MN 7 UP ARROW, EAST MN 7 RIGHT ARROW 5 1 2 36 19.00 WOODDALE AVE S D-3 1 114 x 4

SPECIFIC NOTES:

Z

ŝ


\3400\_

SPACING BETWEEN STIFFENERS SHALL NOT EXCEED 36 INCHES AND SHALL BE UNIFORMLY SPACED. SEE STANDARD SIGNS MANUAL, PAGE 105A FOR BRACKET SPACING REQUIREMENTS.

GENERAL NOTES:


~								
÷	NO.	DATE	BY	CHECK DESIGN	REVISION / SUBMITTAL			
B								
: 37						<b>AECOM</b> Kimley »Horn		
01							SOLITUA/EST	Т
2015						ALETRODOL ITANI	Green Line LRT Extension	
21							[	DISCIPLIN
Sep,						60% SUBMISSION - 09/28/15	Ĕ	
0)	-							

GENERAL NOIES: 1. CORNERS OF STANDARD SIGN PANELS WITH MARGINS SHALL BE TRIMMED. 2. TYPE D SIGN PANELS EXTENDING BEYOND THE BORDER SHALL NOT BE TRIMMED. 3. FOR STRUCTURAL DETAILS OF MAST ARM MOUNTED SIGNS SEE STANDARD SIGN MANUAL, PAGE 105A. 4. FOR TYPE D STRINGER AND PANEL JOINT DETAILS SEE STANDARD SIGNS MANUAL, PAGE 105. 5. THE MAST ARM MOUNTED SIGNS ARE INCIDENTAL.



"WEST" E Mod; "EAST" E Mod; Arrow 5 - 13.0" 90°; Arrow 14 - 18.0" 0°;

CIVIL EAS	Γ - VOLUME 10	SHEET
	SIGNAL SYSTEM "H"	199
-	ND WOODDALE AVE S	OF
	SIGN DETAILS	
	E2-TFC-SIG-TH7E - 003	266



 RA		-1	$\mathbf{r}$
 RA	<b>١</b>	-1	ι.
 •••	••		-

### SHEET NAME E2-TFC-SIG-WDL-001

**CIVIL EAST - VOLUME 10** SIGNAL PLAN - SIGNAL SYSTEM "I" WOODDALE AVE S AND W 36TH ST

SHEET 200

OF

266

- 5, 5, AND 7 BEING PROTECTED-PERMISSIVE, WITH FLASHING YELLOW ARROWS. PHASES 2 AND 6 ARE ON VEHICLE SOFT RECALL. SIGNAL SYSTEM SHALL BE FULLY ACTUATED. LRT AND FREIGHT RAIL SHALL OPERATE WITH PREEMPTION, INCLUDING TRACK CLEARANCE.
- \_

THE SIGNAL SYSTEM FLASH MODE IS ALL RED. NORMAL OPERATION SHALL BE 8 PHASE WITH PHASES 1, 3, 5, AND 7 BEING PROTECTED-PERMISSIVE, WITH \_


SIGNAL SYSTEM OPERATIONS


# SIGNAL SYSTEM "I" IS BEING MODIFIED TO PROVIDE LRT PREEMPTION IN ADDITION TO EXISTING FREIGHT PREEMPTION.

VIDE	O DETECT	OR CHA	RT
DESIGNATION	NO.	FUNCTION	LOCATION
D1-1		INPLACE	
D1-2		INPLACE	
D2-1		INPLACE	
D3-1		INPLACE	
D3-2		INPLACE	
D4-1		INPLACE	
D4-2		INPLACE	
D5-1		INPLACE	
D5-2		INPLACE	
D6-1		INPLACE	
D7-1		INPLACE	
D7-2		INPLACE	
D8-1		INPLACE	
D8-2		INPLACE	

==========:

\_\_\_\_\_





		SIG	NAL IN		ONS A	ND BR	ACKET	ING	
SIG.	FAOF		CIO		LED	INDICA	TIONS		BRACKET MOUNTING
POLE	FACE NO.	SIGNAL FACE MOUNT	SIG.		12" IND	ICATION:	s	PED	ANGLE, TYPE, AND
NO.	NO.		Ø	RED	YEL	FYA	GRN	SYM.	STANDARD PLATE NO.
	1-1	MAST ARM (END)	1		<		<		INPLACE
			2			→			
	6-2	MAST ARM (MID)	6	0	0		0		INPLACE
MA-1	6-1	POLE MOUNT	6	0	0		0	*	INPLACE
	3-2 POL		3						
		POLE MOUNT	4						INPLACE
			4					*	
3–1		3		<b>_</b>		<b>_</b>			
	3–1	MAST ARM (END)	4			-			INPLACE
	8-2	MAST ARM (MID)	8	0	0		0		INPLACE
MA-2	8-1	POLE MOUNT	8	0	0		0	*	INPLACE
			5				<b>—</b>		
	5-2	POLE MOUNT	6						INPLACE
			6					*	
	5-1	MAST ARM (END)	5				<		INPLACE
	5-1		6						
	2-2	MAST ARM (MID)	2	0	0		0		INPLACE
MA-3	2-1	POLE MOUNT	2	0	0		0	*	INPLACE
			7				<		
	7–2	POLE MOUNT	8			-			INPLACE
			8					*	
	7-1	MAST ARM (END)	7		- ▼				INPLACE
			8			<			
	4-2	MAST ARM (MID)	4	0	0		0		INPLACE
MA-4	4-1	POLE MOUNT	4	0	0		0	*	INPLACE
			1	4	<				
	1-2	POLE MOUNT	2			<			INPLACE
			2					*	

\* EXISTING PEDESTRIAN INDICATIONS SHALL REMAIN INPLACE.

NO.	REMARKS	NO.	REMARKS	
MA-1	REMAIN INPLACE	HH-2	REMAIN INPLACE	
MA-2	REMAIN INPLACE	HH-3	REMAIN INPLACE	
MA-3	REMAIN INPLACE	HH-4	REMAIN INPLACE	
/A-4	REMAIN INPLACE	HH-5	REMAIN INPLACE	
CAC-1	REMAIN INPLACE	HH-6	REMAIN INPLACE	
PBS-1	REMAIN INPLACE	HH-7	REMAIN INPLACE	
PBS-2	REMAIN INPLACE	HH-8	REMAIN INPLACE	
PBS-3	REMAIN INPLACE	HH-9	REMAIN INPLACE	
PBS-4	REMAIN INPLACE	HH-10	REMAIN INPLACE	
PBS-5	REMAIN INPLACE	HH-11	REMAIN INPLACE	
PBS-6	REMAIN INPLACE	HH-12	REMAIN INPLACE	
PBS-7	REMAIN INPLACE	HH-13	REMAIN INPLACE	
HH-1	REMAIN INPLACE			

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL				
						<b>AECOM</b> Kimley»Horn	METROPOLITAN	SOUTHWEST Green Line LAT Estimation	
						60% SUBMISSION - 09/28/15			DISCIPLI
						00 /8 SODIMISSION - 09/20/13			

SHEET

OF


266

CIVIL EAST - VOLUME 10 SIGNAL PLAN - SIGNAL SYSTEM "I"

> TRAFFIC SHEET NAME: E2-TFC-SIG-WDL - 002

WOODDALE AVE S AND W 36TH ST


IE:





Sep, 21 2015 07:40 am V: \3400\_ADC\CAD\SEGMENT E2\PLAN SHEETS\TRAFFIC\E2-TFC-SIG-WDL.dwg By: brian.

	INPLACE SIG	NAL STR	UCTURES	٦ 🗆	SIGNAL STRUC	TURE L	DCATIONS				SIGN	AL IND	ICAT	IONS
NO.	REMARKS	NO.	REMARKS	NO.	LOCATION (1)	NO.	LOCATION (1)			FACE	SIGNAL FACE MOUNT	SIG.	1	LED 2″IN
HH-1 HH-2 HH-3 HH-4 HH-5 HH-6 HH-7	REMOVE REMOVE REMOVE, SEE NOTE 19 REMOVE REMOVE OK AS IS OK AS IS		REMOVE FOUNDATION OK AS IS REMOVE FOUNDATION REMOVE FOUNDATION	HH- 1 HH- 2 HH- 3 HH- 4 HH- 5 HH- 6 HH- 7	199+55.49 - 45.34' LT 200+25.83 - 75.61' LT 200+50.94 - 50.74' LT 200+79.04 - 19.27' RT 199+95.61 - 29.05' RT		198+77.61 - 135.76' L 		1A-1 -	6-2 6-1	MAST ARM (END) MAST ARM (MID) POLE MOUNT	1 2 6 6 3	RED •	YEL ••• •
HH-8 HH-9 HH-10 HH-11 HH-12 HH-13	OK AS IS OK AS IS REMOVE OK AS IS OK AS IS REMOVE	MA-3 MA-4	REMOVE FOUNDATION REMOVE FOUNDATION	HH- 8 HH- 9 HH-10 HH-11 HH-12	199+01.00 - 52.02' LT 199+11.74 - 62.70' LT	SP-1	NORTH SIDE OF CAC-1 FOUNDATION BY OTHERS			3–1	POLE MOUNT MAST ARM (END) MAST ARM (MID)	4 4 3 4 8	•	•
CO BA	ORDINATES ARE HENN SED ON THE MINNESO UTHERN ZONE, NAD83	EPIN COL DTA COORI 5 1986 (1	JNTY GROUND FEET, DINATE SYSTEM, NON-HARN VALUES)	PBS-2 PBS-3 PBS-4 PBS-5	198+68.12 - 36.74' LT 200+31.07 - 54.93' LT 200+48.79 - 46.43' LT 200+90.83 - 21.28' RT 200+93.20 - 33.20' RT 199+86.04 - 29.72' RT			M	IA-2 -	5-2	POLE MOUNT POLE MOUNT	8 5 6 6 5	•     •	•
					198+59.64 - 31.26' LT	ATION		AST M	IA-3 -	2-2 2-1	MAST ARM (END) MAST ARM (MID) POLE MOUNT POLE MOUNT	6 2 2 7 8	•	•
				MA-1 MA-2 MA-3 MA-4	199+59.21 - 41.91' LT 200+42.97 - 57.95' LT 200+97.86 - 23.84' RT 200+17.20 - 50.61' RT	200+04 200+97 200+48	.66 - 31.60' LT .29 - 7.66' LT .42 - 23.11' RT	30′ 45′ 30′ 40′		4-2	MAST ARM (END) MAST ARM (MID)	8 7 8 4	•	•
	1)		IRES SHALL BE INSTALLED	ALL ST	THE CENTER OF THE HANDHOLI ATIONS AND OFFSETS ARE REFI	ERENCED F	FROM W. 36TH ST ALIGNM	ENT. M	IA-4		POLE MOUNT	4 1 2	•	•
	2) 3)	ALL HANDHO ALL PEDEST ONE APS PL	RIAN PUSHBUTTONS SHALL SHBUTTON AND SIGN (LT A	ITH METAL F BE APS PUSH RROW) SHALL	VISIONS). RAMES AND COVERS (SEE SPECIA BUTTONS WITH SIGNS (SEE SPEC . BE FURNISHED AND INSTALLED	IAL PROVI ON PS-2,4	SIONS). ,7 & MA-4.	*	PEDES	STRIAN	INDICATIONS SHALL BE	2 INTER	IATIONA	AL SY
3A CHECK DE	2) 3) 4) 5) 6) 7) 8) 9) 10) 11) 12) 13) 14) 15) 16) 17) 18) 19) 20) 21)	ALL HANDHC ALL PEDEST ONE APS PL INTERNATIC (HAND AND (SEE SPECI ALL VEHICL THE ENGINE ALL SIGNAL THE CONTRA WALK, ETC VIDEO DETE COMMON BAC VIDEO DETE COMMON BAC INCIDENTAL OVERHEAD I SYSTEM. (S ALL ITEMS THE CONTRA SIGNAL INIC THE CONTRA THE CONTRA THE CONTRA THE CONTRA THE CONTRA SIGNAL INICATE A INDICATE HANDHOLE I SHALL BE F THE CONTRA MAILROAD H SHALL BE F THE CONTRA SIGNAL BE THE CONTRA	LES SHALL BE PVC TYPE W RIAN PUSHBUTTONS SHALL SHBUTTON AND SIGN (LT A SHBUTTON AND SIGN (RT A NAL SYMBOLS SHALL BE US WALKING PERSON). ALL PE AL PROVISIONS). LAR AND PEDESTRIAN INDI ER SHALL LOCATE ALL POL FACES SHALL HAVE BACKG CTOR SHALL INSTALL COUN ) ON THE LUMINIAIRE EXTE ITED ON THE MAST ARMS (S CTOR SHALL RESTORE ALL . TO ITS ORIGINAL CONDI L PROVISIONS FOR EMERGE CTOR SYSTEM AND BATTEF K FILL AT SIGNAL SYSTEM. MAST ARM MOUNTED TYPE "I SEE SPECIAL PROVISIONS AND CTOR SHALL INSTALL COUN CTOR SHALL INSTALL COUNT CTOR SHALL FURNISH AND NCTOR SHALL FURNISH AND NCTOR SHALL FURNISH AND DICATIONS 1-1,3-1,5-1 AM CTOR IS RESPONSIBLE FOF IS ITEMS TO BE INCLUDED IS SITEMS TO BE INCLUDED IS SITEMS TO BE INCLUDED IS SITEMS TO BE INCLUDED CTOR SHALL FURNISH AND DICATIONS HALL FURNISH AND DICATIONS TO BE INCLUDED CS SITEMS TO BE INCLUDED CTOR SHALL FURNISH AND DICATIONS HALL FURNISH AND DICATIONS TO BE INCLUDED COR SHALL FURNISH AND INEER. THE CONTRACTOR S	ITH METAL F BE APS PUSH RROW) SHALL RROW) SHALL ED FOR ALL DESTRIAN IN CATIONS SHA ES AND HAND ROUND SHIEL TY FURNISHE INSIONS. VII SE SPECIAL DISTURBED T TION OR BET NCY VEHICLE Y BACK-UP S URES AS DIR O' SIGN PANE INSTALL SIG INSTALL 1 Y HALL FURNIS	DVISIONS). RAMES AND COVERS (SEE SPECIA IBUTTONS WITH SIGNS (SEE SPECIA IBUTTONS WITH SIGNS (SEE SPECIA BE FURNISHED AND INSTALLED PEDESTRIAN INDICATIONS IDICATIONS SHALL HAVE COUNTDO ALL USE LED TECHNOLOGY (SEE S HOLES PRIOR TO ANY CONSTRUCT DS. D VIDEO CAMERAS. VIDEO CAMER DEO CAMERAS 2 AND 4 SHALL BE PROVISIONS). URF, CONCRETE OR BITUMINOUS TER (SEE SPECIAL PROVISIONS) E PRE-EMPTION (EVP) SYSTEM, SIGNAL SERVICE CABINET. RECTED BY THE ENGINEER SHALL ELS SHALL BE INCIDENTAL TO SI UNLESS NOTED OTHERWISE. ED CONTROLLER AND CABINET. SNAL SERVICE CABINET. SNAL SERVICE CABINET. ALL SIGNAL SERVICE CABINET. SNAL SERVICE SHALL SHALL SERVICE SHALL SHALL SERVICE CABINET. SNAL SERVICE SHALL SHALL SERVICE CABINET. SNAL SERVICE SHALL SHALL SER	IAL PROVI ON PS-2,4 ON PS-1,3 WN TIMERS PECIAL PR ION. AS 1 AND MOUNTED O BE GNAL ACENT TO ER FOR TH ACE HANDH ND PROTEC D INTERCO D INTERCO D INTERCO	SIONS). ,7 & MA-4. ,5 & 6. OVISIONS). 3 SHALL DN EXTENSION HE TRAFFIC SIGNAL SYSTEM HOLE 3 AND INPLACE DNNECT CABLE	**	PEDES PEDES STRAI	GTRIAN GTRIAN GHT M	INDICATIONS SHALL BE COUNTDOWN TIMER. OUNT PLUMBIZER, SEE S RR BUNGALOW TO INP. RF NTERCONNECT CABLE INP. RR BUNGALOW	INTERI PECIAL R HH TO	PROVIS INP HH-12 CT CABL	· RR
3Y CHECK DE	2) 3) 4) 5) 6) 7) 8) 9) 10) 11) 12) 13) 14) 15) 16) 17) 18) 19) 20) 21)	ALL HANDHC ALL PEDEST ONE APS PL INTERNATIC (HAND AND (SEE SPECI ALL VEHICL THE ENGINE ALL SIGNAL THE CONTRA WALK, ETC VIDEO DETE COMMON BAC VIDEO DETE COMMON BAC INCIDENTAL OVERHEAD I SYSTEM. (S ALL ITEMS THE CONTRA SIGNAL INIC THE CONTRA THE CONTRA THE CONTRA SIGNAL INICATE A INDICATE A INDICATE A INDICATE A SHALL BE F THE CONTRA MAILROAD F SHALL BE F THE CONTRA SIGNAL INE SHALL BE F THE CONTRA ALL CONTRA SHALL BE F THE CONTRA	LES SHALL BE PVC TYPE W RIAN PUSHBUTTONS SHALL SHBUTTON AND SIGN (LT A SHBUTTON AND SIGN (LT A NAL SYMBOLS SHALL BE US WALKING PERSON). ALL PE AL PROVISIONS). LAR AND PEDESTRIAN INDI ER SHALL LOCATE ALL POL FACES SHALL HAVE BACKG CTOR SHALL INSTALL COUND ON THE LUMINIAIRE EXTE ITED ON THE MAST ARMS (S CTOR SHALL RESTORE ALL CTOR SHALL RESTORE ALL CTION SYSTEM AND BATTEF ISTED ON THE MAST ARMS (S CTOR SHALL RESTORE ALL CTION SYSTEM AND BATTEF ISTED ON THE MAST ARMS (S CTOR SHALL RESTORE ALL SCTION SYSTEM AND BATTEF SE SPECIAL PROVISIONS). SHOWN ARE FURNISHED AND CTOR SHALL FURNISH CTOR SHALL FURNISH AND CTOR SHALL FURNISH CTOR SHALL FURNISH AND CTOR SHALL FURNISH CTOR SHALL FURNISH AND CTOR SHALL FURNISH CTOR SHALC FURNISH AND	ITH METAL F BE APS PUSH RROW) SHALL RROW) SHALL ED FOR ALL DESTRIAN IN CATIONS SHA ES AND HAND ROUND SHIEL TY FURNISHE INSIONS. VII SE SPECIAL DISTURBED T TION OR BET NCY VEHICLE Y BACK-UP S URES AS DIR O' SIGN PANE INSTALL SIG INSTALL 1 Y HALL FURNIS	DVISIONS). RAMES AND COVERS (SEE SPECIA IBUTTONS WITH SIGNS (SEE SPECIA IBUTTONS WITH SIGNS (SEE SPECIA DE FURNISHED AND INSTALLED PEDESTRIAN INDICATIONS IDICATIONS SHALL HAVE COUNTDO ALL USE LED TECHNOLOGY (SEE S HOLES PRIOR TO ANY CONSTRUCT DS. ID VIDEO CAMERAS. VIDEO CAMER DE VIDEO CAMERAS. VIDEO CAMER DE OCAMERAS 2 AND 4 SHALL BE PROVISIONS). URF, CONCRETE OR BITUMINOUS TER (SEE SPECIAL PROVISIONS) E PRE-EMPTION (EVP) SYSTEM, SIGNAL SERVICE CABINET. RECTED BY THE ENGINEER SHALL ELS SHALL BE INCIDENTAL TO SI UNLESS NOTED OTHERWISE. ED CONTROLLER AND CABINET. SNAL SERVICE CABINET. SNAL SERVICE CABINET. - R10-X12 (36"X42") SIGNS ADJ ING THE CONNECTION OF THE POW SYSTEM PAY ITEM. ERCONNECT SYSTEM PAY ITEM. INPLACE CONDUIT BETWEEN INPLE NALSE SHALL BE COILED A ALLED. ONCE COMPLETE, RAILROA VIA HANDHOLE 12 AS SHOWN IN T AGI ANTENNA ON MAST ARM 1 AS H AND INSTALL 1 ENCOM RADIO (2) IN THE CONTROLLER CABINET (2) IN THE CONTROLLER CABINET (3) IN THE CONTROLLER CABINET (3) IN THE CONTROLLER CABINET (3) IN THE CONTROLLER CABINET (4) AND INSTALL 1 ENCOM RADIO (2) IN THE CONTROLLER CABINET	IAL PROVI ON PS-2,4 ON PS-1,3 WN TIMERS PECIAL PR ION. AS 1 AND MOUNTED O BE GNAL ACENT TO ER FOR TH ACE HANDH ND PROTEC D INTERCC HE PLANS. DIRECTED 5100 AND	SIONS). ,7 & MA-4. ,5 & 6. OVISIONS). 3 SHALL DN EXTENSION HE TRAFFIC SIGNAL SYSTEM HOLE 3 AND INPLACE DNNECT CABLE	**		INP. RR I	INDICATIONS SHALL BE COUNTDOWN TIMER. OUNT PLUMBIZER, SEE S OUNT PLUMBIZER, SEE S INP. RR BUNGALOW INP. RR BUNGALOW INP. RR BUNGALOW	INTERI PECIAL R HH TO	PROVIS INP HH-12 CT CABL	RR

NO.








						ſ
DICATI	ONS A	ND BR	ACKEI	ING		
	LED	INDICAT	TIONS		BRACKET MOUNTING	1
	12" INDI	CATIONS	S	PED	ANGLE, TYPE, AND	
RED	YEL	FYA	GRN	SYM.	STANDARD PLATE NO.	
<b>~</b>					**	
0	0		0		**	
0	0		0	*	INPLACE	
					INPLACE	
-	-		-		**	
•	•		•		**	
٠	•		٠		**	
•	•		•		180° PLATE 8110E, TYPE 10A	
-	-		-		90° PLATE 8110E, TYPE 10B	
				*		
					INPLACE	
0	0		0		INPLACE	
0	0		0		INPLACE	
4					INPLACE	
4					INPLACE	
0	0		0		INPLACE	1
0	0		0		INPLACE	1
0	0		0		INPLACE	1
4					INPLACE	1
	1					1

SIGNAL STRUCTURE LOCATIONS								
LOCATION (1) NO. LOCATION (1)								
-								
LOCA	TION		MAST					
FOUNDATION (1)		AIM ARM TO	ARM					
			50'					


(1) TO THE CENTER OF THE HANDHOLE OR CONCRETE FOUNDATION.

	INPLACE STRUCTURES							
	REMARKS	NO.	REMARKS					
	REMAIN INPLACE	HH-6	REMOVE					
2	REMOVE	HH-7	REMAIN INPLACE					
3	REMAIN INPLACE	HH-8	REMAIN INPLACE					
ŀ	REMAIN INPLACE	HH-9	REMAIN INPLACE					
1	REMAIN INPLACE	HH-10	REMAIN INPLACE					
	REMAIN INPLACE	HH-11	REMAIN INPLACE					
	REMAIN INPLACE	HH-12	REMAIN INPLACE					
2	REMAIN INPLACE	HH-13	REMAIN INPLACE					
5	REMAIN INPLACE	HH-14	REMAIN INPLACE					
ł	REMOVE	HH-15	REMAIN INPLACE					
5	REMOVE							

CIVIL EAST	- VOLUME 10	SHEET				
SIGNAL PLAN - SIGNAL SYSTEM "J"						
AH 25 AND BELTLINE BLVD/OTTAWA AVE EQUIPMENT SCHEDULE						
	SHEET NAME: E2-TFC-SIG-OTT - 002	266				



Sep, 21 2015 07:45 am V:\3400\_ADC\CAD\SEGMENT E2\PLAN SHEETS\TRAFFIC\E2-TFC-SIG-OTT.dwg By: brian.



sep, 21 2015 07:47 am V:\3400\_ADC\CAD\SEGMENT E2\PLAN SHEETS\TRAFFIC\E2-TFC-SIG-BLT.dwg By: brian.v

	SIGNAL STRU	JCTURE LO	CATIONS	
NO.	LOCATION (1)	NO.	LOCATION	(1)
HH-1		SP-1		
HH-2		CAC-1		
HH-3				
HH-4				
HH-5				
HH-6				
HH-7				
		·		
NO.	L	OCATION		MAST
	FOUNDATION (1)		AIM ARM TO	ARM
MA-1	i i			XX,
SA-1				N/A
SA-2				N/A

		SIG	NAL IN	DICATIO	ONS AI	ND BR	ACKET	ING	
SIG. POLE	FACE NO.	SIGNAL FACE MOUNT	SIG. Ø	12" INDICATIONS   PED			PED	BRACKET MOUNTING ANGLE, TYPE, AND	
NO.	- NO.		~	RED	YEL	FYA	GRN	SYM.	STANDARD PLATE NO.
MA-1	2-3	MAST ARM (END)	2	•	•		•		*
	2-2	MAST ARM (MID)	2	٠	٠		٠		*
SA-1	2-1	PEDESTAL MOUNT	2	٠	٠		۲		90° PLATE 8111E, TYPE 4A
SA-2	2-4	PEDESTAL MOUNT	2	٠	٠		٠		90° PLATE 8111E, TYPE 4A

\* STRAIGHT MOUNT PLUMBIZER, SEE SPECIAL PROVISIONS.


(1) TO THE CENTER OF THE HANDHOLE OR CONCRETE FOUNDATION.


ł		ATE			DEOLON			
	NO. D			CHECK	DESIGN	REVISION / SUBMITTAL	AECOM Kimley »Horn	
			_				60% SUBMISSION - 09/28/15	DISCIPLIN

CIVIL EAS	Г - VOLUME 10	SHEET				
SIGNAL PLAN - SIGNAL SYSTEM "K"						
BELTLINE BLVD AT TRACK CROSSING INTERSECTION NOTES						
TRAFFIC	SHEET NAME: E2-TFC-SIG-BLT - 002	266				

### NOTES:

- 1.) SEE DIVISION "SS" OF SPECIAL PROVISIONS FOR EMERGENCY VEHICLE PREEMPTION (EVP) SYSTEM, VIDEO DETECTION SYSTEM, BATTERY BACK-UP SYSTEM, AND FIBER OPTIC COMMUNICATION EQUIPMENT.
- 2.) ONE LED LUMINAIRE SHALL BE INSTALLED ON EACH MAST ARM LIMINAIRE SHAFT EXTENSION. SEE SPECIAL PROVISIONS.
- 3.) LUMINAIRE SYMBOL IS SHOWN ROTATED ON THE PLAN TO INCREASE LEGIBILITY. MOUNTING POSITION SHALL BE 0 DEGREES.
- THE CONTRACTOR SHALL INSTALL ONE VIDEO DETECTION CAMERA ON EACH DAVIT ARM AND ON SA-1. VIDEO DETECTION CAMERAS SHALL INCLUDE A 6-FT HEIGHT 4.) EXTENSION BRACKET.
- 5.) THE CONTRACTOR SHALL FURNISH AND INSTALL ONE R10-X12 SIGN (36"X42") ON THE MAST ARM OF MA-2 AND MOUNTED TO SIGN BRACKET "D" AS DIRECTED BY THE ENGINEER.
- THE CONTRACTOR SHALL FURNISH AND INSTALL ONE R9-3 SIGN (18"X18") ON 6.) THE UPRIGHT POLE OF MA-3 FACING MA-1, MA-1 FACING MA-3, MA-1 FACING SA-1, SA-1 FACING MA-1, SA-1 FACING MA-2, AND ON THE UPRIGHT POLE OF MA-2 FACING SA-1 AS DIRECTED BY THE ENGINEER.
- THE CONTRACTOR SHALL PLACE COMMON BACK FILL AND RESTORE ALL 7.) DISTURBED TURF, CONCRETE OR BITUMINOUS WALK, ETC. TO ITS ORIGINAL CONDITION OR BETTER. ALL COSTS FOR THIS WORK SHALL BE INCIDENTAL
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING THE CONNECTION 8.)
- OF THE POWER FOR THE TRAFFIC SIGNAL SYSTEM WITH THE POWER COMPANY. THE CONTRACTOR SHALL VERIFY ALL UTILITY LOCATIONS PRIOR TO CONSTRUCTION. 9
- 10.) EXACT LOCATIONS OF HANDHOLES, POLES, DETECTION ZONES, CABINETS, AND
- BASES SHALL BE DETERMINED IN THE FIELD BY THE ENGINEER.
  11.) THIS PLAN SPECIFIES CONDUIT SIZES, TYPES, AND GENERAL LOCATIONS. THE EXACT LOCATION WILL BE DETERMINED IN THE FIELD. CONDUITS UNDER THE DEVINE OF T ROADWAY REQUIRE BORING.
- 12.) ALL NEW VEHICULAR SIGNAL INDICATIONS SHALL BE LED AND SHALL HAVE BACKGROUND SHIELDS. ALL POLE MOUNTED BRACKETING SHALL BE EXTENDED BRACKETING. SEE SPECIAL PROVISIONS.
- 13.) OVERHEAD MAST ARM MOUNTED TYPE "D" SIGN PANELS SHALL BE INCIDENTAL. FOR TYPE "D" SIGNS SEE EQUIPMENT SCHEDULE SHEETS.
- 14.) FOR PAVEMENT MARKINGS, SEE SIGNING AND STRIPING PLANS. 15.) SEE INTERCONNECT PLAN FOR ADDITIONAL DETAIL.





SIG.	<b>F105</b>		010		LED	INDICAT	TIONS		BRACKET MOUNTING	
POLE	FACE	SIGNAL FACE MOUNT	SIG.		12" IND	CATIONS	S	PED	ANGLE, TYPE, AND	
NO.	NO.		ø	RED	YEL	FYA	GRN	SYM.	STANDARD PLATE NO.	
	2-3	MAST ARM (END)	2	•	•		•		**	
MA-1	2-2	MAST ARM (INSIDE)	2	•	•		•		**	
	2-1	POLE MOUNT	2	•	•		•		180° PLATE 8110E, TYPE 10A	
			-							
SA-1	1-2	POLE MOUNT	1	-	-		-		90° PLATE 8111E, TYPE 1A	
			2			-				
	1–1	MAST ARM (END)	1	-	-		-		**	
	1=1	MAST ARM (END)	2			-			**	
MA-2	6-3	MAST ARM (MID)	6	•	•		•		**	
	6-2	MAST ARM (INSIDE)	6	•	•		•		**	
	6-1	POLE MOUNT	6	•	•		•		180° PLATE 8110E, TYPE 10A	
	4-3	POLE MOUNT	4	•	•		•		90° PLATE 8110E, TYPE 10A	
	4-2	MAST ARM (END)	4	•	•		•		**	
MA-3	4-1	POLE MOUNT	4	•	•		•		180° PLATE 8110E, TYPE 10A	


\*\* STRAIGHT MOUNT PLUMBIZER, SEE SPECIAL PROVISIONS.

	SIGNAL STRU	CIURE LU	JUATIONS	
NO.	LOCATION (1)	NO.	LOCATION	(1)
HH-1		SA-1		
HH-2				
HH-3				
HH-4				
HH-5				
NO		OCATION	1	MAS
	FOUNDATION (1)		AIM ARM TO	ARM
MA-1				XX,
MA-2				XX'
MA-3				XX,

VIDEO DETECTOR CHART						
DESIGNATION	NO.	FUNCTION	LOCATION			
D1-1	VIDEO (V-1)	(1)	20 & 50			
D1-2	VIDEO (V-1)	(1)	5 & 35			
D2-1, D2-2	VIDEO (V-3)	(1)	300			
D2-3, D2-4	VIDEO (V-3)	(1)	5 & 20			
D4-1	VIDEO (V-2)	(1)	120			
D4-2	VIDEO (V-2)	(1)	5			
D4-3	VIDEO (V-2)	(1)	5 & 20			
D6-1, D6-2	VIDEO (V-1)	(1)	300			
D6-3, D6-4	VIDEO (V-1)	(1)	5 & 20			

 LOCATION: DISTANCE FROM CROSSWALK/ STOP BAR IN FEET
 (1)-CALL AND EXTEND

SOUTHWEST




Z

•

(1) TO THE CENTER OF THE HANDHOLE OR CONCRETE FOUNDATION.

TYPICAL 4-SECTION SIGNAL HEAD PHASING WITH FLASHING YELLOW ARROW SIGNAL FACE 1-1 AND 1-2 Ø1 Ø2 FYA Ø1 G

	CIVIL EAS	T - VOLUME 10	SHEET			
	SIGNAL PLAN - SIGNAL SYSTEM "L"					
	CSAH 25 AND LYNN AVE EQUIPMENT SCHEDULE					
C		SHEET NAME: E2-TFC-SIG-LYN - 002	266			



AN

CIVIL EAST - VOLUME 10 SIGNAL PLAN - SIGNAL SYSTEM "M"									
	SHEET NAME: E3-TFC-SIG-WLK - 001	266							

PUSH BUTTONS AND COUNTDOWN TIMERS.

- THE SIGNAL SYSTEM FLASH MODE IS ALL RED. - NORMAL OPERATION IS 2 PHASE.

SIGNAL SYSTEM "M" IS BEING MODIFIED TO PROVIDE PEDESTRIAN

SHEET IS INPLACE & SHALL REMAIN INPLACE UNLESS OTHERWISE NOTED. A ▲ DENOTES WORK TO BE COMPLETED BY THE
REMAIN INPLACE UNLESS
OTHERWISE NOTED. A A DENOTES
WORK TO BE COMPLETED BY THE
CONTRACTOR.

ALL SIGNAL EQUIPMENT ON THIS
REMAIN INPLACE & SHALL
ALL SIGNAL EQUIPMENT ON THIS SHEET IS INPLACE & SHALL REMAIN INPLACE UNLESS OTHERWISE NOTED. A ▲ DENOTES WORK TO BE COMPLETED BY THE

EXISTING PUSHBUTTON PEDESTAL 8 IN NORTHWEST CORNER TO BE REMOVED. 2. EXISTING PEDESTRIAN SIGNAL HEADS ON MAST ARM 1 AND 5 AND PEDESTAL POLE 3 AND 7 TO BE REMOVED.

3. EXISTING PEDESTRIAN PUSHBUTTONS ON MAST ARM 1 AND 5

EXISTING CONDUIT RUN BETWEEN HH 3 AND PUSHBUTTON

EXISTING CONDUIT RUN BETWEEN HH 3 AND MAST ARM 5 TO

BE REMOVED AS NEEDED TO MAKE NEW CONDUIT CONNECTION

AND PEDESTAL POLE 4 TO BE REMOVED. 4. EXISTING HH 3 IN SOUTHWEST CORNER TO BE REMOVED.

6. EXISTING CONDUIT RUN BETWEEN HH 3 AND HH 4 TO BE

8. EXISTING CONDUIT RUN BETWEEN PEDESTAL POLE 7 AND

PUSHBUTTON PEDESTAL 8 TO BE REMOVED.

PEDESTAL 4 TO BE REMOVED.

ABANDONED INPLACE.

TO MAST ARM 5

- ▲ REMOVAL NOTES:
- ALL NEW CONDUIT SHALL BE PVC SCHEDULE 80 OR HDPE SCHEDULE 80 AND SHALL CARRY 1/C #6 GREEN INSULATED GROUNDING CONDUCTOR AS SHOWN IN THE PLAN. FOR PAVEMENT MARKINGS, SEE SIGNING AND STRIPING PLANS.

- 1.) SEE DIVISION "SS" OF SPECIAL PROVISIONS FOR ACCESSIBLE PEDESTRIAN SIGNAL (APS). ONE APS PEDESTRIAN PUSH BUTTON WITH SIGN R10-3E (9"X15") SHALL BE INSTALLED ON EACH SIGNAL MAST ARM AND ON EACH PUSH BUTTON STATION AS DIRECTED BY THE ENGINEER FOR OPERATION AS SHOWN IN THE PHASING LAYOUT.
- 3.) PEDESTRIAN INDICATIONS SHALL BE ONE SECTION LED WITH COUNTDOWN TIMERS UTILIZING

INTERNATIONAL SYMBOL (HAND AND WALKING PERSON) INDICATIONS. SEE SPECIAL

5.

7.


SIGNAL SYSTEM OPERATIONS


ALL SIGNAL EQUIPMENT ON THIS SHEET IS INPLACE & SHALL REMAIN INPLACE UNLESS OTHERWISE NOTED. A DENOTES WORK TO BE COMPLETED BY THE CONTRACTOR.

																_
	EQUIPMENT SCHEDULE															
	STRU	CTURE		SIGNA	_ M.A.		l	UMINAIRE	-		L HEAD KETING		S PUSH UTTON	SIGN	EVP	
NO.	TYPE	STD PLATE	FDN TYPE STD PLATE	LENGTH	HEAD LOCATION	ΗТ	M.A. LENGTH	MTD POSITION	FIXTURE	TYPE	MTD POSITION	NO.	MTD POSITION	TYPE		
$\langle \underline{1} \rangle$	MAST ARM POLE	IP	IP	IP	IP	IΡ	IP	IP	IP	IP	IP	1	270 <b>*</b>	R10-3e	_	
2	PUSHBUTTON PEDESTAL	1260	1082	_	_	-	-	-	-	-	-	1	0*	R10-3e	_	
< <u>3</u>	PEDESTAL POLE	IP	IP	-	_	-	-	-	-	IP	IP	1	270*	R10-3e	_	
< <u>4</u> >	PUSHBUTTON PEDESTAL	IP	IP	-	-	-	-	-	-	-	-	1	0*	R10-3e	-	
<u>ر</u> 5	MAST ARM POLE	IP	IP	IP	IP	IP	IP	IP	IP	IP	IP	1	270°	R10-3e	_	
6	PUSHBUTTON PEDESTAL	1260	1082	_	-	-	-	-	-	-	-	1	0*	R10-3e	_	
< <u>7</u> >	PEDESTAL POLE	IP	IP	_	-	-	-	-	-	IP	IP	1	270*	R10-3e	_	
8	PUSHBUTTON PEDESTAL	1260	1082	_	_	-	-	-	-	-	-	1	0*	R10-3e	_	
$(\hat{A})$	CABINET	IP	IP													
( <u>B</u> )	SERVICE CABINET	IP	IP													
(Ĉ)	SOURCE OF POWER	IP	IP													

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL	<b>AECOM</b> Kimley»Horn		SOUTHWEST Green Line Litt Extension	C
							METROPOLITAN		
						60% SUBMISSION - 09/28/15			DISCIPLIN

CIVIL EAST - VOLUME 10 SIGNAL PLAN - SIGNAL SYSTEM "M" CSAH 25 (W LAKE ST) AND DREW AVE S EQUIPMENT SCHEDULE NE: TRAFFIC SHEET NAME: E3-TFC-SIG-WLK - 002





ep, 21 2015 08:06 am V:\3400\_ADC\CAD\SEGMENT E3\PLAN SHEETS\TRAFFIC\E3-TFC-SIG-WLK.dwg BY:


LOOP D	ETECTOR	CHART
DESIGNATION	FUNCTION	LOCATION
D1-1	IP	IP
D1-2	IP	IP
D4-1	IP	IP
D4-2	IP	IP
D4-3	IP	IP
D4-4	IP	IP
D5-1	IP	IP
D5-2	IP	IP
D6-1	IP	IP
D6-2	IP	IP
D8-1	IP	IP
D8-2	IP	IP


ALL SIGNAL EQUIPMENT ON THIS SHEET IS INPLACE & SHALL REMAIN INPLACE UNLESS OTHERWISE NOTED. A DENOTES WORK TO BE COMPLETED BY THE CONTRACTOR.

																٦
EQUIPMENT SCHEDULE																
	STRL	ICTURE		SIGNA	L M.A.		ι		E		L HEAD KETING		S PUSH UTTON	SIGN	EVP	
NO.	TYPE	STD PLATE	FDN TYPE STD PLATE	LENGTH	HEAD LOCATION	нт	M.A. LENGTH	MTD POSITION	FIXTURE	TYPE	MTD POSITION	NO.	MTD POSITION	TYPE		
$\langle \underline{1} \rangle$	MAST ARM POLE	IP	IP	IP	IP	IP	IP	IP	IP	IP	IP	-	-	_	_	
2	PUSHBUTTON PEDESTAL	1260	1082	-	_	-	-	_	-	-	-	1	270°	R10-3e	_	
< <u>3</u> >	PEDESTAL POLE	IP	IP	-	-	-	-	-	-	-	-	1	0°	R10-3e	-	
< <u>4</u> >	MAST ARM POLE	IP	IP	IP	IP	IP	IP	IP	IP	IP	IP 🔺	1	270°	R10-3e	-	
(5)	PUSHBUTTON PEDESTAL	1260	1082	-	-	-	-	-	-	_	-	1	0*	R10-3e	-	
< <u>6</u> )	MAST ARM POLE	IP	IP	IP	IP	IP	IP	IP	IP	IP	IP 🖌	1	270 <b>°</b>	R10-3e	-	
< <u>7</u> >	PEDESTAL POLE	IP	IP	-	-	-	-	-	-	-	- 🔺	1	0°	R10-3e	-	
< <u>8</u> >	MAST ARM POLE	IP	IP	IP	IP	IP	IP	IP	IP	IP	IP 🖌	1	270 <b>°</b>	R10-3e	-	
(9)	PUSHBUTTON PEDESTAL	1260	1082	-	-	-	-	-	-	-	-	1	0°	R10-3e	-	
$(\hat{A})$	CABINET	IP	IP													
(B)	SER VICE CABINET	IP	IP													
(Ĉ)	SOURCE OF POWER	IP	IP													

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL					
						<b>AECOM</b> Kimley»H				
							IOFIT			CS
									SOUTHWEST	03
								METRODOLITAN	Green Line LRT Extension	
								METROPOLITAN		
						60% SUBMISSION - 09/28/15				DISCIPLIN
						60% SOBMISSION - 09/26/15				

CIVIL EAST - VOLUME 10 SIGNAL PLAN - SIGNAL SYSTEM "N" SAH 25 (W LAKE ST) AND MARKET PLAZA EQUIPMENT SCHEDULE INE: TRAFFIC SHEET NAME: E3-TFC-SIG-WLK - 005






p, 21 2015 08:07 am V:\3400\_ADC\CAD\SEGMENT E3\PLAN SHEETS\TRAFFIC\E3-TFC-SIG-EXC.dwg By: bric


						EC	UIPME	ENT SC	HEDU	LE							
	STRU	ICTURE		SIGNA	LUMINAIRE				SIGNAL HEAD BRACKETING		APS PUSH BUTTON		SIGN	EVP			
NO.	TYPE	STD PLATE	FDN TYPE STD PLATE	LENGTH	HEAD LOCATION	нт	M.A. LENGTH	MTD POSITION	FIXTURE	TYPE	MTD POSITION	N0.	MTD POSITION	TYPE		LVF	
$\langle \underline{1} \rangle$	MAST ARM POLE	IP	IP	IP	IP	IP	IP	IP	IP	IP	IP	2	0° 90°	R10-3e R10-3e		-	
< <u>2</u> >	PEDESTAL POLE	IP	IP	-	_	-	-	-	-	-	-	-	-	-		_	
< <u>3</u> >	MAST ARM POLE	IP	IP	IP	IP	IP	IP	IP	IP	IP	IP	1	90°	R10-3e		_	
$\langle 4 \rangle$	PUSHBUTTON PEDESTAL	1260	1082	-	_	-	-	-	-	-	-	1	0°	R10-3e		-	
(5)	MAST ARM POLE	IP	IP	IP	IP	IP	IP	IP	IP	IP	IP	1	90°	R10-3e		_	
6	PUSHBUTTON PEDESTAL	1260	1082	-	_	-	-	-	-	-	-	1	180*	R10-3e		_	
( <u>7</u> )	MAST ARM POLE	IP	IP	IP	IP	IP	IP	IP	IP	IP	IP	1	-	-		_	
<u>(8)</u>	PUSHBUTTON PEDESTAL	1260	1082	-	-	-	-	-	-	-	-	1	180*	R10-3e		_	
<u>(</u> 9)	PUSHBUTTON PEDESTAL	1260	1082	-	-	-	-	-	-	-	-	1	270°	R10-3e		-	
$(\hat{A})$	CABINET	IP	IP														
(B)	SERVICE CABINET	IP	IP														
( <u>c</u> )	SOURCE OF POWER	IP	IP														

ALL SIGNAL EQUIPMENT ON THIS SHEET IS INPLACE & SHALL REMAIN INPLACE UNLESS OTHERWISE NOTED. A DENOTES WORK TO BE COMPLETED BY THE	
OTHERWISE NOTED. A ▲ DENOTES WORK TO BE COMPLETED BY THE CONTRACTOR.	

NO.	DATE	BY	CHECK	DESIGN REVISION / SUBMITTAL				
					<b>AECOM</b> Kimley»Horn		SOLITHWEST	cs
						METROPOLITAN	Green Line LRT Extension	DISCIPLIN
					60% SUBMISSION - 09/28/15			DISCIPLIN

CIVIL EAST - VOLUME 10 SIGNAL PLAN - SIGNAL SYSTEM "O" 218 SAH 3 (EXCELSIOR BLVD) AND W 32ND ST EQUIPMENT SCHEDULE INE: TRAFFIC SHEET NAME: E3-TFC-SIG-EXC - 002





AN

NOTES:

- 1.) SEE DIVISION "SS" OF SPECIAL PROVISIONS FOR ACCESSIBLE PEDESTRIAN SIGNAL (APS).
- 2.) ONE APS PEDESTRIAN PUSH BUTTON WITH SIGN R10-3E (9"X15") SHALL BE INSTALLED ON EACH SIGNAL MAST ARM AND ON EACH PUSH BUTTON STATION AS DIRECTED BY THE ENGINEER FOR OPERATION AS SHOWN IN THE PHASING LAYOUT.
- 3.) PEDESTRIAN INDICATIONS SHALL BE ONE SECTION LED WITH COUNTDOWN TIMERS UTILIZING INTERNATIONAL SYMBOL (HAND AND WALKING PERSON) INDICATIONS. SEE SPECIAL PROVISIONS.
- A.) THE CONTRACTOR SHALL PLACE COMMON BACK FILL AND RESTORE ALL DISTURBED TURF, CONCRETE OR BITUMINOUS WALK, ETC. TO ITS ORIGINAL CONDITION OR BETTER. ALL COSTS FOR THIS WORK SHALL BE INCIDENTAL.
- 5.) THE CONTRACTOR SHALL VERIFY ALL UTILITY LOCATIONS PRIOR TO CONSTRUCTION.
- 6.) EXACT LOCATIONS OF POLES AND BASES SHALL BE DETERMINED IN THE FIELD BY THE ENGINEER.
- 7.) THIS PLAN SPECIFIES CONDUIT SIZES, TYPES, AND GENERAL LOCATIONS. THE EXACT LOCATION WILL BE DETERMINED IN THE FIELD. CONDUITS UNDER THE ROADWAY REQUIRE BORING.
- 8.) ALL NEW CONDUIT SHALL BE PVC SCHEDULE 80 OR HDPE SCHEDULE 80 AND SHALL CARRY 1/C #6 GREEN INSULATED GROUNDING CONDUCTOR AS SHOWN IN THE PLAN.
- 9.) FOR PAVEMENT MARKINGS, SEE SIGNING AND STRIPING PLANS.

REMOVAL NOTES:
 EXISTING PEDESTRIAN SIGNAL HEADS ON MAST ARM 1, 2, AND 4 AND PEDESTAL POLE 6 TO BE REMOVED.
 EXISTING PEDESTRIAN PUSHBUTTONS ON MAST ARM 1, 2, AND

4 AND PEDESTAL POLE 6 TO BE REMOVED.

ALL SIGNAL EQUIPMENT ON THIS
SHEET IS INPLACE & SHALL
REMAIN INPLACE UNLESS
OTHERWISE NOTED. A 🛦 DENOTES
WORK TO BE COMPLETED BY THE
CONTRACTOR.


С	HAR	Т		SIGNAL SYSTEM "P" IS BEING MODIFIED TO PROVIDE I	PEDESTRIAN								
	R Y G PUSH BUTTONS AND COUNTDOWN TIMERS.												
	004	400	400	SIGNAL SYSTEM OPERATIONS - THE SIGNAL SYSTEM FLASH MODE IS ALL RED. - NORMAL OPERATION IS 4 PHASE.									
	CIVIL EAST - VOLUME 10												
				LAN - SIGNAL SYSTEM "P" (EXCELSIOR BLVD) AND	220								
	WHOLE FOODS DRIVEWAY												
NE:		Т	TRAFFIC SHEET NAME: E3-TFC-SIG-EXC - 004										

																	_
	EQUIPMENT SCHEDULE																
	STRUCTURE				SIGNAL M.A.			LUMINAIRE				APS PUSH BUTTON		SIGN	EVP		
NO.	TYPE	STD PLATE	FDN TYPE STD PLATE	LENGTH	HEAD LOCATION	нт	M.A. LENGTH	MTD POSITION	FIXTURE	TYPE	MTD POSITION	NO.	MTD POSITION	TYPE			
$\langle \underline{i} \rangle$	MAST ARM POLE	IP	IP	IP	IP	IP	IP	IP	IP	IP	IP	1	90*	R10-3e		IP	
(2)	MAST ARM POLE	IP	IP	IP	IP	IP	IP	IP	IP	IP	IP	1	180°	R10-3e		IP	
3	PUSHBUTTON PEDESTAL	1260	1082	-	-	-	-	-	-	-	-	1	270°	R10-3e		_	
<b>(</b> 4 <b>)</b>	MAST ARM POLE	IP	IP	IP	IP	IP	IP	IP	IP	IP	IP	1	0°	R10-3e		IP	
(5)	PUSHBUTTON PEDESTAL	1260	1082	-	-	-	-	-	-	-	-	1	270°	R10-3e		-	
< <u>6</u> >	PEDESTAL POLE	IP	IP	-	-	-	-	-	-	IP	IP	1	0*	R10-3e		-	
$(\widehat{A})$	CABINET	IP	IP														
$(\widehat{B})$	SERVICE CABINET	IP	IP														
(Ĉ)	SOURCE OF POWER	IP	IP														


\04C			
:V MB /0:30 GL07 L7	NO.         DATE         BY         CHECK DESIGN REVISION / SUBMITTAL           Image: State	<b>AECOM</b> Kimley»Horn	C FO
sep, z		60% SUBMISSION - 09/28/15	DISCIPLIN

ALL SIGNAL EQUIPMENT ON THIS SHEET IS INPLACE & SHALL REMAIN INPLACE UNLESS OTHERWISE NOTED. A & DENOTES WORK TO BE COMPLETED BY THE CONTRACTOR.

## CIVIL EAST - VOLUME 10 SIGNAL PLAN - SIGNAL SYSTEM "P" CSAH 3 (EXCELSIOR BLVD) AND WHOLE FOODS DRIVEWAY - EQUIPMENT SCHEDULE TRAFFIC SHEET NAME: E3-TFC-SIG-EXC - 005



	DATE	RE	VISION			
/ '	<u> </u>	1				
	INTERSECTIO	NS				
	IL0228					
1			VC (1E) FOR			
lo if	· /		DUCT (2N,	1P, 1J)		
۳/ <i>/</i>	/	999 2" PVC 99 2" PVC				
if.	19	33 Z PVC	(ZN, IP)			
$\backslash$	1000	3" PVC (1J	<b>\</b>			
$\backslash$		3 PVC (1) 3" ROLL DU				
$\backslash \backslash$		2" PVC (1F)				
$\frown$		2" PVC (3N,				
$\backslash$		" PVC (2A,				
$\backslash$		SWEST (200 " PV( (2A,	)p, )	BARIAL		
		" PVC (2A,				
	C (2A, 2C	, 1F)				
PVC VC (	(EMPTY)					
	(MPTY)					
			N LAYOL SHOPPING			
			OF PUBLIC			
			ON DIVISIO			
	DRAWN: S	мм	SCALE	В		
	CHKD:		$1^{"}=40^{"}$	228		
	REV:	IDAI 1: IL0228.D	E:11/30/99	220		
		ILUZZO.U				
					<u> </u>	SHEET
_		-	T - VOLU	-		_
-	-					222
	•				WHOLE	OF
	S DRIVE	-WAY - I		URMA	TION ONLY	
NE:	TRA	AFFIC	SHEET NAME: E3-	<u>rfc-si</u> g	-EXC - 006	266



21 2015 08:08 am V:\3400\_ADC\CAD\SEGMENT E3\PLAN SHEETS\TRAFFIC\E3-TFC-SIG-EXC.dwg 1

 $\langle \widetilde{6} \rangle'$  INPLACE: MAST ARM POLE - SEE EQUIPMENT SCHEDULE X" NMC TO HH-5 W/

- PUSHBUTTON PEDESTAL SEE EQUIPMENT SCHEDULE F&I: X" NMC TO POLE BASE 6 W/
- $\langle \overline{\underline{8}} \rangle$  INPLACE: MAST ARM POLE - SEE EQUIPMENT SCHEDULE X" NMC TO HH-8 W/

▲ (9) PUSHBUTTON PEDESTAL – SEE EQUIPMENT SCHEDULE F&I: X" NMC TO POLE BASE 8 W/

NOTES:


- 1.) SEE DIVISION "SS" OF SPECIAL PROVISIONS FOR ACCESSIBLE PEDESTRIAN SIGNAL (APS).
- 2.) ONE APS PEDESTRIAN PUSH BUTTON WITH SIGN R10-3E (9"X15") SHALL BE INSTALLED ON SIGNAL MAST ARM 2, 3, AND 8 AND ON EACH PUSH BUTTON STATION AS DIRECTED BY THE ENGINEER FOR OPERATION AS SHOWN IN THE PHASING LAYOUT.
- 3.) PEDESTRIAN INDICATIONS SHALL BE ONE SECTION LED WITH COUNTDOWN TIMERS UTILIZING INTERNATIONAL SYMBOL (HAND AND WALKING PERSON) INDICATIONS. SEE SPECIAL PROVISIONS.
- 4.) THE CONTRACTOR SHALL PLACE COMMON BACK FILL AND RESTORE ALL DISTURBED TURF, CONCRETE OR BITUMINOUS WALK, ETC. TO ITS ORIGINAL CONDITION OR BETTER. ALL COSTS FOR THIS WORK SHALL BE INCIDENTAL.
- 5.) THE CONTRACTOR SHALL VERIFY ALL UTILITY LOCATIONS PRIOR TO CONSTRUCTION.
- 6.) EXACT LOCATIONS OF POLES AND BASES SHALL BE DETERMINED IN THE FIELD BY THE ENGINEER.
  7.) THIS PLAN SPECIFIES CONDUIT SIZES, TYPES, AND GENERAL LOCATIONS.
- THIS PLAN SPECIFIES CONDULT SIZES, TYPES, AND GENERAL LUCATIONS. THE EXACT LOCATION WILL BE DETERMINED IN THE FIELD. CONDUITS UNDER THE ROADWAY REQUIRE BORING.
- 8.) ALL NEW CONDUIT SHALL BE PVC SCHEDULE 80 OR HDPE SCHEDULE 80 AND SHALL CARRY 1/C #6 GREEN INSULATED GROUNDING CONDUCTOR AS SHOWN IN THE PLAN.
- 9.) FOR PAVEMENT MARKINGS, SEE SIGNING AND STRIPING PLANS.

 ▲ REMOVAL NOTES:
 1. EXISTING PEDESTRIAN SIGNAL HEADS ON MAST ARM 2, 3, 6, AND 8 TO BE REMOVED.
 2. EXISTING PEDESTRIAN PUSHBUTTONS ON MAST ARM 2, 3, 6,

AND 8 TO BE REMOVED.







۲ ۲	2T			]
<u>.</u>	G	Y	G	SIGNAL SYSTEM "Q" IS BEING MODIFIED TO PROVIDE PEDESTRIAN PUSH BUTTONS AND COUNTDOWN TIMERS.
	0			
	0	$\triangleleft$	$\triangleleft$	- SIGNAL SYSTEM OPERATIONS
	0			THE SIGNAL SYSTEM FLASH MODE IS ALL RED.
	0	$\rightarrow$	$\rightarrow$	- NORMAL OPERATION IS 3 PHASE.
		(		IL EAST - VOLUME 10
	010			

CIVIL EAS									
SIGNAL PLAN - S	SIGNAL SYSTEM "Q"	223							
CSAH 3 (EXCELSIOR BLVD) AND MARKET PLAZA									
	SHEET NAME: E3-TFC-SIG-EXC - 007	266							


LOOP D	ETECTOR	CHART
DESIGNATION	FUNCTION	LOCATION
D1-1	IP	IP
D1-2	IP	IP
D1-3	IP	IP
D1-4	IP	IP
D4-1	IP	IP
D4-2	IP	IP
D4-3	IP	IP
D4-4	IP	IP
D4-5	IP	IP

ALL SIGNAL EQUIPMENT ON THIS SHEET IS INPLACE & SHALL REMAIN INPLACE UNLESS OTHERWISE NOTED. A ▲ DENOTES WORK TO BE COMPLETED BY THE CONTRACTOR.

						EC		ENT SC	HEDU	LE							
	STRL	ICTURE		SIGNA	LUMINAIRE				SIGNAL HEAD BRACKETING		APS PUSH BUTTON		SIGN	EVP			
NO.	TYPE	STD PLATE	FDN TYPE STD PLATE	LENGTH	HEAD LOCATION	ΗТ	M.A. LENGTH	MTD POSITION	FIXTURE	TYPE	MTD POSITION	NO.	MTD POSITION	TYPE		EVP	
$\langle 1 \rangle$	PUSHBUTTON PEDESTAL	1260	1082	-	-	-	-	-	-	_	-	1	270 <b>°</b>	R10-3e		_	
(2)	MAST ARM POLE	IP	IP	IP	IP	IP	IP	IP	IP	IP	IP	1	90*	R10-3e		IP	
< <u>3</u>	MAST ARM POLE	IP	IP	IP	IP	IP	IP	IP	IP	IP	IP	1	270°	R10-3e		IP	
4	PUSHBUTTON PEDESTAL	1260	1082	-	-	-	-	-	-	-	-	1	180°	R10-3e		-	
(5)	PUSHBUTTON PEDESTAL	1260	1082	-	-	-	-	-	-	-	-	1	270 <b>°</b>	R10-3e		-	
< <u>6</u> >	MAST ARM POLE	IP	IP	IP	IP	IP	IP	IP	IP	IP	IP	-	-	-		IP	
$\langle 7 \rangle$	PUSHBUTTON PEDESTAL	1260	1082	-	-	-	-	-	-	-	-	1	0°	R10-3e		-	
< <u>8</u> >	MAST ARM POLE	IP	IP	IP	IP	IP	IP	IP	IP	IP	IP	1	270°	R10-3e		IP	
(9)	PUSHBUTTON PEDESTAL	1260	1082	-	-	_	-	-	-	_	-	1	0*	R10-3e		-	
$(\hat{A})$	CABINET	IP	IP														
$(\tilde{B})$	SERVICE CABINET	IP	IP														
(Ĉ)	SOURCE OF POWER	IP	IP														

1	NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL		<b>—</b>
							AECOM Kimley »Horn	C
-							60% SUBMISSION - 09/28/15	DISCIPL

CIVIL EAS	Γ - VOLUME 10	SHEET						
SIGNAL PLAN - S	SIGNAL SYSTEM "Q"	224						
CSAH 3 (EXCELSIOR BLVD) AND MARKET PLAZA - EQUIPMENT SCHEDULE								
	SHEET NAME: E3-TFC-SIG-EXC - 008	266						



NOTES:

3.)

5.)

6.)

7.)

9.)

2

CONSTRUCTION.

THE PLAN.

- 1.) TRAIL CROSSING WILL INCLUDE PASSIVE DETECTION FOR BICYCLES AND PEDESTRIANS. CONDUIT STUB OUTS FOR FUTURE PEDESTRIAN PUSH BUTTONS
- SHALL BE INSTALLED. ONE LED LUMINAIRE SHALL BE INSTALLED ON EACH MAST ARM LUMINAIRE SHAFT EXTENSION. SEE SPECIAL PROVISIONS.

LUMINAIRE SYMBOL IS SHOWN ROTATED ON THE PLAN TO INCREASE LEGIBILITY.

OF THE POWER FOR THE TRAFFIC SIGNAL SYSTEM WITH THE POWER COMPANY. THE CONTRACTOR SHALL VERIFY ALL UTILITY LOCATIONS PRIOR TO

4.) THE CONTRACTOR SHALL FURNISH AND INSTALL ONE BLANKOUT "STOP FOR PEDESTRIANS/BIKES" SIGN (24"X 24") ON THE MAST ARM OF MA-1 AND MA-2.

THE CONTRACTOR SHALL PLACE COMMON BACK FILL AND RESTORE ALL

DISTURBED TURF, CONCRETE OR BITUMINOUS WALK, ETC. TO ITS ORIGINAL CONDITION OR BETTER. ALL COSTS FOR THIS WORK SHALL BE INCIDENTAL. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING THE CONNECTION

8.) EXACT LOCATIONS OF HANDHOLES, POLES, DETECTION ZONES, CABINETS, AND


THIS PLAN SPECIFIES CONDUIT SIZES, TYPES, AND GENERAL LOCATIONS. THE

10.) ALL NEW CONDUIT SHALL BE PVC - SCHEDULE 80 OR HDPE SCHEDULE 80 AND SHALL CARRY 1/C #6 GREEN INSULATED GROUNDING CONDUCTOR AS SHOWN IN


MOUNTING POSITION SHALL BE 0 DEGREES.

BASES SHALL BE DETERMINED IN THE FIELD.

EXACT LOCATION WILL BE DETERMINED IN THE FIELD.







E3-TFC-SIG-CED - 001

N	IO. DATE	BY	CHECH	DESIGN	N REVISION / SUBMITTAL					
						]	<b>AECOM</b> Kimley »Horn			
										CE
									SOUTHWEST	CE
						]		METROPOLITAN	Green Line LRT Extension	
								METROPOLITAN	_	
							60% SUBMISSION - 09/28/15			DISCIPL
						7	00 /0 30 Divita 310 N - 09/20/15			1

	EQUIPMENT SCHEDULE														
	STRUCTURE				SIGNAL M.A.		LUMINAIRE			SIGNAL HEAD BRACKETING		APS PUSH BUTTON		SIGN	EVP
NO.	TYPE	STD PLATE	FDN TYPE STD PLATE	LENGTH	HEAD LOCATION	нт	M.A. LENGTH	MTD POSITION	FIXTURE	TYPE	MTD POSITION	NO.	MTD POSITION	TYPE	
$\langle 1 \rangle$	MAST ARM POLE	1224	SEE DETAIL	18'	0',7'	30'	0'	0°	LED	-	-	-	-	-	_
2	MAST ARM POLE	1224	SEE DETAIL	20'	0',7'	30'	0'	0.	LED	_	-	-	-	-	_
A	CABINET	Ρ	1071	I	-	-	-	-	-	-	-	-	_	_	_
B	SERVICE CABINET	3487		-	-	-	-	-	-	-	-	-	-	-	_
0	SOURCE OF POWER	-	XCEL POLE	-	_	-	-	-	-	-	-	-	-	-	_

	DATE	
		_
METROPOLITAN		
		_
60% SUBMISSION - 09/28/15		

<b>CIVIL EAST - VOLUME 10</b>								
SIGNAL PLAN - FLASHER SYSTEM "R"								
DAR LAKE PKWY AND KENILWORTH TRAIL								
EQUIPMENT SCHEDULE								
TRAFFIC E3-TFC-SIG-CED - 002	266							

### NOTES:

- 1.) SEE DIVISION "SS" OF SPECIAL PROVISIONS FOR EMERGENCY VEHICLE PREEMPTION (EVP) SYSTEM, VIDEO DETECTION SYSTEM, BATTERY BACK-UP SYSTEM, ACCESSIBLE PEDESTRIAN SIGNAL (APS), AND FIBER OPTIC COMMUNICATION EQUIPMENT.
- 2.) ONE APS PEDESTRIAN PUSH BUTTON WITH SIGN R10-3E (9"X15") SHALL BE INSTALLED ON SIGNAL MAST ARM POLE 4, EACH PEDESTAL POLE, AND ON EACH PUSH BUTTON STATION AS DIRECTED BY THE ENGINEER FOR OPERATION AS SHOWN IN THE PHASING LAYOUT.
- PEDESTRIAN INDICATIONS SHALL BE ONE SECTION LED WITH 3.) COUNTDOWN TIMERS UTILIZING INTERNATIONAL SYMBOL (HAND AND WALKING PERSON) INDICATIONS. SEE SPECIAL PROVISIONS.
- ONE LED LUMINAIRE SHALL BE INSTALLED ON EACH MAST ARM 4.) LUMINAIRE SHAFT EXTENSION. SEE SPECIAL PROVISIONS.
- LUMINAIRE SYMBOL IS SHOWN ROTATED ON THE PLAN TO 5.) INCREASE LEGIBILITY. MOUNTING POSITION SHALL BE 0 DEGREES
- THE CONTRACTOR SHALL INSTALL ONE VIDEO DETECTION CAMERA ON EACH DAVIT ARM. VIDEO DETECTION CAMERAS SHALL INCLUDE A 6-FT HEIGHT EXTENSION BRACKET. 6.)
- THE CONTRACTOR SHALL FURNISH AND INSTALL ONE R10-12 7.) SIGN (36"X42") ON POLE 1 AND THE MAST ARMS OF MA-4 AND MA-7.
- THE CONTRACTOR SHALL PLACE COMMON BACK FILL AND 8.) RESTORE ALL DISTURBED TURF, CONCRETE OR BITUMINOUS WALK, ETC. TO ITS ORIGINAL CONDITION OR BETTER. ALL COSTS FOR THIS WORK SHALL BE INCIDENTAL.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING 9.) THE CONNECTION OF THE POWER FOR THE TRAFFIC SIGNAL SYSTEM WITH THE POWER COMPANY.
- THE CONTRACTOR SHALL VERIFY ALL UTILITY LOCATIONS PRIOR 10.) TO CONSTRUCTION.
- 11.) EXACT LOCATIONS OF HAND HOLES, POLES, DETECTION ZONES, CABINETS, AND BASES SHALL BE DETERMINED IN THE FIELD. 12.) THIS PLAN SPECIFIES CONDUIT SIZES, TYPES, AND GENERAL
- LOCATIONS. THE EXACT LOCATION WILL BE DETERMINED IN THE FIELD. CONDUITS UNDER THE ROADWAY REQUIRE BORING.
- 13.) ALL NEW CONDUIT SHALL BE PVC SCHEDULE 80 OR HDPE SCHEDULE 80 AND SHALL CARRY 1/C #6 GREEN INSULATED GROUNDING CONDUCTOR AS SHOWN IN THE PLAN.
- 14.) ALL VEHICULAR SIGNAL INDICATIONS SHALL BE LED AND SHALL HAVE BACKGROUND SHIELDS. ALL POLE MOUNTED BRACKETING SHALL BE EXTENDED BRACKETING. SEE SPECIAL PROVISIONS
- 15.) THE CONTRACTOR SHALL FURNISH AND INSTALL ONE R9-3A SIGN (18"X18") ON POLES 7, 8, AND 9 FACING ROYALSTON AVE. N
- 16.) A 3/4 INCH HALF COUPLING, 3/4 INCH PIPE NIPPLE, AND CONDUIT OUTLET BODY FOR EMERGENCY VEHICLE PREEMPTION EQUIPMENT SHALL BE FURNISHED AND MOUNTED 6-FT FROM THE END OF EACH MAST ARM. SEE SIGNAL DETAILS FOR INSTALLATION OF EMERGENCY VEHICLE PREEMPTION EQUIPMENT.

CONTROLLER PHASING, PEDESTRIAN

INDICATIONS AND PUSH BUTTONS

 $\langle 2 \rangle$ 

P6-1

PB4-2

(5)

P2-1

6 2 PB2-1

PEDESTRIAN PUSH BUTTONS SHALL BE LOCATED AS SHOWN ABOVE

← PB6-1 PB4-1 H P84-1 P4-1

P4-2

 $\frac{4}{4}$ 

P2

PB2-:

—Ø6

AVE N

2-1, 2-2, 2-3, 2-4

4-1, 4-2, 4-3, 4-4

6-1, 6-2, 6-3, 6-4

L-1, L-2, L-3, L-4,

L-5, L-6, L-7, L-8

•

 $\ominus | \oplus (1) | \oplus$ 

**AECOM** Kimley»Horn

60% SUBMISSION - 09/28/15

(1) FLASHING LRT SIGNAL. PTS = PREPARE TO STOP ALL SIGNAL INDICATIONS SHALL BE 12" LED - ALL SIGNAL HEADS SHALL BE BLACK

POLYCARBONATE WITH BACKGROUND SHIELDS

z ST

HOLDEN

Ø4

P2-3


DATE BY CHECK DESIGN REVISION / SUBMITTA

(10)

(1) P6-2

₽ PB6-2 PB2-3 'P

- NOTES (CONT):
- 17.) OVERHEAD MAST ARM MOUNTED TYPE "D" SIGN PANELS SHALL BE INCIDENTAL
- 18.) FOR PAVEMENT MARKINGS, SEE SIGNING AND STRIPING PLANS.



ž
6 M
оо
Ř I
-SIG
FC-
4
Š
FFI
TR/
TS
SHEE
AN
PL
Н4
ENT
EGMI
SE ∕
CAD
6 am V:\3400_ADC\CAD\SEGMENT E4\PLAN SHEETS\TRAFFIC\E4-TFC-SIG-ROY.
8
/34
∻
Б
26
08:
21 2015 08:26
21
Sep,

PB2-

90

P2-4

Ø2

(A) CONTROLLER CABINET – SEE EQUIPMENT (2) PEDESTAL POLE – X" NMC TO HH–1	SEE EQUIPMENT SCHEDULE W/
CONTROLLER CABINET TO LRT XING HOUSE:	SEE EQUIPMENT SCHEDULE W/
B SERVICE CABINET - SEE EQUIPMENT SCHEDULE SERVICE CABINET TO SOURCE OF POWER: X" NMC W/	STAL – SEE EQUIPMENT BASE 4 W/
C SOURCE OF POWER X" NMC TO POLE E	SEE EQUIPMENT SCHEDULE BASE 7 W/
SCHEDULE '	
1-ONE WAY SINGLE INDICATOR LIGHT	
	SEE EQUIPMENT SCHEDULE OLLER CABINET W/
X" CONDUIT TO PO	-1 & L-2)-POLE MOUNTED
	B (SEE SYSTEM PLAN) –3 & L–4)–POLE MOUNTED LE BASE 9 W/
	6 (SEE SYSTEM PLAN) –5 & L–6)–POLE MOUNTED LE BASE 6 W/
RT TRACK 2     (13) OCS POLE E294110 2-LRT SIGNALS (L- X" CONDUIT TO PO	-7 & L-8)-POLE MOUNTED
	ter t
	0 10 20 40 SCALE IN FEET
SIGNAL SYSTEM OPERATIONS - THE SIGNAL SYSTEM FLAS - NORMAL OPERATION SHAL - SIGNAL SYSTEM SHALL BE	L BE 3 PHASE.
CIVIL EAST - VOLUME	-
SIGNAL PLAN - SIGNAL SYS ROYALSTON AVE AND HOL	
DISCIPLINE: TRAFFIC SHEET NAME: F4-TFC.	-SIG-ROY-001 266

SOUTHWEST


METROPOLITAN

						EG		ENT SC	HEDU	LE					
	STRU	ICTURE		SIGNAI	SIGNAL M.A.			LUMINAIRE				APS PUSH BUTTON		SIGN	EVP
NO.	NO. TYPE		FDN TYPE STD PLATE	LENGTH	HEAD LOCATION	ΗТ	M.A. LENGTH	MTD POSITION	FIXTURE	TYPE	MTD POSITION	NO.	MTD POSITION	TYPE	LVF
$\langle 1 \rangle$	PEDESTAL POLE	1266	1076	-	-	-	-	-	I	10B	180°	1	0*	R10-3e	-
2	PEDESTAL POLE	1266	1076	-	1	-	-	-	I	30A(L)	90°	1	270°	R10-3e	_
3	PEDESTAL POLE	1266	1076	-	-	-	-	-	I	10A 10B	0° 180°	1	0°	R10-3e	_
4	MAST ARM POLE	1224	1072	24'	1.3'	30'	0'	0'	LED	10B 10B	90° 180°	1	270 <b>°</b>	R10-3e	1-1 CHANNEL W/ INDICATOR LIGHT
(5)	PUSHBUTTON PEDESTAL	1260	1082	-	-	-	-	-	1	-	I	1	90°	R10-3e	-
6	PEDESTAL POLE	1266	1076	-	-	-	-	-	-	30A(R)	270 <b>°</b>	1	90*	R10-3e	-
$\overline{2}$	COMBINED OCS/MAST ARM POLE	SEE SYSTEM PLAN	SEE SYSTEM PLAN	18'	0'	30'	0'	0'	LED	10A 10A	90° 180°	-	-	R9-3a	1-1 CHANNEL W/ INDICATOR LIGHT
8	MAST ARM POLE	1224	1072	16'	0'	30'	0'	0'	LED	10B	180°	1	0*	R9—3a R10—3e	1-1 CHANNEL W/ INDICATOR LIGHT
9	PEDESTAL POLE	1266	1076	-	-	-	-	-	-	10B	0*	1	90*	R9—3a R10—3e	-
A	CABINET	Ρ	1071												
B	B SERVICE 3487		1071												
C SOURCE -			XCEL POLE												


ITERIS VIDEO DETECTOR CHART												
VIDEO CAMERA 1												
DESIGNATION	NO.	FUNCTION	LOCATION									
D2-1	VIDEO (V-3)	(1)	120'									
D2-2	VIDEO (V-3)	(1)	5'& 20'									
D2-3	VIDEO (V-3)	(1)	5'& 20'									
D4-1	VIDEO (V-1)	(1)	120'									
D4-2	VIDEO (V-1)	(1)	5'& 20'									
D6-1	VIDEO (V-2)	(1)	120'									
D6-2	VIDEO (V-2)	(1)	5'& 20'									
	LOCATION OF DETECTION ZONE: DISTANCE FROM CROSSWALK/STOP BAR IN FEET											

CALL AND EXTEND
 DELAY CALL AND IMMEDIATE EXTEND
 SYSTEM

SIGN	PANEL	FOR	MA-4	AND	MA-8



SIGN PANEL FOR MA-7



NOTES: 1.) SIGNS SHALL BE MOUNTED TO THE MAST ARM WITH STAINLESS BANDS AS DIRECTED BY THE ENGINEER. 2.) ALL SIGNING SHALL USE DG3 SHEETING. 3.) SIGN PANELS SHALL BE INCIDENTAL.

ATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL				1
					A=CON KITTIEY # HOT			
							SOUTHWEST	
						METROPOLITAN	Green Line LRT Extension	
							-	DISCIPI
					60% SUBMISSION - 09/28/15			
	TE	TE BY		TE BY CHECK DESIGN	TE BY CHECK DESIGN REVISION / SUBMITTAL		AECOM Kimley »Horn	


	CIVIL EAST - VOLUME 10								
SIGNAL PLAN - SIGNAL SYSTEM "S"									
	ROYALSTON AVE AND HOLDEN ST								
	EQUIPMENT SCHEDULE								
PLINE:	TRAFFIC	E4-TFC-SIG-ROY - 002	266						


### NOTES:

- 1.) SEE DIVISION "SS" OF SPECIAL PROVISIONS FOR EMERGENCY VEHICLE PREEMPTION (EVP) SYSTEM, VIDEO DETECTION SYSTEM, BATTERY BACK-UP SYSTEM, ACCESSIBLE PEDESTRIAN SIGNAL (APS), FIBER OPTIC COMMUNICATION EQUIPMENT, AND MATERIALS PROVIDED BY THE CITY OF MINNEAPOLIS.
- ONE APS PEDESTRIAN PUSH BUTTON WITH SIGN R10-3E (9"X15") 2.) SHALL BE INSTALLED ON EACH SIGNAL MAST ARM AND PEDESTAL POLE AND ON EACH PUSH BUTTON STATION AS DIRECTED BY THE ENGINEER FOR OPERATION AS SHOWN IN THE PHASING LAYOUT.
- 3.) PEDESTRIAN INDICATIONS SHALL BE ONE SECTION LED WITH COUNTDOWN TIMERS UTILIZING INTERNATIONAL SYMBOL (HAND AND WALKING PERSON) INDICATIONS. SEE SPECIAL PROVISIONS.
- ONE LED LUMINAIRE SHALL BE INSTALLED ON EACH MAST ARM 4.) LUMINAIRE SHAFT EXTENSION. SEE SPECIAL PROVISIONS.
- 5.) LUMINAIRE SYMBOL IS SHOWN ROTATED ON THE PLAN TO INCREASE LEGIBILITY. MOUNTING POSITION SHALL BE 0 DEGREES. THE CONTRACTOR SHALL INSTALL ONE VIDEO DETECTION CAMERA
- 6.) ON EACH DAVIT ARM. VIDEO DETECTION CAMERAS SHALL INCLUDE A 6-FT HEIGHT EXTENSION BRACKET.
- 7.) THE CONTRACTOR SHALL FURNISH AND INSTALL ONE R10-12 SIGN (36"X42") ON THE MAST ARM OF MA-6 AND MOUNTED TO SIGN BRACKET "D" AS DIRECTED BY THE ENGINEER.
- THE CONTRACTOR SHALL PLACE COMMON BACK FILL AND RESTORE 8.) ALL DISTURBED TURF, CONCRETE OR BITUMINOUS WALK, ETC. TO ITS ORIGINAL CONDITION OR BETTER. ALL COSTS FOR THIS WORK SHALL BE INCIDENTAL
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING THE 9.) CONNECTION OF THE POWER FOR THE TRAFFIC SIGNAL SYSTEM WITH THE POWER COMPANY.
- 10.) THE CONTRACTOR SHALL VERIFY ALL UTILITY LOCATIONS PRIOR TO CONSTRUCTION
- 11.) EXACT LOCATIONS OF HAND HOLES, POLES, DETECTION ZONES, CABINETS, AND BASES SHALL BE DETERMINED IN THE FIELD BY THE ENGINEER.
- 12.) THIS PLAN SPECIFIES CONDUIT SIZES, TYPES, AND GENERAL LOCATIONS. THE EXACT LOCATION WILL BE DETERMINED IN THE FIELD. CONDUITS UNDER THE ROADWAY REQUIRE BORING.
- 13.) ALL NEW CONDUIT SHALL BE PVC SCHEDULE 80 OR HDPE SCHEDULE 80 AND SHALL CARRY 1/C #6 GREEN INSULATED GROUNDING CONDUCTOR AS SHOWN IN THE PLAN.
- 14.) ALL VEHICULAR SIGNAL INDICATIONS SHALL BE LED AND SHALL HAVE BACKGROUND SHIELDS. ALL POLE MOUNTED BRACKETING SHALL BE EXTENDED BRACKETING. SEE SPECIAL PROVISIONS.
- 15.) A 3/4 INCH HALF COUPLING, 3/4 INCH PIPE NIPPLE, AND CONDUIT OUTLET BODY FOR EMERGENCY VEHICLE PREEMPTION EQUIPMENT SHALL BE FURNISHED AND MOUNTED 6-FT FROM THE END OF EACH MAST ARM. SEE SIGNAL DETAILS FOR INSTALLATION OF EMERGENCY VEHICLE PREEMPTION EQUIPMENT.
- 16.) OVERHEAD MAST ARM MOUNTED TYPE "D" SIGN PANELS SHALL BE INCIDENTAL
- 17.) FOR PAVEMENT MARKINGS, SEE SIGNING AND STRIPING PLANS. 18.) SEE INTERCONNECT PLAN FOR ADDITIONAL DETAIL.
- CONTROLLER PHASING, PEDESTRIAN INDICATIONS AND PUSH BUTTONS (6) ⊢● PB4-4 P4-4♥ NO SCALE (1) ₱ PB4-2 ↓ P4-2 — Ø2 7TH ST N Ø6 – P4-3 P4-1 P6-2 ② `₽₿4—3` P6−1  $\langle 4 \rangle$ 3 4 AN

- (A) CONTROLLER CABINET SEE EQUIPMENT SCHEDULE CONTROLLER CABINET TO HH-1: X" NMC W/
- B SERVICE CABINET SEE EQUIPMENT SCHEDULE SERVICE CABINET TO SOURCE OF POWER: X"NMC W/
- (C) SOURCE OF POWER X" NMC TO SERVICE CABINET W/

- 1 mast arm pole see equipment schedule 1–one way single channel evp detector WITH INDICATOR LIGHT 1-ONE VIDEO DETECTOR
- X" NMC TO CONTROLLER CABINET W/
- $\langle 2 \rangle$  MAST ARM POLE SEE EQUIPMENT SCHEDULE 1-ONE WAY SINGLE CHANNEL EVP DETECTOR WITH INDICATOR LIGHT -ONE VIDEO DETECTOR
  - X" NMC TO CONTROLLER CABINET W/





X" NMC TO HH-1 W/


e chart							
R Y G							
$\mathbf{\bullet}$							
SHALL BE 12" LED . BE BLACK CKGROUND SHIELDS	SIGNAL SYSTEM OPERATIONS - THE SIGNAL SYSTEM FLASH MODE IS ALL RED. - NORMAL OPERATION SHALL BE 3 PHASE. - SIGNAL SYSTEM SHALL BE FULLY ACTUATED.						
CIVII	EAST - VOLUME 10	SHEET					
SIGNAL PL	AN - SIGNAL SYSTEM "T"	230					
7TH ST N & 5TH AVE N							
	E4-TFC-SIG-7TH-001	266					

	EQUIPMENT SCHEDULE														
	STRU	ICTURE		SIGNA	_ M.A.					SIGNAL HEAD BRACKETING		APS PUSH BUTTON		SIGN	EVP
NO.	TYPE	STD PLATE	FDN TYPE STD PLATE	LENGTH	HEAD LOCATION	нт	M.A. LENGTH	MTD POSITION	FIXTURE	TYPE	TYPE POSITION		MTD POSITION	TYPE	LVF
$\langle 1 \rangle$	MAST ARM POLE	1231	1074	34'	0'	30'	0'	0*	LED	10B	180°	1	180 <b>°</b>	R10-3e	1-1 CHANNEL W/ INDICATOR LIGHT
2	MAST ARM POLE	1231	1074	28'	0'	30'	0'	0°	LED	10B 30A(L)	180° 90°	1	270 <b>°</b>	R10-3e	1-1 CHANNEL W/ INDICATOR LIGHT
3	PUSHBUTTON PEDESTAL	1260	1082	I	-	-	-	-	-	-	-	1	0*	R10-3e	-
4	PEDESTAL POLE	1266	1076	Ι	-	-	-	-	-	10B 30A(R)	0° 180°	2	0° 90°	R10-3e R10-3e	-
(5)	MAST ARM POLE	1231	1074	46'	0',12'	30'	0'	0*	LED	10A 10B	180° 90°	1	90°	R10-3e	1-1 CHANNEL W/ INDICATOR LIGHT
A	CABINET	Ρ	1071												
B	) SERVICE CABINET 3487														
0	SOURCE OF POWER	3487	XCEL VAULT												

ITERIS \	/IDEO DET	ECTOR	CHART					
VIDEO CAMERA 1								
DESIGNATION	NO.	FUNCTION	LOCATION					
D2-1	VIDEO (V-3)	(1)	120'					
D2-2	VIDEO (V-3)	(1)	120'					
D2-3	VIDEO (V-3)	(1)	5'& 20'					
D2-4	VIDEO (V-3)	(1)	5'& 20'					
D2-5	VIDEO (V-3)	(1)	5'& 20'					
D4-1	VIDEO (V-1)	(1)	120'					
D4-2	VIDEO (V-1)	(1)	5'& 20'					
D6-1	VIDEO (V-2)	(1)	120'					
D6-2	VIDEO (V-2)	(1)	120'					
D6-3	VIDEO (V-2)	(1)	5' & 20'					
D6-4	VIDEO (V-2)	(1)	5'& 20'					

LOCATION OF DETECTION ZONE: DISTANCE FROM CROSSWALK/STOP BAR IN FEET

(1) CALL AND EXTEND
 (2) DELAY CALL AND IMMEDIATE EXTEND
 (3) SYSTEM



SIGN PANEL FOR MA-2 AND MA-6

SIGN PANEL FOR MA-1




NOTES: 1.) SIGNS SHALL BE MOUNTED TO THE MAST ARM WITH STAINLESS BANDS AS DIRECTED BY THE ENGINEER. 2.) ALL SIGNING SHALL USE DG3 SHEETING. 3.) SIGN PANELS SHALL BE INCIDENTAL TO SIGNAL SYSTEM.


NO.	DATE	BV	CHECK	DESIGN	REVISION / SUBMITTAL				1
110.	DATE		ONEON						
								_	
						<b>AECOM</b> Kimley » Horr			
								SOUTHWEST	
							METROPOLITAN	Green Line LRT Extension	
						60% SUBMISSION - 09/28/15			DISCIPLIN

<b>CIVIL EAST - VOLUME 10</b>								
SIGNAL PLAN - SIGNAL SYSTEM "T"								
7TH ST N & 5TH AVE N								
EQUIPMENT SCHEDULE								
TRAFFIC	E4-TFC-SIG-7TH - 002	266						

### NOTES:

- 1.) SEE DIVISION "SS" OF SPECIAL PROVISIONS FOR ACCESSIBLE PEDESTRIAN SIGNAL (APS)
- ONE APS PEDESTRIAN PUSH BUTTON WITH SIGN R10-3E (9"X15") SHALL BE 2.) INSTALLED ON EACH SIGNAL MAST ARM AND ON EACH PUSH BUTTON STATION AS DIRECTED BY THE ENGINEER FOR OPERATION AS SHOWN IN THE PHASING I AYOUT
- PEDESTRIAN INDICATIONS SHALL BE ONE SECTION LED WITH COUNTDOWN TIMERS 3.) UTILIZING INTERNATIONAL SYMBOL (HAND AND WALKING PERSON) INDICATIONS. SEE SPECIAL PROVISIONS.
- THE CONTRACTOR SHALL PLACE COMMON BACK FILL AND RESTORE ALL DISTURBED TURF, CONCRETE OR BITUMINOUS WALK, ETC. TO ITS ORIGINAL 4.) CONDITION OR BETTER. ALL COSTS FOR THIS WORK SHALL BE INCIDENTAL.
- THE CONTRACTOR SHALL VERIFY ALL UTILITY LOCATIONS PRIOR TO 5.) CONSTRUCTION
- EXACT LOCATIONS OF HANDHOLES, POLES, DETECTION ZONES, CABINETS, AND BASES SHALL BE DETERMINED IN THE FIELD BY THE ENGINEER. 6.)
- 7.) THIS PLAN SPECIFIES CONDUIT SIZES, TYPES, AND GENERAL LOCATIONS. THE EXACT LOCATION WILL BE DETERMINED IN THE FIELD. CONDUITS UNDER THE ROADWAY REQUIRE BORING.
- ALL NEW CONDUIT SHALL BE PVC SCHEDULE 80 OR HDPE SCHEDULE 80 AND 8.) SHALL CARRY 1/C #6 GREEN INSULATED GROUNDING CONDUCTOR AS SHOWN IN THE PLAN.
- FOR PAVEMENT MARKINGS, SEE SIGNING AND STRIPING PLANS.
- 10.) THE CONTRACTOR SHALL FURNISH AND INSTALL ONE R9-3A SIGN (18"X18") ON POLES 1, 2 AND 4.
  - ▲ REMOVAL NOTES: EXISTING PEDESTAL POLE 7 IN EAST MEDIAN TO BE REMOVED. EXISTING CONDUIT RUNS BETWEEN MAST ARM 4 AND HH 5 TO BE 2.
  - REMOVED. 3. EXISTING CONDUIT RUNS BETWEEN MAST ARM 5 AND HH 5 TO BE
  - REMOVED. 4. EXISTING CONDUIT RUN BETWEEN PUSHBUTTON PEDESTAL 6 AND HH 5 TO BE REMOVED.
  - 5. EXISTING CONDUIT RUN BETWEEN PEDESTAL POLE 7 AND HH 6 TO BE ABANDONED INPLACE.
  - EXISTING CONDUIT RUN BETWEEN HH 6 AND DETECTION ZONE 1-2 TO BE ABANDONED INPLACE.
  - 7. EXISTING CONDUIT RUN BETWEEN HH 6 AND DETECTION ZONE 1-1 TO BE ABANDONED INPLACE.
  - EXISTING CONDUIT RUN BETWEEN CONTROLLER CABINET AND PEDESTAL 8. POLE 7 TO BE ABANDONED INPLACE. 9. EXISTING CONDUIT BETWEEN HH 6 AND HH 5 TO BE ABANDONED
  - INPLACE.
  - 10. EXISTING HH 5 IN NORTHEAST CORNER SHALL BE REMOVED. 11. EXISTING HH 6 IN EAST MEDIAN SHALL BE REMOVED.






PEDESTRIAN PUSH BUTTONS SHALL BE LOCATED AS SHOWN ABOVE NO DATE BY CHECK DESIGN REVISION / SUBMITTAL

		8-1, 8-2, 8-3	0	0	_
<b>AECOM</b> Kimley » Horn	METROPOLITAN			DUN	
60% SUBMISSION - 09/28/15			DI	ISCIPLINE:	

Ø5. Ø1



()

 $O \mid$ 

6-1, 6-2

6-3, 6-4


LOOP D	ETECTOR	CHART		
DESIGNATION	FUNCTION	LOCATION		
D1-1	IP	IP		
D1-2	IP	IP		
D4-1	IP	IP		
D4-2	IP	IP		
D5-1	IP	IP		
D5-2	IP	IP		
D8-1	IP	IP		
D8-2	IP	IP		
D8-3	IP	IP		

ALL SIGNAL E SHEET IS INPL	QUIPMENT ON THIS
OTHERWISE NO WORK TO BE CONTRACTOR.	QUIPMENT ON THIS ACE & SHALL CE UNLESS DTED. A DENOTES COMPLETED BY THE


						EG	UIPME	ENT SC	HEDU	LE						7
STRUCTURE SIGNAL M.A.							LUMINAIRE				_ HEAD KETING		S PUSH UTTON	SIGN	EVP	
NO.	TYPE	STD PLATE	FDN TYPE STD PLATE	LENGTH	HEAD LOCATION	нт	M.A. LENGTH	MTD POSITION	FIXTURE	TYPE	MTD POSITION	NO.	MTD POSITION	TYPE		
$\langle 1 \rangle$	MAST ARM POLE	IP	IP	IP	IP	IP	IP	IP	IP	IP	IP	1	270 <b>°</b>	R10-3e	-	
(2)	MAST ARM POLE	IP	IP	IP	IP	-	-	-	-	IP	IP	-	-	-	_	
(3)	PEDESTAL POLE	IP	IP	-	-	_	-	-	I	IP	IP	-	_	_	-	
(4)	MAST ARM POLE	IP	IP	IP	IP	IP	IP	IP	IP	IP	IP	1	0°	R10-3e	-	
(5)	MAST ARM POLE	IP	IP	IP	IP	-	-	-	-	IP	IP	1	270°	R10-3e	-	
(6)	PUSHBUTTON PEDESTAL	IP	IP	-	-	-	-	-	-	-	-	1	0*	R10-3e	-	
$\overline{\mathcal{O}}$	PEDESTAL POLE	1266	1076	-	-	-	-	-	-	10A	270 <b>°</b>	-	-	-	-	
(Â)	CABINET	IP	IP													
$(\widehat{B})$	SERVICE CABINET	IP	IP													
(Ĵ)	SOURCE OF POWER	IP	IP													

NO. DATE	E B		N REVISION / SUBMITTAL	<b>AECOM</b> Kimley»Horn	METROPOLITAN	SOUTHWEST Green Line Litt Extension	DUN
				60% SUBMISSION - 09/28/15			DISCIPLINE


CIVIL EAST - VOLUME 10							
SIGNAL PLAN - SYSTEM "U"							
NWOODY BLVD AND PARADE STADIUM DR EQUIPMENT SCHEDULE							
TRAFFIC SHEET NAME: E4-TFC-SIG-DUN - 002	266						



DATE	REVISION		
N 09-11-03 REVISED D	UNWOODY DRIVE		
12-28-12 PARADE D	R REBUILT, NEW CONDU	IIT, LIGHTS,	
HH'S, & LO	DOPS ON PARADE DR ON	LY; ALSO	
CONVERT	ED TO MICROSTATION 1/	4 SECT BKK	
EX 2" PVC (LTG) EX 2" PVC (LTG)	SVI		
PARADE STADIUM MINNEAPOLIS D TRAFFIC AND	CTION LAYOU A DR & DUNWOOE DEPT. OF PUBLIC W D PARKING SERVIC	Y BLVD ORKS ES	
DRAWN: DRM CHKD: -	SCALE 1" = 40'	B	
REV: BKK	DATE: 12-20-96	107	
FILENAME: TRAFFI	0_202924NE_1EX1	DGN	
	AST - VOLU	-	SHEET
SIGNAL P	IAN - SYSI		
	AND PARA	DE STADIUM	DR OF
	AND PARA ORMATION	DE STADIUM	DR




ES: EXACT LOCATION OF HANDHOLE FIELD. SEE SIGNAL PLANS FOR SIGNAL ALL HANDHOLES SHALL BE FIBI THE EQUIPMENT CALLED OUT O THE INTERCONNECT SYSTEM UN THIS PLAN SPECIFIES CONDUIT LOCATIONS. THE EXACT LOCATIN CONDUITS UNDER THE ROADWA	N THIS PLAN IS FOR INSTALLATION OF LESS OTHERWISE NOTED. SIZES, TYPES, AND GENERAL DN WILL BE DETERMINED IN THE FIELD.	
THE CONTRACTOR SHALL VERIF		
-	- VOLUME 10	SHEET
INTERCO	NNECT PLAN	235
		OF
TRAFFIC	SHEET NAME: E1-TFC-INT-01 - 001	266




; [	NO.	DATE	BY CHECK DESIGN	REVISION / SUBMITTAL					
					-				
Š -					-				
00						<b>ECOM</b> Kimley »Horn			
2						/		SOUTHWEST	
N L					_		METROPOLITAN	Green Line LRT Extension	
- -							C O U N C I L		DISCIPLINE:
ń.					-	60% SUBMISSION - 09/28/15			DISCIPLINE:
ñ L									


С 6.) Т	ONDUITS UNDER	SHALL VERIFY ALL UTILITY LOCATIONS PRIOR	
С	IVIL EAST	- VOLUME 10	SHEET
	INTERCO	NNECT PLAN	236
			OF
TF	RAFFIC	SHEET NAME: E2-TFC-INT-01 - 001	266

- NOTES:
  1.) EXACT LOCATION OF HANDHOLES SHALL BE DETERMINED IN THE FIELD.
  2.) SEE SIGNAL PLANS FOR SIGNAL CABINET AND SIGNAL EQUIPMENT.
  3.) ALL HANDHOLES SHALL BE FIBER OPTIC HANDHOLES.
  4.) THE EQUIPMENT CALLED OUT ON THIS PLAN IS FOR INSTALLATION OF THE INTERCONNECT SYSTEM UNLESS OTHERWISE NOTED.
  5.) THIS PLAN SPECIFIES CONDUIT SIZES, TYPES, AND GENERAL LOCATIONS. THE EXACT LOCATION WILL BE DETERMINED IN THE FIELD. CONDULTS. UNDER THE POADWAY PEODUCE






NAL SYSTEM "L" CONDUIT NMC W/	
NAL SYSTEM "L"	
NTROLLER CABINET NAL SYSTEM "L" CONDUIT	
NMC W/	
  L_	
230+00	
0100	
3001	
X	
	200
SCALE IN	FEET
NOTES:	
<ol> <li>EXACT LOCATION OF HANDHOLES SHALL BE DETERMINED IN TH FIELD.</li> </ol>	ΗE
<ol> <li>SEE SIGNAL PLANS FOR SIGNAL CABINET AND SIGNAL EQUIPM</li> <li>ALL HANDHOLES SHALL BE FIBER OPTIC HANDHOLES.</li> </ol>	ENT.
<ol> <li>THE EQUIPMENT CALLED OUT ON THIS PLAN IS FOR INSTALLA THE INTERCONNECT SYSTEM UNLESS OTHERWISE NOTED.</li> </ol>	TION OF
<ol> <li>THIS PLAN SPECIFIES CONDUIT SIZES, TYPES, AND GENERAL LOCATIONS. THE EXACT LOCATION WILL BE DETERMINED IN TH</li> </ol>	
CONDUITS UNDER THE ROADWAY REQUIRE BORING.	
<ol><li>THE CONTRACTOR SHALL VERIFY ALL UTILITY LOCATIONS PRIO CONSTRUCTION.</li></ol>	IX IU
	SHEET
INTERCONNECT PLAN	237
	0-
	OF
	266
TRAFFIC E2-TFC-INT-01 - 002	




NC	D. DATE	E BY CHECK DESIGN REVISION / SUBMITTAL			
			<b>AECOM</b> Kimley»Horn		
				METROPOLITAN	
			60% SUBMISSION - 09/28/15		DISCIPLIN

6.)	CONDUITS UNDER	XACT LOCATION WILL BE DETERMINED IN THE THE ROADWAY REQUIRE BORING. SHALL VERIFY ALL UTILITY LOCATIONS PRIOR	
	CIVIL EAS	Γ - VOLUME 10	SHEET
	INTERCONNECT PLAN		
			OF
:	TRAFFIC	SHEET NAME: E4-TFC-INT-01 - 001	266


- NOTES:
  1.) EXACT LOCATION OF HANDHOLES SHALL BE DETERMINED IN THE FIELD.
  2.) SEE SIGNAL PLANS FOR SIGNAL CABINET AND SIGNAL EQUIPMENT.
  3.) ALL HANDHOLES SHALL BE FIBER OPTIC HANDHOLES.
  4.) THE EQUIPMENT CALLED OUT ON THIS PLAN IS FOR INSTALLATION OF THE INTERCONNECT SYSTEM UNLESS OTHERWISE NOTED.
  5.) THIS PLAN SPECIFIES CONDUIT SIZES, TYPES, AND GENERAL LOCATIONS THE EXACT LOCATION WILL BE DETERMINED IN THE FIELD.






0 15 30 SCALE IN	60 FEET
KEYNOTES:	
1. CUSTOMER METERING ENCLOSURE.	
<u>GENERAL NOTES</u> : 1. DASHED LINES WITH ARROWHEAD D HOMERUN TO NEAREST COMMUNIC/ CABINET.	
CIVIL EAST - VOLUME 10	SHEE
DOWNTOWN HOPKINS STATION ELECTRICAL	239
SITE PLAN (1 OF 2)	OF
	266

E1-HOP-ELE-PLN-101




Sep, 21 2015 08:26 am V: \3400\_ADC\CAD\SEGMENT E1\PLAN SHEETS\ELECTRICAL\E1-HOP-ELE-PLN-102.dwg By: V-B




2. DASHED LINES WITH ARROWHEAD DENOTE HOMERUN TO NEAREST COMMUNICATION CABINET.

CIVIL EAST - VOLUME 10			
DOWNTOWN HOPKINS STATION			
SITE PLAN (2 OF 2)			
ELECTRICAL E1-HOP-ELE-PLN-102			





ELECTRICAL




E
0 15 30 60 SCALE IN FEET
KEYNOTES:

- 2. PROVIDE CCTV CAMERA ON THIS POLE AT 20'-0" A.F.F.
- 3. PROVIDE LICENSE PLATE READER (LPR) CAMERA ON THIS POLE AT 15'-0" A.F.F.


### GENERAL NOTES:

- 1. ALL LUMINAIRES NEAR FREIGHT CONDITIONS SHALL MAINTAIN A MINIMUM OF 25' CLEARANCE FROM FREIGHT CENTER LINE.
- 2. DASHED LINES WITH ARROWHEAD DENOTE HOMERUN TO NEAREST COMMUNICATION CABINET.


	CIVIL EAST - VOLUME 10		
	BLAKE STATION		
	ELECTRICAL SITE PLAN (2 OF 2)		
E:		SHEET NAME:	266
	ELECTRICAL	E1-BLK-ELE-PLN-102	




ep, 21 2015 02:16 pm V:\3400\_ADC\CAD\SEGMENT E2\PLAN SHEETS\ELECTRICAL\E2-LOU-ELE-PLN-101.dwg By: V-.




p. 21 2015 02:19 pm V:\3400\_ADC\CAD\SEGMENT E2\PLAN SHEETS\ELECTRICAL\E2-LOU-ELE-PLN-102.dwg By: V-Bec





Sep, 21 2015 11:46 am V:\3400\_ADC\CAD\SEGMENT E2\PLAN SHEETS\ELECTRICAL\E2-WDL-ELE-PLN-101.dwg By: V-BegeJ




		ENOTE ATION
CIVIL EAST - VOLUME 10		SHEET
BELTLINE STATION		246
ELECTRICAL		
	AN (1 OF 3)	OF
	E2-BLT-ELE-PLN-101	266









# CIVIL EAST - VOLUME 10 SHEET BELTLINE STATION 248 ELECTRICAL OF SITE PLAN (3 OF 3) 0F DISCIPLINE: ELECTRICAL 266



ieb. 21 2015 10:41 am V: \3400\_ADC\CAD\SEGMENT E3\PLAN SHEETS\ELECTRICAL\E3-WST-ELE-PLN-101.dwg By: V-BegeJB





DISCIPLINE:




# WEST LAKE STATION ELECTRICAL SITE PLAN (2 OF 3)


ELECTRICAL









v, 21 2015 10:43 am V:\3400\_ADC\CAD\SEGMENT E3\PLAN SHEETS\ELECTRICAL\E3-CHO-ELE-PLN-101.dwg By: V-B








NO.         DATE         BY         CHECK DESIGN REVISION / SUBMITTAL           Image: Constraint of the second sec	60% SUBMISSION - 09/28/15	METROPOLITAN SOUTHWEST	DISCIPI




## GENERAL NOTES:


1. TRACK 1 AND TRACK 2 NOT SHOWN FOR CLARITY.

CIVIL EAS	۲ - VOLUME 10	SHEET				
CEDAR LAKE PKWY						
	ELECTRICAL SITE PLAN					
	SHEET NAME: E3-CED-ELE-PLN-101	266				











Sep, 21 2015 10:57 am V:\3400\_ADC\CAD\SEGMENT E4\PLAN SHEETS\ELECTRICAL\E4-WAY-ELE-PLN-101.dwg By: V-B






NO.	DATE	BY CHECK DESIG	N REVISION / SUBMITTAL					
				AECOM	M-P Consultants			
					CONSULTING ENGINEERING MINNEAPOLIS ⊀ MINNESOTA		SOUTHWEST	
						METROBOLITAN	Green Line LRT Extension	
						METROPOLITAN		
				60% SUBMISS	SION - 09/28/15			DISCIPLINE
				00 /8 SOBINISC	SICIN - 09/20/15			


	CIVIL EAS	Γ - VOLUME 10	SHEET					
	WAYZATA BLVD/PENN AVE							
	ELECTRICAL SITE PLAN (2 OF 2)							
NE:	ELECTRICAL	SHEET NAME: E4-WAY-ELE-PLN-102	266					




	I		Г	` <b>L</b> /	41
-	-	le.	100		ME·




21 2015 11:14 am V:\3400\_ADC\CAD\SEGMENT E4\PLAN SHEETS\ELECTRICAL\E4-DUN-ELE-PLN-101.dwg By: V-




3400_AUC\CAD\SEGMENI E4 \PLAN										
	NO. DA	TE BY	CHECK	DESIGN	REVISION / SUBMITTAL					
21:11 C						AECOM	MP Consultants consulting engineering minneapolis < minnesota		SOUTHWEST	
107. LZ								METROPOLITAN	Green Line LRT Extension	DISCIPLI
, kep,						60% SUBMIS	SION - 09/28/15			




Sep, 21 2015 11:22 am V:\3400\_ADC\CAD\SEGMENT E4\PLAN SHEETS\ELECTRICAL\E4-BOR-ELE-PLN-101.dwg BY: V-BegeJE






ep, 21 2015 12:30 pm V:\3400\_ADC\CAD\SEGMENT E4\PLAN SHEETS\ELECTRICAL\E4-R0Y-ELE-PLN-101.dwg By: V-Bege



3, 21 2015 11:25 am V:\3400\_ADC\CAD\SEGMENT E4\PLAN SHEETS\ELECTRICAL\E4-ROY-ELE-PLN-102.dwg B



		IVI	LUMINAIRE	30C-1000-4K-T3M-MVOLT-PE-DBLXD	GASKETED. ZINK-INFUSED SUPER DURABLE TGIC THERMOSET POWDER COAT FINISH.	DISTRIBUTION	SCHEDULE	LUMENS	1000mA	SURFACE	BL
	(1)	)	IMINAIF	RE SCHEDULE		_					
NO.	DATE	BY	CHECK DESIGN	N REVISION / SUBMITTAL							
							A=C			nsultants	
									C O N S U L T M I N N E A P	ING ENGINE OLIS KMINNE	ERING ESOTA
		-					60%	SUBMIS	SION - 0	9/28/15	

TYPE	DESCRIPTION	MANUFACTURER	HOUSING	OPTICS	VOLTAGE	LAMP TYPE	DRIVER	MOUNTING	FINISH
A	SINGLE HEAD POLE MOUNTED LUMINAIRE	PHILIPS GARDCO ECOFORM ECF-1-3-75LA-4853-CW-UNV-BLP-	ONE PIECE DIE CAST ALUMINUM HOUSING, ONE PIECE DIE CAST DOOR FRAME, ELECTROSTATICALLY APPLIED POWDER COAT FNISH, IP66 RATED, 120-277V	TYPE III DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 8753 LUMENS	530mA	20' POLE	BLACK
в	SINGLE HEAD POLE MOUNTED LUMINAIRE	PHILIPS GARDCO ECOFORM ECF-1-4-55LA-3253-CW-UNV-BLP-	ONE PIECE DIE CAST ALUMINUM HOUSING, ONE PIECE DIE CAST DOOR FRAME, ELECTROSTATICALLY APPLIED POWDER COAT FINISH, IP66 RATED, 120-277V	TYPE N DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 5823 LUMENS	530mA	20' POLE	BLACK
С	SINGLE HEAD POLE MOUNTED LUMINAIRE	PHILIPS GARDCO ECOFORM ECF-1-2-55LA-3253-CW-UNV-BLP-	ONE PIECE DIE CAST ALUMINUM HOUSING, ONE PIECE DIE CAST DOOR FRAME, ELECTROSTATICALLY APPLIED POWDER COAT FINISH, IP66 RATED, 120-277V	Type II Distribution	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 5994 LUMENS	530mA	15' POLE	BLACK
D	SINGLE HEAD POLE MOUNTED LUMINAIRE	PHILIPS GARDCO ECOFORM ECF-1-4-75LA-4853-CW-UNV-BLP-	ONE PIECE DIE CAST ALUMINUM HOUSING, ONE PIECE DIE CAST DOOR FRAME, ELECTROSTATICALLY APPLIED POWDER COAT FINISH, IP66 RATED, 120-277V	TYPE N DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 8646 LUMENS	530mA	20' POLE	BLACK
E	SINGLE HEAD UTILITY POLE MOUNTED LUMINAIRE	PHILIPS GARDCO ECOFORM EC- 1-2-100LA-4853-CW-UNV-BLP-	ONE PIECE DIE CAST ALUMINUM HOUSING, ONE PIECE DIE CAST DOOR FRAME, ELECTROSTATICALLY APPLIED POWDER COAT FINISH, IP66 RATED, 120-277V	Type II Distribution	SEE PANELBOARD SCHEDULE	LED, COOL WHITE, 11896 LUMENS	530mA	20' POLE	BLACK
F	SINGLE HEAD POLE MOUNTED LUMINAIRE	PHILIPS GARDCO ECOFORM ECF-1-4-160LA-481A-CW-UNV-BLP-	ONE PIECE DIE CAST ALUMINUM HOUSING, ONE PIECE DIE CAST DOOR FRAME, ELECTROSTATICALLY APPLIED POWDER COAT FNISH, IP66 RATED, 120-277V	TYPE N DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 14955 LUMENS	1050mA	20' POLE	BLACK
G1	SINGLE HEAD POLE MOUNTED LUMINAIRE	PHILIPS GARDCO ECOFORM ECF-1-4-100LA-6453-CW-UNV-BLP-	ONE PIECE DIE CAST ALUMINUM HOUSING, ONE PIECE DIE CAST DOOR FRAME, ELECTROSTATICALLY APPLIED POWDER COAT FINISH, IP66 RATED, 120-277V	TYPE IV DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 11558 LUMENS	530mA	20' POLE	BLACK
G2	SINGLE HEAD POLE MOUNTED LUMINAIRE	PHILIPS GARDCO ECOFORM ECF-1-4-100LA-6453-CW-UNV-BLP-	ONE PIECE DIE CAST ALUMINUM HOUSING, ONE PIECE DIE CAST DOOR FRAME, ELECTROSTATICALLY APPLIED POWDER COAT FINISH, IP66 RATED, 120-277V	TYPE N DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 11558 LUMENS	530mA	15' POLE	BLACK
Н	SINGLE HEAD POLE MOUNTED LUMINAIRE	PHILIPS GARDCO ECOFORM ECF-1-2-70LA-3270-CW-UNV-BLP-	ONE PIECE DIE CAST ALUMINUM HOUSING, ONE PIECE DIE CAST DOOR FRAME, ELECTROSTATICALLY APPLIED POWDER COAT FINISH, IP66 RATED, 120-277V	TYPE II DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 7385 LUMENS	700mA	15' POLE	BLACK
I	SINGLE HEAD POLE MOUNTED LUMINAIRE	PHILIPS GARDCO ECOFORM ECF-1-4-70LA-3270-CW-UNV-BLP-	ONE PIECE DIE CAST ALUMINUM HOUSING, ONE PIECE DIE CAST DOOR FRAME, ELECTROSTATICALLY APPLIED POWDER COAT FINISH, IP66 RATED, 120-277V	TYPE N DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 7293 LUMENS	700mA	15' POLE	BLACK
J	SINGLE HEAD POLE MOUNTED LUMINAIRE	PHILIPS GARDCO ECOFORM ECF-1-3-100LA-6453-CW-UNV-BLP-	ONE PIECE DIE CAST ALUMINUM HOUSING, ONE PIECE DIE CAST DOOR FRAME, ELECTROSTATICALLY APPLIED POWDER COAT FINISH, IP66 RATED, 120-277V	TYPE III DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 11700 LUMENS	530mA	20' POLE	BLACK
к	TWIN HEAD POLE MOUNTED LUMINAIRE	PHILIPS GARDCO ECOFORM ECF-2@90-4-100LA-6453-CW-UNV-BLP-	ONE PIECE DIE CAST ALUMINUM HOUSING, ONE PIECE DIE CAST DOOR FRAME, ELECTROSTATICALLY APPLIED POWDER COAT FINISH, 1966 RATED, 120-277V	TYPE IV DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 11558 LUMENS EACH	530mA	20' POLE	BLACK
L	TWIN HEAD POLE MOUNTED LUMINAIRE	PHILIPS GARDCO ECOFORM ECF-2@90-4-160LA-481A-CW-UNV-BLP-	ONE PIECE DIE CAST ALUMINUM HOUSING, ONE PIECE DIE CAST DOOR FRAME, ELECTROSTATICALLY APPLIED POWDER COAT FINISH, 1966 RATED, 120-277V	TYPE IV DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 14955 LUMENS EACH	1050mA	20' POLE	BLACK
М	WALLPACK LUMINAIRE	LITHONIA TWH LED TWHLED- 30C-1000-4K-T3M-MVOLT-PE-DBLXD	DIE CAST ALUMINUM HOUSING HAS AN IMPACT-RESISTANT, TEMPERED GLASS LENS THAT IS FULLY GASKETED.ZINK-INFUSED SUPER DURABLE TGIC THERMOSET POWDER COAT FINISH.	TYPE III MEDIUM DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 6391 LUMENS	1000mA	SURFACE	BLACK

CIVIL EAST - VOLUME 10	SHEET					
ELECTRICAL						
LUMINAIRE SCHEDULE 1 OF 3						
INE: SHEET NAME: ELECTRICAL E0-ELE-SITE-SCH-501	266					

	$\cup$					
NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL	



AECOM



## LUMINAIRE SCHEDULE

TYPE	DESCRIPTION	MANUFACTURER	HOUSING	OP TIC S	VOLTAGE	LAMP TYPE	DRIVER	MOUNTING	FINISH
N	SINGLE HEAD POLE MOUNTED LUMINARE	PHILIPS GARDCO ECOFORM ECF-1-5-160LA-481A-CW-UNV-BLP-	ONE PIECE DIE CAST ALUMINUM HOUSING, ONE PIECE DIE CAST DOOR FRAME, ELECTROSTATICALLY APPLIED POWDER COAT FINISH, IP66 RATED, 120-277V	TYPE V DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 14465 LUMENS	1050mA	20' POLE	BLACK
0	POST TOP POLE MOUNTED LUMINAIRE	HOLOPHANE PTUE-70-4K-AS-P3-B-S	CAST ALUMINUM HOUSING, ASYMMETRIC POLYCARBONATE REFRACTOR, GASKETED, 4000K, SPIKE FINIAL, SUPFITTER, 120-277V	TYPE V DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 5183 LUMENS	350mA	15' POLE	BLACK
Ρ			NOT USED						BLACK
Q	POST TOP POLE MOUNTED LUMINARE	HOLOPHANE PTUE-70-4K-AS-P3-B-S	CAST ALUMINUM HOUSING, ASYMMETRIC POLYCARBONATE REFRACTOR, GASKETED, 4000K, SPIKE FINIAL, SLIPFITTER, 120-277V	TYPE II DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 5427 LUMENS	530mA	15' POLE	BLACK
R	POST TOP POLE MOUNTED LUMINAIRE	HOLOPHANE PTUE-70-4K-AS-P3-B-S	CAST ALUMINUM HOUSING, ASYMMETRIC POLYCARBONATE REFRACTOR, GASKETED, 4000K, SPIKE FINIAL, SLIPFITTER, 120-277V	TYPE IV DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 5736 LUMENS	530mA	15' POLE	BLACK
S	TWN HEAD POLE MOUNTED LUMINARE	PHILIPS GARDCO ECOFORM ECF-2@90-4-55LA-3253-CW-UNV-BLP-	ONE PIECE DIE CAST ALUMINUM HOUSING, ONE PIECE DIE CAST DOOR FRAME, ELECTROSTATICALLY APPLIED POWDER COAT FINISH, IP66 RATED, 120-277V	TYPE IV DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 5823 LUMENS EACH	530mA	15' POLE	BLACK
Т	TWIN HEAD POLE MOUNTED LUMINAIRE	PHILIPS GARDCO ECOFORM ECF-2@90-2-55LA-3253-CW-UNV-BLP-	ONE PIECE DIE CAST ALUMINUM HOUSING, ONE PIECE DIE CAST DOOR FRAME, ELECTROSTATICALLY APPUED POWDER COAT FINISH, IP66 RATED, 120-277V	TYPE II DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 5994 LUMENS EACH	530mA	15' POLE	BLACK
U	SINGLE HEAD POLE MOUNTED LUMINARE	PHILIPS GARDCO ECOFORM ECF-1-105LA-4870-CW-UNV-BLP-	ONE PIECE DIE CAST ALUMINUM HOUSING, ONE PIECE DIE CAST DOOR FRAME, ELECTROSTATICALLY APPLIED POWDER COAT FINISH, IP66 RATED, 120-277V	TYPE V DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 10494 LUMENS	700mA	20' POLE	BLACK
V	SINGLE HEAD POLE MOUNTED LUMINAIRE			TYPE II DISTRIBUTION	SEE PANELBOARD SCHEDULE	250W HIGH PRESSURE SODIUM	N/A	20' POLE	BLACK
W	TWN HEAD POLE MOUNTED LUMINARE	PHILIPS GARDCO ECOFORM ECF-2@90-3-70LA-3270-CW-UNV-BLP-	ONE PIECE DIE CAST ALUMINUM HOUSING, ONE PIECE DIE CAST DOOR FRAME, ELECTROSTATICALLY APPLIED POWDER COAT FINISH, IP66 RATED, 120-277V	TYPE III DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED/COOL WHITE, 7576 LUMENS	700mA	15' POLE	BLACK
Y	Wallpack Luminaire			UP AND DOWN DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED		WALL	BLACK
Z	WALLPACK LUMINAIRE			DOWN DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED		WALL	BLACK
A1	RECESSED CAN LUMINAIRE			WIDE DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED		RECESSED	WHITE TRIM

	CIVIL EAST	Γ - VOLUME 10	SHEET					
	ELECTRICAL							
	2	OF 3						
NE:	ELECTRICAL	SHEET NAME: E0-ELE-SITE-SCH-502	266					

TYPE	DESCRIPTION	MANUFACTURER	HOUSING	OP TIC S	VOLTAGE	LAMP TYPE	DRIVER	MOUNTING	FINISH
B1	WALLPACK LUMINAIRE			UP AND DOWN DISTRIBUTION	SEE PANELBOARD SCHEDULE	LED		WALL	ALUMINUM
C1	LINEAR LUMINAIRE			N/A	SEE PANELBOARD SCHEDULE	LED		SURFACE	WHITE
D1	LINEAR LUMINAIRE			N/A	SEE PANELBOARD SCHEDULE	LED		RECESSED	WHITE TRIM
E1	2X2 LUMINAIRE			N/A	SEE PANELBOARD SCHEDULE	LED		RECESSED	WHITE TRIM

## 1 LUMINAIRE SCHEDULE

L						
NC	DATE BY CHECK DESIGN REVISION / SUBMITTAL			<b>CIVIL EAST - VOLUME 10</b>	SHEET	
				ELECTRICAL	266D	
_		ACCOM		LUMINAIRE SCHEDULE		
			METROPOLITAN	3 OF 3	OF	
-				DISCIPLINE: SHEET NAME:	266	
		60% SUBMISSION - 09/28/15		ELECTRICAL E0-ELE-SITE-SCH-50	3	